

Chapter

Gaseous state

The state of matter in which the molecular forces of attraction between the particles of matter are minimum, is known as *gaseous state*. It is the simplest state and shows great uniformity in behaviour.

Characteristics of gases

- (1) Gases or their mixtures are homogeneous in composition.
- (2) Gases have very low density due to negligible intermolecular forces.
- (3) Gases have infinite expansibility and high compressibility.
 - (4) Gases exert pressure.
 - (5) Gases possess high diffusibility.
- (6) Gases do not have definite shape and volume like liquids.
- (7) Gaseous molecules move very rapidly in all directions in a random manner i.e., gases have highest kinetic energy.
- (8) Gaseous molecules collide with one another and also with the walls of container with perfectly *elastic* collisions.
- (9) Gases can be liquified, if subjected to low temperatures (below critical) or high pressures.
- (10) Thermal energy of gases >> molecular attraction.
- (11) Gases undergo similar change with the change of temperature and pressure. In other words, gases obey certain laws known as *gas laws*.

Measurable properties of gases

(1) The characteristics of gases are described fully in terms of four parameters or measurable properties :

- (i) The volume, *V*, of the gas.
- (ii) Its pressure, P
- (iii) Its temperature, T
- (iv) The amount of the gas (*i.e.*, mass or number of moles).
- (2) **Volume:** (i) Since gases occupy the entire space available to them, the measurement of volume of a gas only requires a measurement of the container confining the gas.
- (ii) Volume is expressed in litres (L), millilitres (mL) or cubic centimetres (cm^3) or cubic metres (m^3).

(iii)
$$1L = 1000 \ mL$$
; $1mL = 10^{-3} L$; $1L = 1 \ dm^3 = 10^{-3} m^3$
 $1m^3 = 10^3 \ dm^3 = 10^6 \ cm^3 = 10^6 \ mL = 10^3 \ L$

- (3) Mass: (i) The mass of a gas can be determined by weighing the container in which the gas is enclosed and again weighing the container after removing the gas. The difference between the two weights gives the mass of the gas.
- (ii) The mass of the gas is related to the number of moles of the gas *i.e.*

moles of gas (n) =
$$\frac{\text{Mass in grams}}{\text{Molar mass}} = \frac{m}{M}$$

- (4) **Temperature :** (i) Gases expand on increasing the temperature. If temperature is increased twice, the square of the velocity (v^2) also increases two times.
- (ii) Temperature is measured in centigrade degree (^{o}C) or celsius degree with the help of

thermometers. Temperature is also measured in Fahrenheit (F°) .

(iii) S.I. unit of temperature is kelvin (K) or absolute degree.

$$K = {}^{o}C + 273$$

- (iv) Relation between F and ${}^{o}C$ is $\frac{{}^{o}C}{5} = \frac{F^{o} 32}{9}$
- (5) **Pressure :** (i) Pressure of the gas is the force exerted by the gas per unit area of the walls of the container in all directions. Thus, Pressure $(P) = \frac{\text{Force}(F)}{A \cos(A)} = \frac{\text{Mass}(m) \times \text{Acceleration}(a)}{A \cos(A)}$
- (ii) Pressure exerted by a gas is due to kinetic energy ($KE = \frac{1}{2}mv^2$) of the molecules. Kinetic energy of the gas molecules increases, as the temperature is increased. Thus, *Pressure of a gas \alpha Temperature (T)*.
- (iii) Pressure of a pure gas is measured by manometer while that of a mixture of gases by barometer.
 - (iv) Commonly two types of manometers are used,
- (a) Open end manometer; (b) Closed end manometer
- (v) The S.I. unit of pressure, the pascal (*Pa*), is defined as 1 newton per *metre square*. It is very small unit.

$$1Pa = 1Nm^{-2} = 1 kg m^{-1} s^{-2}$$

- (vi) C.G.S. unit of pressure is dynes cm^{-2} .
- (vii) M.K.S. unit of pressure is kgf/m^2 . The unit kgf/cm^2 sometime called *ata* (atmosphere technical absolute).
 - (viii) Higher unit of pressure is *bar*, *KPa* or *MPa*. $1bar = 10^5 Pa = 10^5 Nm^{-2} = 100 KNm^{-2} = 100 KPa$
 - (ix) Several other units used for pressure are,

1				
Name	Symbol	Value		
bar	bar	$1bar = 10^5 Pa$		
atmosphe re	atm	$1 atm = 1.01325 \times 10^5 Pa$		
Torr	Torr	$1Torr = \frac{101325}{760}Pa = 133.322Pa$		
millimetr	mm <i>Hg</i>	1 mm Hg = 133.322 Pa		
e of				
mercury				

(x) The pressure relative to the atmosphere is called *gauge pressure*. The pressure relative to the perfect vacuum is called *absolute pressure*.

Absolute pressure = Gauge pressure + Atmosphere pressure.

(xi) When the pressure in a system is less than atmospheric pressure, the gauge pressure becomes negative, but is frequently designated and called vacuum. For example, 16 *cm* vacuum will be

$$\frac{76-16}{76} \times 1.013 = 0.80 \, bar .$$

(xii) If 'h' is the height of the fluid in a column or the difference in the heights of the fluid columns in the two limbs of the manometer, d is the density of the fluid

 $(Hg = 13.6 \times 10^3 \ Kg/m^3 = 13.6 \ g/cm^3)$ and g is the gravity, then pressure is given by, $P_{\rm gas} = P_{\rm atm} + h dg$

(xiii) Two sets of conditions are widely used as 'standard' values for reporting data.

Condition	Т	P	V _m (Molar volume)
S.T.P./N.T. P.	273.15 K	1 atm	22.414 L
S.A.T.P*.	298.15 K	1 bar	24.800 L

* Standard ambient temperature and pressure.


Boyle's law

- (1) In 1662, *Robert Boyle* discovered the first of several relationships among gas variables (*P*, *T*, *V*).
- (2) It states that, "For a fixed amount of a gas at constant temperature, the gas volume is inversely proportional to the gas pressure."

Thus, $P \propto 1/V$ at constant temperature and mass

or
$$P=K/V$$
 (where K is constant) or $PV=K$ or $P_1V_1=P_2V_2=K$ (For two or more gases)

(3) Graphical representation of Boyle's law: Graph between P and V at constant temperature is called **isotherm** and is an equilateral (or rectangular) hyperbola. By plotting P versus 1/V, this hyperbola can be converted to a straight line. Other types of isotherms are also shown below,



(4) At constant mass and temperature density of a gas is directly proportional to its pressure and inversely proportional to its volume.

Thus,
$$d \propto P \propto \frac{1}{V}$$
 $\left[\because V = \frac{\text{mass}}{d}\right]$ or $\frac{d_1}{d_2} = \frac{P_1}{P_2} = \frac{V_2}{V_1} = \dots = K$

(5) At altitudes, as P is low d of air is less. That is why mountaineers carry oxygen cylinders.

Charle's law

- (1) French chemist, *Jacques Charles* first studied variation of volume with temperature, in 1787.
- (2) It states that, "The volume of a given mass of a gas is directly proportional to the absolute temperature $(= {}^{\circ}C + 273)$ at constant pressure".

Thus, $V \propto T$ at constant pressure and mass or $V = KT = K(t(^{\circ}C) + 273.15)$, (where k

constant),

$$K = \frac{V}{T}$$
 or $\frac{V_1}{T_1} = \frac{V_2}{T_2} = K$ (For two or more gases)

(3) If
$$t = 0^{\circ} C$$
, then $V = V_0$

hence,
$$V_0 = K \times 273.15$$

$$K = \frac{V_0}{273.15}$$


$$V = \frac{V_0}{273.15} [t + 273.15] = V_0 \left[1 + \frac{t}{273.15} \right] = V_0 [1 + \alpha_v t]$$

where α_{v} is the volume coefficient,

$$\alpha_{v} = \frac{V - V_0}{tV_0} = \frac{1}{273.15} = 3.661 \times 10^{-3} \, {}^{o}C^{-1}$$

Thus, for every 1^o change in temperature, the volume of a gas changes by $\frac{1}{273.15} \left(\approx \frac{1}{273} \right)$ of the volume at $0^o C$.

(4) *Graphical representation of Charle's law*: Graph between V and T at constant pressure is called *isobar or isoplestics* and is always a straight line. A plot of V versus $t(^{\circ}C)$ at constant pressure is a straight line cutting the temperature axis at $-273.15^{\circ}C$. It is the lowest possible temperature.



(5) At constant mass and pressure density of a gas is inversely proportional to it absolute temperature.

Thus,
$$d \propto \frac{1}{T} \propto \frac{1}{V} \quad \left[\because V = \frac{\text{mass}}{\text{d}} \right]$$

or
$$\frac{d_1}{d_2} = \frac{T_2}{T_1} = \frac{V_2}{V_1} = \dots = K$$

(6) Use of hot air balloons in sports and meteorological observations is an application of Charle's law.

Gay-Lussac's law (Amonton's law)

- (1) In 1802, French chemist *Joseph Gay-Lussac* studied the variation of pressure with temperature and extende the Charle's law so, this law is also called Charle's-Gay Lussac's law.
- (2) It states that, "The pressure of a given mass of a gas is directly proportional to the absolute temperature (= $^{\circ}C + 273$) at constant volume."

Thus, $P \propto T$ at constant volume and mass

or
$$P = KT = K(t(^{\circ}C) + 273.15)$$
 (where *K* is constant)

$$K = \frac{P}{T}$$
 or $\frac{P_1}{T_1} = \frac{P_2}{T_2} = K$ (For two or more gases)

(3) If
$$t = 0^{\circ} C$$
, then $P = P_0$

Hence,
$$P_0 = K \times 273.15$$

$$K = \frac{P_0}{273.15}$$


$$P = \frac{P_0}{273.15}[t + 273.15] = P_0 \left[1 + \frac{t}{273.15} \right] = P_0 [1 + \alpha t]$$

where α_P is the pressure coefficient,

$$\alpha_P = \frac{P - P_0}{tP_0} = \frac{1}{273.15} = 3.661 \times 10^{-3} \, {}^{o}C^{-1}$$

Thus, for every 1^o change in temperature, the pressure of a gas changes by $\frac{1}{273.15} \left(\approx \frac{1}{273} \right)$ of the pressure at $0^o C$.

- (4) This law fails at low temperatures, because the volume of the gas molecules be come significant.
- (5) Graphical representation of Gay-Lussac's law: A graph between P and T at constant V is called isochore.



Avogadro's law

(1) According to this law, "Equal volumes of any two gases at the same temperature and pressure contain the same number of molecules."

Thus, $V \propto n$ (at constant T and P)

or V = Kn (where *K* is constant)

or
$$\frac{V_1}{n_1} = \frac{V_2}{n_2} = \dots = K$$

$$\begin{array}{cccc} \textbf{Example,} & 2H_2(g) + O_2(g) & \longrightarrow & 2H_2O(g) \\ & & 2 \textit{moles} & 1 \textit{mole} & 2 \textit{moles} \\ & 2 \textit{volumes} & 1 \textit{volume} & 2 \textit{volumes} \\ & 2 \textit{litres} & 1 \textit{litre} & 2 \textit{litres} \\ & 1 \textit{litre} & 1 / 2 \textit{litre} & 1 \textit{litre} \\ & 1 \textit{n litre} & 1 / 2 \textit{n litre} & 1 \textit{n litre} \end{array}$$

- (2) One mole of any gas contains the same number of molecules (Avogadro's number = 6.02×10^{23}) and by this law must occupy the same volume at a given temperature and pressure. The volume of one mole of a gas is called **molar volume**, V_m which is 22.4 $L \ mol^{-1}$ at S.T.P. or N.T.P.
- (3) This law can also express as, "The molar gas volume at a given temperature and pressure is a specific constant independent of the nature of the gas".

Thus, $V_m = \text{specific constant} = 22.4 \, Lmol^{-1}$ at S.T.P. or N.T.P.

Ideal gas equation

(1) The simple gas laws relating gas volume to pressure, temperature and amount of gas, respectively, are stated below:

Boyle's law: $P \propto \frac{1}{V}$ or $V \propto \frac{1}{P}$ (n and

constant)

Charle's law: $V \propto T$ (n and I constant)

Avogadro's law : $V \propto n$ (T and I constant)

If all the above law's combines, then

$$V \propto \frac{nT}{P}$$
 or $V = \frac{nRT}{P}$ ($R = \text{Ideal gas constant}$) or $PV = nRT$

This is called *ideal gas equation*. *R* is called *ideal gas constant*. This equation is obeyed by isothermal and adiabatic processes.

(2) **Nature and values of R :** From the ideal gas equation, $R = \frac{PV}{nT} = \frac{\text{Pressure} \times \text{Volume}}{\text{mole} \times \text{Temperatur e}}$

$$= \frac{\frac{Force}{Area} \times Volume}{\frac{mole \times Temperatur e}{mole \times Temperatur e}} = \frac{Force \times Length}{\frac{mole \times Temperatur e}{mole \times Temperatur e}}.$$

R is expressed in the unit of work or energy $mol^{-1} K^{-1}$.

Since different values of ${\it R}$ are summarised below .

$$R = 0.0821 \ Latm \ mol^{-1} \ K^{-1}$$

$$= 8.3143 \ joule \ mol^{-1} \ K^{-1} \quad (S.I. \ unit)$$

$$= 8.3143 \ Nm \ mol^{-1} \ K^{-1}$$

$$= 8.3143 \ NPa \ dm^3 \ mol^{-1} \ K^{-1}$$

$$= 8.3143 \ MPa \ cm^3 \ mol^{-1} \ K^{-1}$$

$$= 5.189 \times 10^{19} \ eV \ mol^{-1} \ K^{-1}$$

$$= 1.99 \ cal \ mol^{-1} \ K^{-1}$$

(3) Gas constant, R for a single molecule is called *Boltzmann constant* (k)

$$k = \frac{R}{N} = \frac{8.314 \times 10^{7}}{6.023 \times 10^{23}} ergs \, mole^{-1} \, degree^{-1}$$
$$= 1.38 \times 10^{-16} \, ergs \, mol^{-1} \, degree^{-1}$$
$$or \, 1.38 \times 10^{-23} \, joule \, mol^{-1} \, degree^{-1}$$

(4) Calculation of mass, molecular weight and density of the gas by gas equation

$$PV = nRT = \frac{m}{M}RT$$

$$\therefore n = \frac{\text{mass of the gas } (m)}{\text{Molecular weight of the gas } (M)}$$

$$\therefore M = \frac{mRT}{PV}$$

$$d = \frac{PM}{RT} \qquad \left(\because d = \frac{m}{V}\right)$$

or
$$\frac{dT}{P} = \frac{M}{R}$$
, $\frac{M}{R} = \text{Constant}$

(: M and R are constant for a particular gas)

Thus,
$$\frac{dT}{P}$$
 or $\frac{d_1T_1}{P_1} = \frac{d_2T_2}{T_2} = \text{Constant}$

(For two or more different temperature and pressure)

- (5) Gas densities differ from those of solids and liquids as,
- (i) Gas densities are generally stated in g/L instead of g/cm^3 .
- (ii) Gas densities are strongly dependent on pressure and temperature as, $d \propto P \propto 1/T$

Densities of liquids and solids, do depend somewhat on temperature, but they are far less dependent on pressure.

(iii) The density of a gas is directly proportional to its molar mass. No simple relationship exists between the density and molar mass for liquid and solids.

(iv) Density of a gas at STP =
$$\frac{\text{molar mass}}{22.4}$$

$$d(N_2)$$
 at STP = $\frac{28}{22.4}$ = 1.25 g L^{-1} ,

$$d(O_2)$$
 at STP = $\frac{32}{22.4}$ = 1.43 g L^{-1}

Dalton's law of partial pressures

(1) According to this law, "When two or more gases, which do not react chemically are kept in a closed vessel, the total pressure exerted by the mixture is equal to the sum of the partial pressures of individual gases."

Thus,
$$P_{\text{total}} = P_1 + P_2 + P_3 + \dots$$

Where $P_1, P_2, P_3,...$ are partial pressures of gas number 1, 2, 3

(2) *Partial pressure* is the pressure exerted by a gas when it is present alone in the same container and at the same temperature.

Partial pressure of a gas

$$(P_1) = \frac{\text{Number of moles of the gas } (n_1) \times P_{\text{Total}}}{\text{Total number of moles } (n) \text{ in the mixture}} = \text{Mole fraction } (X_1) \times P_{\text{Total}}$$

(3) If a number of gases having volume V_1, V_2, V_3, \dots at pressure P_1, P_2, P_3, \dots are mixed together in container of volume V, then,

$$P_{\text{Total}} = \frac{P_1 V_1 + P_2 V_2 + P_3 V_3}{V}$$

or
$$= (n_1 + n_2 + n_3 \dots) \frac{RT}{V} \qquad (\because PV = nRT)$$

or
$$= n \frac{RT}{V}$$
 (: $n = n_1 + n_2 + n_3$)

- (4) **Applications**: This law is used in the calculation of following relationships,
 - (i) Mole fraction of a gas (X_1) in a mixture

of gas =
$$\frac{\text{Partial pressure of a gas } (P_1)}{P_{\text{Total}}}$$

- (ii) % of a gas in mixture $= \frac{\text{Partial pressure of a gas } (P_1)}{P_{rr}} \times 100$
- (iii) Pressure of dry gas collected over water: When a gas is collected over water, it becomes moist due to water vapour which exerts its own partial pressure at the same temperature of the gas. This partial perssure of water vapours is called aqueous tension. Thus, $P_{\rm dry\,gas} = P_{\rm moist\,gas}$ or $P_{\rm Total} P_{\rm water\,vapour}$
- or $P_{\rm dry\,gas}=P_{\rm moist\,gas}$ Aqueous tension (Aqueous tension is directly proportional to absolute temperature)
- (iv) Relative humidity (RH) at a given temperature is given by,

$$RH = \frac{\text{Partial pressure of water in air}}{\text{Vapour pre ssure of water}}.$$

- (5) *Limitations*: This law is applicable only when the component gases in the mixture do not react with each other. For example, N_2 and O_2 , CO and CO_2 , N_2 and Cl_2 , CO and N_2 etc. But this law is not applicable to gases which combine chemically. For example, H_2 and Cl_2 , CO and Cl_2 , NH_3 , HBr and HCl, NO and O_2 etc.
- (6) Another law, which is really equivalent to the law of partial pressures and related to the partial volumes of gases is known as *Law of partial volumes* given by *Amagat*. According to this law, "When two or more gases, which do not react chemically are kept in a closed vessel, the total volume exerted by the mixture is equal to the sum of the partial volumes of individual gases."

Thus,
$$V_{\text{Total}} = V_1 + V_2 + V_3 + \dots$$

Where $V_1, V_2, V_3,...$ are partial volumes of gas number 1, 2, 3.....

Graham's law of diffusion and Effusion

- (1) **Diffusion** is the process of spontaneous spreading and intermixing of gases to form homogenous mixture irrespective of force of gravity. While **Effusion** is the escape of gas molecules through a tiny hole such as pinhole in a balloon.
- All gases spontaneously diffuse into one another when they are brought into contact.
- Diffusion into a vacuum will take place much more rapidly than diffusion into another place.

- Both the rate of diffusion of a gas and its rate of effusion depend on its molar mass. Lighter gases diffuses faster than heavier gases. The gas with highest rate of diffusion is *hydrogen*.
- (2) According to this law, "At constant pressure and temperature, the rate of diffusion or effusion of a gas is inversely proportional to the square root of its vapour density."

Thus, rate of diffusion $(r) \propto \frac{1}{\sqrt{d}}$ (T and P

constant)

For two or more gases at constant pressure and temperature, $% \left(1\right) =\left(1\right) \left(1\right)$

$$\frac{r_1}{r_2} = \sqrt{\frac{d_2}{d_1}}$$

- (3) Graham's law can be modified in a number of ways as,
- (i) Since, 2 \times vapour density (V.D.) = Molecular weight

then,
$$\frac{r_1}{r_2} = \sqrt{\frac{d_2}{d_1}} = \sqrt{\frac{d_2 \times 2}{d_1 \times 2}} = \sqrt{\frac{M_2}{M_1}}$$

where, $\,M_1\,$ and $\,M_2\,$ are the molecular weights of the two gases.

(ii) Since, rate of diffusion $(r) = \frac{\text{Volume of a gas diffused}}{\text{Time taken for diffusion}}$ then,

$$\frac{r_1}{r_2} = \frac{V_1 / t_1}{V_2 / t_2} = \frac{w_1 / t_1}{w_2 / t_2} = \sqrt{\frac{d_2}{d_1}}$$

(a) When equal volume of the two gases diffuse, *i.e.* $V_1 = V_2$

then,
$$\frac{r_1}{r_2} = \frac{t_2}{t_1} = \sqrt{\frac{d_2}{d_1}}$$

(b) When volumes of the two gases diffuse in the same time, *i.e.* $t_1 = t_2$

then,
$$\frac{r_1}{r_2} = \frac{V_1}{V_2} = \sqrt{\frac{d_2}{d_1}}$$

(iii) Since, $r \propto p$ (when p is not constant)

then,
$$\frac{r_1}{r_2} = \frac{P_1}{P_2} \sqrt{\frac{M_2}{M_1}}$$
 $\left(\because r \propto \frac{P}{\sqrt{M}}\right)$

- (4) Rate of diffusion and effusion can be determined as,
- (i) Rate of diffusion is equal to distance travelled by gas per unit time through a tube of uniform cross-section.
- (ii) Number of moles effusing per unit time is also called rate of diffusion.
- (iii) Decrease in pressure of a cylinder per unit time is called rate of effusion of gas.

- (iv) The volume of gas effused through a given surface per unit time is also called rate of effusion.
- (5) **Applications:** Graham's law has been used as follows.
- (i) To determine vapour densities and molecular weights of gases.
- (ii) To prepare Ausell's marsh gas indicator, used in mines.
- (iii) *Atmolysis*: The process of separation of two gases on the basis of their different rates of diffusion due to difference in their densities is called atmolysis. It has been applied with success for the separation of isotopes and other gaseous mixtures.

Kinetic theory of gases

(1) Kinetic theory was developed by Bernoulli, Joule, Clausius, Maxwell and Boltzmann etc. and represents *dynamic particle or microscopic model* for different gases since it throws light on the behaviour of the particles (atoms and molecules) which constitute the gases and cannot be seen. Properties of gases which we studied earlier are part of macroscopic model.

(2) Postulates

- (i) Every gas consists of a large number of small particles called molecules moving with very high velocities in all possible directions.
- (ii) The volume of the individual molecule is negligible as compared to the total volume of the gas.
- (iii) Gaseous molecules are *perfectly elastic* so that there is no net loss of kinetic energy due to their collisions.
- (iv) The effect of gravity on the motion of the molecules is negligible.
- (v) Gaseous molecules are considered as *point masses* because they do not posses potential energy. So the attractive and repulsive forces between the gas molecules are negligible.
- (vi) The pressure of a gas is due to the continuous bombardment on the walls of the containing vessel.
- (vii) At constant temperature the average K.E. of all gases is same.
- (viii) The average K.E. of the gas molecules is directly proportional to the absolute temperature.
- (3) **Kinetic gas equation :** On the basis of above postulates, the following gas equation was derived,

$$PV = \frac{1}{3} mnu_{rms}^2$$

where, P = pressure exerted by the gas

V = volume of the gas

m =average mass of each molecule

n = number of molecules

u = root mean square (RMS) velocity of the gas.

(4) Calculation of kinetic energy

We know that,

K.E. of one molecule = $\frac{1}{2}mu^2$

K.E. of
$$n$$
 molecules $=\frac{1}{2}mnu^2 = \frac{3}{2}PV$

$$(: PV = \frac{1}{3} mnu^2)$$

$$n = 1$$
, Then K.E. of 1 mole gas $= \frac{3}{2}RT$
 $(:PV = RT)$

$$=\frac{3}{2} \times 8.314 \times T = 12.47 \ T \ Joules$$
.

$$= \frac{\text{Average K.E.per mole}}{N(\text{Avogadro number })} = \frac{3}{2} \frac{RT}{N} = \frac{3}{2} KT$$


$$\left(K = \frac{R}{N} = \text{Boltzmann constant}\right)$$

This equation shows that K.E. of translation of a gas depends only on the absolute temperature. This is known as *Maxwell generalisation*. Thus average K.E. \propto T.

If T=0K (i.e., $-273.15^{\circ}C$) then, average K.E. = O. Thus, absolute zero (OK) is the temperature at which molecular motion ceases.

Molecular collisions

(1) The closest distance between the centres of two molecules taking part in a collision is called molecular or collision diameter (σ). The molecular diameter of all the gases is nearly same lying in the order of 10^{-8} cm



- (2) The number of collisions taking place in unit time per unit volume, called *collision frequency* (z).
- (i) The number of collision made by a single molecule with other molecules per unit time are given by, $Z_A = \sqrt{2}\pi\sigma^2 u_{\rm av} n$

where n is the number of molecules per unit molar volume.

$$n = \frac{\text{Avogadro number}(N_0)}{V_m} = \frac{6.02 \times 10^{23}}{0.0224} m^{-3}$$

- (ii) The total number of bimolecular collision per unit time are given by, $Z_{AA} = \frac{1}{\sqrt{2}} \pi \sigma^2 u_{av} n^2$
- (iii) If the collisions involve two unlike molecules, the number of bimolecular collision are given by,

$$Z_{AB} = \sigma_{AB}^2 \left[8\pi RT \frac{(M_A + M_B)}{M_A M_B} \right]^{1/2}$$

where,
$$\sigma_{AB} = \frac{\sigma_A + \sigma_B}{2}$$

 M_A , M_B are molecular weights $(M = mN_0)$

- (iv) (a) At particular temperature; $Z \propto p^2$
- (b) At particular pressure; $Z \propto T^{-3/2}$
- (c) At particular volume; $Z \propto T^{1/2}$
- (3) During molecular collisions a molecule covers a small distance before it gets deflected. The average distance travelled by the gas molecules between two successive collision is called mean free path (λ) .

$$\lambda = \frac{\text{Average distance travelled per unit time}(u_{\text{av}})}{\text{No. of collisions made by single molecule per unit time}(Z_A)}.$$

$$= \frac{u_{\text{av}}}{\sqrt{2\pi\sigma^2}u_{\text{av}}n} = \frac{1}{\sqrt{2\pi n}\sigma^2}$$

- (4) Based on kinetic theory of gases mean free path, $\lambda \propto \frac{T}{D}$. Thus,
- (i) Larger the size of the molecules, smaller the mean free path, *i.e.*, $\lambda \propto \frac{1}{\left(\text{radius}\right)^2}$
- (ii) Greater the number of molecules per unit volume, smaller the mean free path.
- (iii) Larger the temperature, larger the mean free path.
- (iv) Larger the pressure, smaller the mean free path.
- (5) Relation between collision frequency (*Z*) and mean free path (λ) is given by, $Z = \frac{u_{rms}}{\lambda}$


Molecular speeds or velocities

- (1) At any particular time, in the given sample of gas all the molecules do not possess same speed, due to the frequent molecular collisions with the walls of the container and also with one another, the molecules move with ever changing speeds and also with ever changing direction of motion.
- (2) According to Maxwell, at a particular temperature the distribution of speeds remains constant and this distribution is referred to as the *Maxwell-Boltzmann distribution* and given by the following expression,

$$\frac{dn_0}{n} = 4\pi \left(\frac{M}{2\pi RT}\right)^{3/2} . e^{-Mu^2/2RT} . u^2 dc$$

where, $dn_0 = \text{Number of molecules out of total}$ number of molecules n, having velocities between c and c+dc, $dn_0/n = \text{Fraction}$ of the total number of molecules, M = molecular weight, T = absolute temperature. The exponential factor $e^{-Mu^2/2RT}$ is called $Boltzmann\ factor$.

- (3) Maxwell gave distribution curves of molecular speeds for CO_2 at different temperatures. Special features of the curve are :
- (i) Fraction of molecules with two high or two low speeds is very small.
 - (ii) No molecules has zero velocity.
- (iii) Initially the fraction of molecules increases in velocity till the peak of the curve which pertains to most probable velocity and thereafter it falls with increase in velocity.



(4) Types of molecular speeds or Velocities

(i) **Root mean square velocity** (u_{rms}) : It is the square root of the mean of the squares of the velocity of a large number of molecules of the same gas.

$$u_{rms} = \sqrt{\frac{u_1^2 + u_2^2 + u_3^2 + \dots u_n^2}{n}}$$

$$u_{rms} = \sqrt{\frac{3PV}{(mN_0) = M}} = \sqrt{\frac{3RT}{(mN_0) = M}} = \sqrt{\frac{3RT}{M}} = \sqrt{\frac{3kT}{m}} = \sqrt{\frac{3P}{d}}$$

where $k = \text{Boltzmann constant} = \frac{R}{N_0}$

(a) For the same gas at two different temperatures, the ratio of $\it RMS$ velocities will be,

$$\frac{u_1}{u_2} = \sqrt{\frac{T_1}{T_2}}$$

(b) For two different gases at the same temperature, the ratio of *RMS* velocities will be,

$$\frac{u_1}{u_2} = \sqrt{\frac{M_2}{M_1}}$$

(c) *RMS* velocity at any temperature t^oC may be related to its value at S.T.P. as, $u_t = \sqrt{\frac{3P(273+t)}{273\,d}}$.

(ii) **Average velocity** (v_{av}) : It is the average of the various velocities possessed by the molecules.

$$v_{av} = \frac{v_1 + v_2 + v_3 + \dots v_n}{n}$$
; $v_{av} = \sqrt{\frac{8RT}{\pi M}} = \sqrt{\frac{8kT}{\pi m}}$

(iii) *Most probable velocity* (α_{mp}) : It is the velocity possessed by maximum number of molecules of a gas at a given temperature.

$$\alpha_{mp} = \sqrt{\frac{2RT}{M}} = \sqrt{\frac{2PV}{M}} = \sqrt{\frac{2P}{d}}$$

- (5) Relation between molecular speeds or velocities,
- (i) Relation between u_{rms} and v_{av} : $v_{av} = 0.9213 \times u_{rms}$

or $u_{rms} = 1.085 \times v_{av}$

(ii) Relation between α_{mp} and u_{mns} : $\alpha_{mn} = 0.816 \times u_{rms}$


or
$$u_{rms} = 1.224 \times \alpha_{mp}$$

(iii) Relation between α_{mp} and v_{av} : $v_{av} = 1.128 \times \alpha_{mp}$

(iv) Relation between α_{mp} , v_{av} and u_{rms}

Real and Ideal gases

- (1) Gases which obey gas laws or ideal gas equation (PV = nRT) at all temperatures and pressures are called *ideal or perfect gases*. Almost all gases deviate from the ideal behaviour *i.e.*, *no gas is perfect* and the concept of perfect gas is only theoretical.
- (2) Gases tend to show ideal behaviour more and more as the temperature rises above the boiling point of their liquefied forms and the pressure is lowered. Such gases are known as real or non ideal gases. Thus, a "real gas is that which obeys the gas laws under low pressure or high temperature".
- (3) The deviations can be displayed, by plotting the *P-V* isotherms of real gas and ideal gas.



(4) It is difficult to determine quantitatively the deviation of a real gas from ideal gas behaviour from the P-V isotherm curve as shown above. Compressibility factor Z defined by the equation,

$$PV = ZnRT$$
 or $Z = PV/nRT = PV_m/RT$

is more suitable for a quantitative description of the deviation from ideal gas behaviour.

- (5) Greater is the departure of Z from unity, more is the deviation from ideal behaviour. Thus, when
- (i) Z=1, the gas is ideal at all temperatures and pressures. In case of N_2 , the value of Z is close to 1 at $50\,^{\circ}\,C$. This temperature at which a real gas exhibits ideal behaviour, for considerable range of pressure, is known as *Boyle's temperature or Boyle's point* (T_R) .
- (ii) Z>1, the gas is less compressible than expected from ideal behaviour and shows positive deviation, usual at high P i.e. PV>RT.
- (iii) Z < 1, the gas is more compressible than expected from ideal behaviour and shows negative deviation, usually at low P i.e. PV < RT.
- (iv) Z > 1 for H_2 and He at all pressure *i.e.*, always shows positive deviation.
- (v) The most easily liquefiable and highly soluble gases (NH_3,SO_2) show larger deviations from ideal behaviour i.e. Z << 1.
- (vi) Some gases like ${\it CO}_2$ show both negative and positive deviation.
- (6) Causes of deviations of real gases from ideal behaviour: The ideal gas laws can be derived from the kinetic theory of gases which is based on the following two important assumptions,
- (i) The volume occupied by the molecules is negligible in comparison to the total volume of gas.
- (ii) The molecules exert no forces of attraction upon one another. It is because neither of these assumptions can be regarded as applicable to real gases that the latter show departure from the ideal behaviour.

Vander Waal's equation

- (1) To rectify the errors caused by ignoring the intermolecular forces of attraction and the volume occupied by molecules, Vander Waal (in 1873) modified the ideal gas equation by introducing two corrections,
- (i) Volume correction (ii) Pressure correction

- (2) Vander Waal's equation is obeyed by the real gases over wide range of temperatures and pressures, hence it is called *equation of state for the real gases*.
- (3) The Vander Waal's equation for n moles of the gas is,

$$\left(P + \frac{n^2 a}{V^2}\right) \qquad [V - nb] = nRT$$
Pressure correction Volume correction for finite size of molecules

a and b are Vander Waal's constants whose values depend on the nature of the gas. Normally for a gas a>>b.

(i) **Constant a**: It is a indirect measure of magnitude of attractive forces between the molecules. Greater is the value of a, more easily the gas can be liquefied. Thus the easily liquefiable gases (like $SO_2 > NH_3 > H_2S > CO_2$) have high values than the permanent gases (like $N_2 > O_2 > H_2 > He$).

Units of 'a' are : $atm. L^2 mol^{-2}$ or $atm. m^6 mol^{-2}$ or $N m^4 mol^{-2}$ (S.I. unit).

(ii) ${\it Constant}\ b$: Also called co-volume or excluded volume,

$$b = 4N_0 v = 4N_0 \left(\frac{4}{3}\pi r^3\right)$$

It's value gives an idea about the effective size of gas molecules. Greater is the value of b, larger is the size and smaller is the compressible volume. As b is the effective volume of the gas molecules, the constant value of b for any gas over a wide range of temperature and pressure indicates that the gas molecules are incompressible.

Units of 'b' are : $Lmol^{-1}$ or $m^3 mol^{-1}$ (S.I. unit)

(iii) The two Vander Waal's constants and Boyle's temperature (T_B) are related as,

$$T_B = \frac{a}{bR}$$

- (4) Vander Waal's equation at different temperature and pressures
- (i) When pressure is extremely low: For one mole of gas,

$$\left(P + \frac{a}{V^2}\right)(V - b) = RT$$
 or $PV = RT - \frac{a}{V} + Pb + \frac{ab}{V^2}$

(ii) When pressure is extremely high: For one mole of gas,

$$PV = RT + Pb$$
; $\frac{PV}{RT} = 1 + \frac{Pb}{RT}$ or $Z = 1 + \frac{Pb}{RT}$

where Z is compressibility factor.

(iii) When temperature is extremely high: For one mole of gas,

$$PV = RT$$
.

(iv) When pressure is low: For one mole of gas,

$$\left(P + \frac{a}{V^2}\right)(V - b) = RT \quad \text{or} \quad PV = RT + Pb - \frac{a}{V} + \frac{ab}{V^2}$$
or
$$\frac{PV}{PT} = 1 - \frac{a}{VPT} \quad \text{or} \quad Z = 1 - \frac{a}{VPT}$$

(v) For hydrogen: Molecular mass of hydrogen is small hence value of 'a' will be small owing to smaller intermolecular force. Thus the terms $\frac{a}{V}$ and $\frac{ab}{V^2}$ may be ignored. Then Vander Waal's equation becomes,

$$PV = RT + Pb$$
 or $\frac{PV}{RT} = 1 + \frac{Pb}{RT}$
or $Z = 1 + \frac{Pb}{RT}$

In case of hydrogen, compressibility factor is always greater than one.

(5) Merits of Vander Waal's equation

- (i) The Vander Waal's equation holds good for real gases upto moderately high pressures.
- (ii) The equation represents the trend of the isotherms representing the variation of PV with P for various gases.
- (iii) From the Vander Waal's equation it is possible to obtain expressions of Boyle's temperature, critical constants and inversion temperature in terms of the Vander Waal's constants 'a' and 'b'.
- (iv) Vander Waal's equation is useful in obtaining a 'reduced equation of state' which being a general equation of state has the advantage that a single curve can be obtained for all gases when the equation if graphically represented by plotting the variables.

(6) Limitations of Vander Waal's equation

- (i) This equation shows appreciable deviations at too low temperatures or too high pressures.
- (ii) The values of Vander Waal's constants a and b do not remain constant over the entire ranges of T and P, hence this equation is valid only over specific range of T and P.
- (7) **Other equations of state:** In addition to Vander Waal's equation, there are also equations of state which have been used to explain real behaviour of gases are,
- (i) Clausius equation : $\left[P+\frac{a}{T(V+c)^2}\right](V-b)=RT \text{ . Here 'c' is another constant besides } a,b \text{ and } R.$

(ii) Berthelot equation :
$$\left(P + \frac{a}{TV^2}\right)(V - b) = RT$$
.

- (iii) **Wohl equation**: $P = \frac{RT}{(V-b)} \frac{a}{V(V-b)} + \frac{c}{V^2}$
- (iv) **Dieterici equation :** $P = \frac{RT}{V h} e^{-a/RTV}$.

The expression is derived on the basis of the concept that molecules near the wall will have higher potential energy than those in the bulk.

(v) Kammerlingh Onnes equation: It is the most general or satisfactory expression as equation expresses PV as a power series of P at a given temperature.

$$PV = A + BP + CP^{2} + DP^{3} + \dots$$

Here coefficients A, B, C etc. are known as first, second and third etc. virial coefficients.

- (a) Virial coefficients are different for different gases.
- (b) At very low pressure, first virial coefficient, A = RT.
- (c) At high pressure, other virial coefficients also become important and must be considered.

The critical state

- (1) A state for every substance at which the vapour and liquid states are indistinguishable is known as *critical state*. It is defined by critical temperature and critical pressure.
- (2) Critical temperature (T_c) of a gas is that temperature above which the gas cannot be liquified however large pressure is applied. It is given by,

$$T_c = \frac{8a}{27Rb}$$

- (3) **Critical pressure** (P_c) is the minimum pressure which must be applied to a gas to liquify it at its critical temperature. It is given by, $P_c = \frac{a}{27h^2}$
- (4) **Critical volume (V_c)** is the volume occupied by one mole of the substance at its critical temperature and critical pressure. It is given by, $V_c = 3b$
- (5) Critical compressibility factor (Z_c) is given by, $Z_c = \frac{P_c V_c}{RT_c} = \frac{3}{8} = 0.375$

A gas behaves as a Vander Waal's gas if its critical compressibility factor (Z_c) is equal to 0.375. A substance is the gaseous state below T_c is called vapour and above T_c is called gas.

Degrees of freedom of a gaseous molecule

- (1) The motion of atoms and molecules is generally described in terms of the degree of freedom which they possess.
- (2) The degrees of freedom of a molecule are defined as the independent number of parameters

required to describe the state of the molecule completely.

- (3) When a gaseous molecule is heated, the energy supplied to it may bring about three kinds of motion in it, these are,
- (i) The translational motion (ii) The rotational motion (iii) The vibrational motion.

This is expressed by saying that the molecule possesses translational, rotational and vibrational degrees of freedom

(4) For a molecule made up of N atoms, total degrees of freedom = 3N. Further split up of these is as follows:

follows,					
Tra	Translational		Rotational		
Vibrational					
$For \ linear \ molecule:$	3	2	3 <i>N</i> - 5		
For non-linear molecu	ıle: 3	3	3 <i>N</i> - 6		

Specific and Molar heat capacity of gases

- (1) **Specific heat (or specific heat capacity)** of a substance is the quantity of heat (in *calories*, *joules*, *kcal*, or *kilo joules*) required to raise the temperature of 1g of that substance through $1^{o}C$. It can be measured at constant pressure (c_{p}) and at constant volume (c_{y}) .
- (2) Molar heat capacity of a substance is the quantity of heat required to raise the temperature of 1 mole of the substance by $1^{\circ}C$.
- \therefore Molar heat capacity = Specific heat capacity \times Molecular weight, *i.e.*,

$$C_v = c_v \times M$$
 and $C_p = c_p \times M$.

(3) Since gases upon heating show considerable tendency towards expansion if heated under constant pressure conditions, an additional energy has to be supplied for raising its temperature by $1^{\circ}C$ relative to that required under constant volume conditions, *i.e.*,

$$C_p > C_v$$
 or $C_p = C_v + \text{Work done on expansion}$, $P\Delta V (= R)$

where, C_p = molar heat capacity at constant pressure; C_v = molar heat capacity at constant volume.

(4) Some useful relations of C_p and C_v

(i)
$$C_p - C_v = R = 2 \text{ calories} = 8.314 J$$

(ii)
$$C_v = \frac{3}{2}R$$
 (for monoatomic gas) and

 $C_v = \frac{3}{2} + x$ (for *di* and polyatomic gas), where *x* varies from gas to gas.

(iii)
$$\frac{C_p}{C_v} = \gamma$$
 (Ratio of molar capacities)

(iv) For monoatomic gas $C_v = 3$ calories whereas, $C_p = C_v + R = 5$ calories

(v) For monoatomic gas,

$$(\gamma) = \frac{C_p}{C_v} = \frac{\frac{5}{2}R}{\frac{3}{2}R} = 1.66.$$

(vi) For diatomic gas
$$(\gamma) = \frac{C_p}{C_v} = \frac{\frac{7}{2}R}{\frac{5}{2}R} = 1.40$$

(vii) For triatomic gas
$$(\gamma) = \frac{C_p}{C_n} = \frac{8R}{6R} = 1.33$$

Liquefaction of gases

- (1) A gas may be liquefied by cooling or by the application of high pressure or by the combined effect of both. The first successful attempt for liquefying gases was made by *Faraday*.
- (2) Gases for which the intermolecular forces of attraction are small such as H_2 , N_2 , Ar and O_2 , have low values of T_c and cannot be liquefied by the application of pressure are known as "permanent gases" while the gases for which the intermolecular forces of attraction are large, such as polar molecules NH_3 , SO_2 and H_2O have high values of T_c and can be liquefied easily.
- (3) Methods of liquefaction of gases: The modern methods of cooling the gas to or below their T_c and hence of liquefaction of gases are done by Linde's method and Claude's method.
- (i) **Linde's method:** This process is based upon **Joule-Thomson effect** which states that "When a gas is allowed to expand adiabatically from a region of high pressure to a region of extremely low pressure, it is accompained by cooling."
- (ii) Claude's method: This process is based upon the principle that when a gas expands adiabatically against an external pressure (as a piston in an engine), it does some external work. Since work is done by the molecules at the cost of their kinetic energy, the temperature of the gas falls causing cooling.
 - (iii) By adiabatic demagnetisation.
- (4) **Uses of liquefied gases**: Liquefied and gases compressed under a high pressure are of great importance in industries.
- (i) Liquid ammonia and liquid sulphur dioxide are used as refrigerants.
- (ii) Liquid carbon dioxide finds use in soda fountains.
- (iii) Liquid chlorine is used for bleaching and disinfectant purposes.
- (iv) Liquid air is an important source of oxygen in rockets and jet-propelled planes and bombs.

- (v) Compressed oxygen is used for welding purposes.
 - (vi) Compressed helium is used in airships.
- (5) **Joule-Thomson effect:** When a real gas is allowed to expand adiabatically through a porous plug or a fine hole into a region of low pressure, it is accompanied by cooling (except for hydrogen and helium which get warmed up).

Cooling takes place because some work is done to overcome the intermolecular forces of attraction. As a result, the internal energy decreases and so does the temperature.

Ideal gases do not show any cooling or heating because there are no intermolecular forces of attraction i.e., they do not show Joule-Thomson effect.

During Joule-Thomson effect, enthalpy of the system remains constant.

Joule-Thomson coefficient. $\mu = (\partial T / \partial P)_H$.

For cooling, $\mu = +ve$ (because dT and dP will be -ve)

For heating $\mu = -ve$ (because dT = +ve, dP = -ve).

For no heating or cooling $\mu = 0$ (because dT = 0).

(6) **Inversion temperature :** It is the temperature at which gas shows neither cooling effect nor heating effect *i.e.*, Joule-Thomson coefficient $\mu = 0$. Below this temperature, it shows cooling effect and above this temperature, it shows heating effect.

Any gas like H_2 , He etc, whose inversion temperature is low would show heating effect at room temperature. However, if these gases are just cooled below inversion temperature and then subjected to Joule-Thomson effect, they will also undergo cooling.



- If the number of molecules present in 1 c.c. of the gas or vapour at S.T.P., then that is called loschmidt number. Its value is 2.687×10^{19} per C.C.
- $\angle S$ $CO_2 > SO_2 > SO_3 > PCl_3$ is order of rate of diffusion
- $\boldsymbol{\varkappa}$ The isotherms of CO_2 were first studied by Andrews.

- ★ 1 Cal = 4.2 Joule, 1 Kcal = 4200 Joule
- \mathcal{L} $T_c < T_b < T_i$
- \angle For critical constants, compression factor Z is < 1.
- \mathcal{E} Boyle's law and Avogadro's law are applicable under limiting condition. This limiting condition is $P \to 0$.
- $\not \mathbf{z}$ $T_c = 0.296 \ T_b$; $T_i = 6.75 \ T_c$
- \angle Mean free path increases if H_2 is replaced by He.