

MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

"In nature, we have to deal not with material points but with material bodies ... - Max Planck

EARNING OBJECTIVES

In this unit, the student is exposed to

- relevance of the centre of mass in various systems of particles
- torque and angular momentum in rotational motion
- types of equilibria with appropriate examples
- moment of inertia of different rigid bodies
- dynamics of rotation of rigid bodies
- distinguishing translational motion from rotational motion
- rolling motion, slipping and sliding motions.

INTRODUCTION

5.1

Most of the objects that we come across in our day to day life consist of large number of particles. In the previous Units, we studied the motion of bodies without considering their size and shape. So far we have treated even the bulk bodies as only point objects. In this section, we will give importance to the size and shape of the bodies. These bodies are actually made up of a large number of particles. When such a body moves, we consider it as the motion of collection of particles as a whole. We define the concept of centre of mass to deal with such a system of particles.

The forces acting on these bulk bodies are classified into *internal* and *external*

208

۲

forces. Internal forces are the forces acting among the particles within a system that constitute the body. External forces are the forces acting on the particles of a system from outside. In this unit, we deal with such system of particles which make different rigid bodies. A rigid body is the one which maintains its definite and fixed shape even when an external force acts on it. This means that, the interatomic distances do not change in a rigid body when an external force is applied. However, in real life situation, we have bodies which are not ideally rigid, because the shape and size of the body change when forces act on them. For the rigid bodies we study here, we assume that such deformations are negligible. The deformations produced on non-rigid bodies are studied separately in Unit 7 under elasticity of solids.





5.1.1 CENTRE OF MASS

When a rigid body moves, all particles that constitute the body need not take the same path. Depending on the type of motion, different particles of the body may take different paths. For example, when a wheel rolls on a surface, the path of the centre point of the wheel and the paths of other points of the wheel are different. In this Unit, we study about the translation, rotation and the combination of these motions of rigid bodies in detail.

5.1.2 Centre of Mass of a Rigid Body

When a bulk object (say a bat) is thrown at an angle in air as shown in Figure 5.1; do all the points of the body take a parabolic path? Actually, only one point takes the parabolic path and all the other points take different paths.



Figure 5.1 Centre of mass tracing the path of a parabola

The one point that takes the parabolic path is a very special point called *centre of mass* (CM) of the body. Its motion is like the motion of a single point that is thrown. *The centre of mass of a body is defined as a point where the entire mass of the body appears to be concentrated.* Therefore, this point can represent the entire body.

For bodies of regular shape and uniform mass distribution, the centre of mass is at the geometric centre of the body. As examples, for a circle and sphere, the centre of mass is at their centres; for square and rectangle, at the point their diagonals meet; for cube and cuboid, it is at the point where their body diagonals meet. For other bodies, the centre of mass has to be determined using some methods. The centre of mass could be well within the body and in some cases outside the body as well.

5.1.3 Centre of Mass for Distributed Point Masses

A point mass is a hypothetical point particle which has nonzero mass and no size or shape. To find the centre of mass for a collection of n point masses, say, $m_1, m_2, m_3 \dots m_n$ we have to first choose an origin and an appropriate coordinate system as shown in Figure 5.2. Let, $x_1, x_2, x_3 \dots x_n$ be the X-coordinates of the positions of these point masses in the X direction from the origin.



distributed point masses

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES



The equation for the x coordinate of the centre of mass is,

 $(\mathbf{0})$

$$x_{_{CM}} = \frac{\sum m_{_{i}}x_{_{i}}}{\sum m_{_{i}}}$$

where, $\sum m_i$ is the total mass M of all the particles, $(\sum m_i = M)$. Hence,

$$x_{\rm CM} = \frac{\sum m_i x_i}{M}$$
(5.1)

Similarly, we can also find y and z coordinates of the centre of mass for these distributed point masses as indicated in Figure (5.2).

$$y_{\rm CM} = \frac{\sum m_i y_i}{M}$$
(5.2)

$$z_{\rm CM} = \frac{\sum m_i z_i}{M}$$
(5.3)

Hence, the position of centre of mass of these point masses in a Cartesian coordinate system is (x_{CM}, y_{CM}, z_{CM}) . In general, the position of centre of mass can be written in a vector form as,

$$\vec{r}_{CM} = \frac{\sum m_i \vec{r}_i}{M}$$
(5.4)

where, $\vec{r}_{CM} = x_{CM}\hat{i} + y_{CM}\hat{j} + z_{CM}\hat{k}$ is the position vector of the centre of mass and $\vec{r}_i = x_i\hat{i} + y_i\hat{j} + z_i\hat{k}$ is the position vector of the distributed point mass; where, \hat{i} , \hat{j} and \hat{k} are the unit vectors along X, Y and Z-axes respectively.

5.1.4 Centre of Mass of Two Point Masses

With the equations for centre of mass, let us find the centre of mass of two point masses m_1 and m_2 , which are at positions x_1 and x_2 respectively on the X-axis. For this case, we can express the position of centre of mass in the following three ways based on the choice of the coordinate system.

(i) When the masses are on positive X-axis: The origin is taken arbitrarily so that the masses m_1 and m_2 are at positions x_1 and x_2 on the positive X-axis as shown in Figure 5.3(a). The centre of mass will also be on the positive X-axis at x_{CM} as given by the equation,

$$x_{\rm CM} = \frac{m_1 x_1 + m_2 x_2}{m_1 + m_2}$$

(ii) When the origin coincides with any one of the masses:

The calculation could be minimised if the origin of the coordinate system is made to coincide with any one of the masses as shown in Figure 5.3(b). When the origin coincides with the point mass m_1 , its position x_1 is zero, (i.e. $x_1 = 0$). Then,

$$\mathbf{x}_{\rm CM} = \frac{\mathbf{m}_1(0) + \mathbf{m}_2 \mathbf{x}_2}{\mathbf{m}_1 + \mathbf{m}_2}$$

The equation further simplifies as,

$$x_{_{CM}} = \frac{m_2 x_2}{m_1 + m_2}$$

(*iii*) When the origin coincides with the centre of mass itself:

If the origin of the coordinate system is made to coincide with the centre of mass,

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

(210

then, $x_{CM} = 0$ and the mass m_1 is found to be on the negative X-axis as shown in Figure 5.3(c). Hence, its position x_1 is negative, (i.e. $-x_1$).

$$0 = \frac{m_1(-x_1) + m_2 x_2}{m_1 + m_2}$$
$$0 = m_1(-x_1) + m_2 x_2$$
$$m_1 x_1 = m_2 x_2$$

The equation given above is known as *principle of moments*. We will learn more about this in Section 5.3.3.



EXAMPLE 5.1

۲

Two point masses 3 kg and 5 kg are at 4 m and 8 m from the origin on X-axis. Locate the position of centre of mass of the two point masses (i) from the origin and (ii) from 3 kg mass.

Solution

Let us take, $m_1 = 3 \text{ kg and } m_2 = 5 \text{ kg}$

(i) To find centre of mass from the origin:

The point masses are at positions, $x_1 = 4$ m, $x_2 = 8$ m from the origin along X axis.



The centre of mass x_{CM} can be obtained using equation 5.4.

$$x_{CM} = \frac{m_1 x_1 + m_2 x_2}{m_1 + m_2}$$
$$x_{CM} = \frac{(3 \times 4) + (5 \times 8)}{3 + 5}$$
$$x_{CM} = \frac{12 + 40}{8} = \frac{52}{8} = 6.5 \,\mathrm{m}$$

The centre of mass is located 6.5 m from the origin on X-axis.

(ii) To find the centre of mass from 3 kg mass: The origin is shifted to 3 kg mass along X-axis. The position of 3 kg point mass is zero $(x_1 = 0)$ and the position of 5 kg point mass is 4 m from the shifted origin $(x_2 = 4 m)$.



UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

$$x_{CM} = \frac{(3 \times 0) + (5 \times 4)}{3 + 5}$$
$$x_{CM} = \frac{0 + 20}{8} = \frac{20}{8} = 2.5 \,\mathrm{m}$$

The centre of mass is located 2.5 m from 3 kg point mass, (and 1.5 m from the 5 kg point mass) on X-axis.

- This result shows that the centre of mass is located closer to larger mass.
- If the origin is shifted to the centre of mass, then the principle of moments holds good. m₁x₁ = m₂x₂; 3×2.5=5×1.5; 7.5=7.5

When we compare case (i) with case (ii), the $x_{CM} = 2.5 \text{ m}$ from 3 kg mass could also be obtained by subtracting 4 m (the position of 3 kg mass) from 6.5 m, where the centre of mass was located in case (i)

EXAMPLE 5.2

From a uniform disc of radius R, a small disc of radius $\frac{R}{2}$ is cut and removed as shown in the diagram. Find the centre of mass of the remaining portion of the disc.

Solution

Let us consider the mass of the uncut full disc be M. Its centre of mass would be at the geometric centre of the disc on which the origin coincides.

Let the mass of the small disc cut and removed be m and its centre of mass is at a position $\frac{R}{2}$ to the right of the origin as shown in the figure.



Hence, the remaining portion of the disc should have its centre of mass to the left of the origin; say, at a distance x. We can write from the principle of moments,

$$(M-m)x = (m)\frac{R}{2}$$

 $x = \left(\frac{m}{(M-m)}\right)\frac{R}{2}$

If σ is the surface mass density (i.e. mass per unit surface area), $\sigma = \frac{M}{\pi R^2}$; then, the mass m of small disc is,

$$\overline{\mathbf{m} = \text{surface mass density} \times \text{surface area}}$$
$$\overline{\mathbf{m} = \mathbf{\sigma} \times \pi \left(\frac{R}{2}\right)^2}$$
$$\overline{\mathbf{m}} = \left(\frac{M}{\pi R^2}\right) \pi \left(\frac{R}{2}\right)^2 = \frac{M}{\pi R^2} \pi \frac{R^2}{4} = \frac{M}{4}$$
substituting m in the expression for x
$$x = \frac{\frac{M}{4}}{\left(M - \frac{M}{4}\right)} \times \frac{R}{2} = \frac{\frac{M}{4}}{\left(\frac{3M}{4}\right)} \times \frac{R}{2}$$
$$x = \frac{R}{6}$$

212

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

UNIT-5(XI-Physics_Vol-1).indd 212

The centre of mass of the remaining portion is at a distance $\frac{R}{6}$ to the left from the centre of the disc.

If, the small disc is removed concentrically from the large disc, what will be the position of the centre of mass of the remaining portion of disc?

EXAMPLE 5.3

The position vectors of two point masses 10 kg and 5 kg are $(-3\hat{i}+2\hat{j}+4\hat{k})$ m and $(3\hat{i}+6\hat{j}+5\hat{k})$ m respectively. Locate the position of centre of mass.

Solution

$$m_{1} = 10 \, kg$$

$$m_{2} = 5 \, kg$$

$$\vec{r}_{1} = (-3\hat{i} + 2\hat{j} + 4\hat{k})m$$

$$\vec{r}_{2} = (3\hat{i} + 6\hat{j} + 5\hat{k})m$$

$$\vec{r} = \frac{m_{1}\vec{r}_{1} + m_{2}\vec{r}_{2}}{m_{1} + m_{2}}$$

$$\therefore \vec{r} = \frac{10(-3\hat{i} + 2\hat{j} + 4\hat{k}) + 5(3\hat{i} + 6\hat{j} + 5\hat{k})}{10 + 5}$$

$$= \frac{-30\hat{i} + 20\hat{j} + 40\hat{k} + 15\hat{i} + 30\hat{j} + 25\hat{k}}{15}$$

$$= \frac{-30\hat{i} + 20\hat{j} + 40\hat{k} + 15\hat{i} + 30\hat{j} + 25\hat{k}}{15}$$

$$\vec{r} = \left(-\hat{i} + \frac{10}{3}\hat{j} + \frac{13}{3}\hat{k}\right)m$$
The centre of mass is located at position \vec{r} .

5.1.5 Centre of mass for uniform distribution of mass

If the mass is uniformly distributed in a bulk object, then a small mass (Δm) of the body can be treated as a point mass and the summations can be done to obtain the expressions for the coordinates of centre of mass.

$$x_{CM} = \frac{\sum (\Delta m_{i}) x_{i}}{\sum \Delta m_{i}}$$

$$y_{CM} = \frac{\sum (\Delta m_{i}) y_{i}}{\sum \Delta m_{i}}$$

$$z_{CM} = \frac{\sum (\Delta m_{i}) z_{i}}{\sum \Delta m_{i}}$$
(5.5)

On the other hand, if the small mass taken is infinitesimally* small (dm) then, the summations can be replaced by integrations as given below.

$$x_{cm} = \frac{\int x dm}{\int dm}$$

$$y_{cm} = \frac{\int y dm}{\int dm}$$

$$z_{cm} = \frac{\int z dm}{\int dm}$$
(5.6)

EXAMPLE 5.4

Locate the centre of mass of a uniform rod of mass M and length ℓ .

Solution

Consider a uniform rod of mass M and length ℓ whose one end coincides with the origin as shown in Figure. The rod is kept along the x axis. To find the centre of mass

* Infinitesimal quantity is an extremely small quantity.

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES





of this rod, we choose an infinitesimally small mass dm of elemental length dx at a distance x from the origin.

 λ is the linear mass density (i.e. mass per unit length) of the rod. $\lambda = \frac{M}{\ell}$

The mass of small element (dm) is, $dm = \frac{M}{\ell} dx$

Now, we can write the centre of mass equation for this mass distribution as,

$$\begin{aligned} \mathbf{x}_{\rm CM} &= \frac{\int \mathbf{x} d\mathbf{m}}{\int d\mathbf{m}} \\ \mathbf{x}_{\rm CM} &= \frac{\int_{0}^{\ell} \mathbf{x} \left(\frac{M}{\ell} d\mathbf{x}\right)}{M} = \frac{1}{\ell} \int_{0}^{\ell} \mathbf{x} d\mathbf{x} \\ &= \frac{1}{\ell} \left[\frac{\mathbf{x}^{2}}{2}\right]_{0}^{1} = \frac{1}{\ell} \left(\frac{\ell^{2}}{2}\right) \\ \mathbf{x}_{\rm CM} &= \frac{\ell}{2} \end{aligned}$$

As the position $\frac{\ell}{2}$ is the geometric centre of the rod, it is concluded that the centre of mass of the uniform rod is located at its geometric centre itself.

5.1.6 Motion of Centre of Mass

When a rigid body moves, its centre of mass will also move along with the body. For kinematic quantities like velocity (v_{CM}) and acceleration (a_{CM}) of the centre of mass, we can differentiate the expression for position of centre of mass with respect to time once and twice respectively. For simplicity, let us take the motion along X direction only.

$$\vec{v}_{CM} = \frac{d\vec{x}_{CM}}{dt} = \frac{\sum m_i \left(\frac{d\vec{x}_i}{dt}\right)}{\sum m_i}$$

$$\vec{v}_{CM} = \frac{\sum m_i \vec{v}_i}{\sum m_i}$$
(5.7)
$$\vec{a}_{CM} = \frac{d}{dt} \left(\frac{d\vec{x}_{CM}}{dt}\right) = \left(\frac{d\vec{v}_{CM}}{dt}\right) = \frac{\sum m_i \left(\frac{d\vec{v}_i}{dt}\right)}{\sum m_i}$$

$$\vec{a}_{CM} = \frac{\sum m_i \vec{a}_i}{\sum m_i}$$
(5.8)

 \mathbf{M}_{i}

In the absence of external force, i.e.
$$\vec{F}_{ext} = 0$$
,
the individual rigid bodies of a system
can move or shift only due to the internal
forces. This will not affect the position of
the centre of mass. This means that the
centre of mass will be in a state of rest
or uniform motion. Hence, \vec{v}_{CM} will be
zero when centre of mass is at rest and
constant when centre of mass has uniform
motion ($\vec{v}_{CM} = 0$ or $\vec{v}_{CM} = \text{constant}$). There
will be no acceleration of centre of mass,
($\vec{a}_{CM} = 0$).

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

(214

 (\bullet)

From equation (5.7) and 5.8,

$$\vec{v}_{CM} = \frac{\sum m_i \vec{v}_i}{\sum m_i} = 0 \text{ (or) } \vec{v}_{CM} = \text{constant}$$

It implies
$$\vec{a}_{CM} = \frac{\sum m_i \vec{a}_i}{\sum m_i} = 0$$

Here, the individual particles may still move with their respective velocities and accelerations due to internal forces.

In the presence of external force, (i.e. $\vec{F}_{ext} \neq 0$), the centre of mass of the system will accelerate as given by the following equation.

$$\vec{F}_{ext} = \left(\sum m_i\right) \vec{a}_{CM}; \quad \vec{F}_{ext} = M \vec{a}_{CM}; \quad \vec{a}_{CM} = \frac{\vec{F}_{ext}}{M}$$

EXAMPLE 5.5

A man of mass 50 kg is standing at one end of a boat of mass 300 kg floating on still water. He walks towards the other end of the boat with a constant velocity of 2 m s^{-1} with respect to a stationary observer on land. What will be the velocity of the boat, (a) with respect to the stationary observer on land? (b) with respect to the man walking in the boat?



[Given: There is friction between the man and the boat and no friction between the boat and water.]

Solution

Mass of the man (m_1) is, $m_1 = 50$ kg Mass of the boat (m_2) is, $m_2 = 300$ kg With respect to a stationary observer:

The man moves with a velocity, $v_1 = 2 \text{ m s}^{-1}$ and the boat moves with a velocity v_2 (which is to be found)

(i) To determine the velocity of the boat with respect to a stationary observer on land:

As there is no external force acting on the system, the man and boat move due to the friction, which is an internal force in the boat-man system. Hence, the velocity of the centre of mass is zero ($v_{CM} = 0$).

Using equation 5.7,

$$0 = \frac{\sum m_i v_i}{\sum m_i} = \frac{m_1 v_1 + m_2 v_2}{m_1 + m_2}$$

$$0 = m_1 v_1 + m_2 v_2$$

$$-m_2 v_2 = m_1 v_1$$

$$v_2 = -\frac{m_1}{m_2} v_1$$

$$v_2 = -\frac{50}{300} \times 2 = -\frac{100}{300}$$

$$v_2 = -0.33 \,\mathrm{m \, s^{-1}}$$

The negative sign in the answer implies that the boat moves in a direction opposite to that of the walking man on the boat to a stationary observer on land.

(ii) To determine the velocity of the boat with respect to the walking man:We can find the relative velocity as,

 $v_{21} = v_2 - v_1$

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES



UNIT-5(XI-Physics_Vol-1).indd 215

where, v_{21} is the relative velocity of the boat with respect to the walking man.

$$v_{21} = (-0.33) - (2)$$

 $v_{21} = -2.33 \,\mathrm{ms}^{-1}$

The negative sign in the answer implies that the boat appears to move in the opposite direction to the man walking in the boat.

- The magnitude of the relative velocity of the boat with respect to the walking man is greater than the magnitude of the relative velocity of the boat with respect to the stationary observer.
- The negative signs in the two answers indicate the opposite direction of the boat with respect to the stationary observer and the walking man on the boat.

Centre of mass in explosions:

Many a times rigid bodies are broken in to fragments. If an explosion is caused by the internal forces in a body which is at rest or in motion, the state of the centre of mass is not affected. It continues to be in the same state of rest or motion. But, the kinematic quantities of the fragments get affected. If the explosion is caused by an external agency, then the kinematic quantities of the centre of mass as well as the fragments get affected.

EXAMPLE 5.6

A projectile of mass 5 kg, in its course of motion explodes on its own into two fragments. One fragment of mass 3 kg falls at three fourth of the range R of the projectile. Where will the other fragment fall?

Solution

It is an explosion of its own without any external influence. After the explosion, the centre of mass of the projectile will continue to complete the parabolic path even though the fragments are not following the same parabolic path. After the fragments have fallen on the ground, the centre of mass rests at a distance R (the range) from the point of projection as shown in the diagram.



If the origin is fixed to the final position of the centre of mass, the principle of moments holds good.

$$m_1 x_1 = m_2 x_2$$

where, $m_1 = 3$ kg, $m_2 = 2$ kg, $x_1 = \frac{1}{4}$ R. The value of $x_2 = d$

$$3 \times \frac{1}{4} R = 2 \times d;$$
$$d = \frac{3}{8} R$$

The distance between the point of launching and the position of 2 kg mass is R+d.

$$R + d = R + \frac{3}{8}R = \frac{11}{8}R = 1.375R$$

The other fragment falls at a distance of 1.375R from the point of launching. (Here R is the range of the projectile.)



UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

UNIT-5(XI-Physics_Vol-1).indd 216

۲

<u>5.2</u>

TORQUE AND ANGULAR MOMENTUM

When a net force acts on a body, it produces linear motion in the direction of the applied force. If the body is fixed to a point or an axis, such a force rotates the body depending on the point of application of the force on the body. This ability of the force to produce rotational motion in a body is called torque or moment of force. Examples for such motion are plenty in day to day life. To mention a few; the opening and closing of a door about the hinges and turning of a nut using a wrench.



The extent of the rotation depends on the magnitude of the force, its direction and the distance between the fixed point and the point of application. When torque produces rotational motion in a body, its angular momentum changes with respect to time. In this Section we will learn about the torque and its effect on rigid bodies.

5.2.1 Definition of Torque

Torque is defined as the moment of the external applied force about a point or axis of rotation. The expression for torque is,

$$\vec{\tau} = \vec{r} \times \vec{F}$$
 (5.9)

where, \vec{r} is the position vector of the point where the force \vec{F} is acting on the body as shown in Figure 5.4.



Here, the product of \vec{r} and \vec{F} is called the *vector product or cross product*. The vector product of two vectors results in another vector that is perpendicular to both the vectors (refer Section 2.5.2). Hence, torque $(\vec{\tau})$ is a vector quantity.

Torque has a magnitude $rFsin\theta$ and direction perpendicular to \vec{r} and \vec{F} . Its unit is N m.

$$\vec{\tau} = (\mathbf{r}\mathbf{F}\sin\theta)\hat{\mathbf{n}} \tag{5.10}$$

Here, θ is the angle between \vec{r} and \vec{F} , and \hat{n} is the unit vector in the direction of $\vec{\tau}$. Torque $(\vec{\tau})$ is sometimes called as a *pseudo vector* as it needs the other two vectors \vec{r} and \vec{F} for its existence.

The direction of torque is found using right hand rule. This rule says that if fingers of right hand are kept along the position vector with palm facing the direction of the force and when the fingers are curled the thumb points to the direction of the torque. This is shown in Figure 5.5.

The direction of torque helps us to find the type of rotation caused by the torque. For example, if the direction of torque is out

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES



of the paper, then the rotation produced by the torque is anticlockwise. On the other hand, if the direction of the torque is into the paper, then the rotation is clockwise as shown in Figure 5.6.

In many cases, the direction and magnitude of the torque are found

separately. For direction, we use the vector rule or right hand rule. For magnitude, we use scalar form as,

$$\tau = r F \sin \theta \qquad (5.11)$$

The expression for the magnitude of torque can be written in two different ways by associating $\sin \theta$ either with r or F in the following manner.

$$\tau = r \left(F \sin \theta \right) = r \times \left(F \bot \right) \quad (5.12)$$

$$\tau = (r \sin \theta) F = (r \perp) \times F \quad (5.13)$$

Here, $(F \sin\theta)$ is the component of \vec{F} perpendicular to \vec{r} . Similarly, $(r \sin\theta)$ is the component of \vec{r} perpendicular to \vec{F} . The two cases are shown in Figure 5.7.





Figure 5.7 Two ways of calculating the torque.

218 UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

۲

Based on the angle θ between \vec{r} and \vec{F} , the torque takes different values.

The torque is maximum when, \vec{r} and \vec{F} are perpendicular to each other. That is when $\theta = 90^{\circ}$ and sin $90^{\circ} = 1$, Hence, $\tau_{max} = rF$.

The torque is zero when \vec{r} and \vec{F} are parallel or antiparallel. If parallel, then $\theta = 0^{\circ}$ and sin $0^{\circ} = 0$. If antiparallel, then $\theta = 180^{\circ}$ and sin $180^{\circ} = 0$. Hence, $\tau = 0$.

The torque is zero if the force acts at the reference point. i.e. as $\vec{r} = 0$, $\tau = 0$. The different cases discussed are shown in Table 5.1.



EXAMPLE 5.7

If the force applied is perpendicular to the handle of the spanner as shown in the diagram, find the (i) torque exerted by the force about the centre of the nut, (ii) direction of torque and (iii) type of rotation caused by the torque about the nut.



Solution

۲

Arm length of the spanner, r = 15 cm $= 15 \times 10^{-2}$ m

Force, F = 2.5 N

Angle between r and F, $\theta = 90^{\circ}$

(i) Torque,
$$\tau = rF \sin \theta$$

$$\tau = 15 \times 10^{-2} \times 2.5 \times \sin(90^{\circ})$$

[here, sin 90° = 1]
 $\tau = 37.5 \times 10^{-2} \text{ N m}$

- (ii) As per the right hand rule, the direction of torque is out of the page.
- (iii) The type of rotation caused by the torque is anticlockwise.

EXAMPLE 5.8

A force of $(4\hat{i} - 3\hat{j} + 5\hat{k})N$ is applied at a point whose position vector is $(7\hat{i} + 4\hat{j} - 2\hat{k})m$. Find the torque of force about the origin.

Solution

$$\vec{r} = 7\hat{i} + 4\hat{j} - 2\hat{k}$$
$$\vec{F} = 4\hat{i} - 3\hat{j} + 5\hat{k}$$

Torque, $\vec{\tau} = \vec{r} \times \vec{F}$

$$\vec{\tau} = \begin{vmatrix} \hat{i} & \hat{j} & \hat{k} \\ 7 & 4 & -2 \\ 4 & -3 & 5 \end{vmatrix}$$
$$\vec{\tau} = \hat{i} (20 - 6) - \hat{j} (35 + 8) + \hat{k} (-21 - 16)$$
$$\vec{\tau} = (14\hat{i} - 43\hat{j} - 37\hat{k}) N m$$

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES



EXAMPLE 5.9

A crane has an arm length of 20 m inclined at 30° with the vertical. It carries a container of mass of 2 ton suspended from the top end of the arm. Find the torque produced by the gravitational force on the container about the point where the arm is fixed to the crane. [Given: 1 ton = 1000 kg; neglect the weight of the arm. $g = 10 \text{ m s}^{-2}$]



Solution

The force F at the point of suspension is due to the weight of the hanging mass.

 $F = mg = 2 \times 1000 \times 10 = 20000 \text{ N};$ The arm length, r = 20 m

We can solve this problem by three different methods.

Method - I

The angle (θ) between the arm length (r) and the force (F) is, $\theta = 150^{\circ}$

The torque (τ) about the fixed point of the arm is,

$$\tau = r F \sin \theta$$

$$\tau = 20 \times 20000 \times \sin(150^{\circ})$$

$$= 400000 \times \sin(90^{\circ} + 60^{\circ})$$

[here, $\sin(90^{\circ} + \theta) = \cos \theta$]

$$= 400000 \times \cos(60^{\circ})$$

$$= 400000 \times \frac{1}{2} \left[\cos 60^{\circ} = \frac{1}{2}\right]$$

$$= 200000 \text{ N m}$$

$$\tau = 2 \times 10^{5} \text{ N m}$$

Method – II

Let us take the force and perpendicular distance from the point where the arm is fixed to the crane.



Method – III

Let us take the distance from the fixed point and perpendicular force.

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

220



All the three methods, give the same answer.

5.2.2 Torque about an Axis

In the earlier sections, we have dealt with the torque about a point. In this section we will deal with the torque about an axis. Let us consider a rigid body capable of rotating about an axis AB as shown in Figure 5.8. Let the force F act at a point P on the rigid body. *The force F may not be on the plane ABP*. We can take the origin O at any random point on the axis AB.





Tamil Nadu is known for creative and innovative traditional games played by children. One such very popular game is "silli" (சில்லி) or "sillukodu" (சில்லுக்கோடு). There is a rectangular area which is further partitioned as seen in the Figure. One has to hop through the rectangles. While doing so, children lean on one side.

What is the reason?

Naturally the body takes this position to balance the gravitational force (mg) and Normal force (N) acting on the body and to nullify the torque. Failing which, both these forces act along different lines leading to a net torque which makes one to fall.

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

221

The torque of the force \vec{F} about O is, $\vec{\tau} = \vec{r} \times \vec{F}$. The component of the torque along the axis is the torque of \vec{F} about the axis. To find it, we should first find the vector $\vec{\tau} = \vec{r} \times \vec{F}$ and then find the angle ϕ between τ and AB. (Remember here, \vec{F} is not on the plane ABP). The torque about AB is the parallel component of the torque along AB, which is $|\vec{r} \times \vec{F}| \cos \phi$. And the torque perpendicular to the axis AB is $|\vec{r} \times \vec{F}| \sin \phi$.

The torque about the axis will rotate the object about it and the torque perpendicular to the axis will turn the axis of rotation. When both exist simultaneously on a rigid body, the body will have a *precession*. One can witness the precessional motion in a spinning top when it is about to come to rest as shown in Figure 5.9.



Figure 5.9 Precession of a spinning top

Study of precession is beyond the scope of the higher secondary physics course. Hence, it is assumed that there are constraints to cancel the effect of the perpendicular components of the torques, so that the fixed position of the axis is maintained. Therefore, perpendicular components of the torque need not be taken into account. Hereafter, for the calculation of torques on rigid bodies we will:

- 1. Consider only those forces that lie on planes perpendicular to the axis (and do not intersect the axis).
- 2. Consider position vectors which are perpendicular to the axis.

• Forces parallel to the axis will give torques perpendicular to the axis of rotation and need not be taken into account.

- Forces that intersect (pass through) the axis cannot produce torque as r = 0.
- Position vectors along the axis will result in torques perpendicular to the axis and need not be taken into account.

EXAMPLE 5.10

Three mutually perpendicular beams AB, OC, GH are fixed to form a structure which is fixed to the ground firmly as shown in the Figure. One string is tied to the point C and its free end D is pulled with a force F. Find the magnitude and direction of the torque produced by the force,



(i) about the points D, C, O and B
(ii) about the axes CD, OC, AB and GH.

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

Solution

(i) Torque about point D is zero. (as F passes through D).

Torque about point C is zero. (as F passes through C).

Torque about point O is $(\overrightarrow{OC}) \times F$ and direction is along GH.

Torque about point B is $(\overline{BD}) \times \overline{F}$ and direction is along GH

(The perpendicular distance of \overrightarrow{BD} with respect to \vec{F} is OC).

(ii) Torque about axis CD is zero (as F is parallel to CD).

Torque about axis OC is zero (as F intersects OC).

Torque about axis AB is zero (as F is parallel to AB).

Torque about axis GH is $(\overline{OC}) \times F$ and direction is along GH.

The torque of a force about an axis is independent of the choice of the origin as long as it is chosen on that axis itself. This can be shown as below.

Let O be the origin on the axis AB, which is the rotational axis of a rigid body. F is the force acting at the point P. Now, choose another point O' anywhere on the axis as shown in Figure 5.10.



Figure 5.10 Torque about an axis is independent of origin



(in Tamil, 'Marasekku' மரச்செக்கு)

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES



 (\bullet)

The torque of F about O' is,

$$\overrightarrow{O'P} \times \overrightarrow{F} = \left(\overrightarrow{O'O} + \overrightarrow{OP}\right) \times \overrightarrow{F}$$
$$= \left(\overrightarrow{O'O} \times \overrightarrow{F}\right) + \left(\overrightarrow{OP} \times \overrightarrow{F}\right)$$

As O'O × \vec{F} is perpendicular to O'O, this term will not have a component along AB. Thus, the component of $\overrightarrow{O'P} \times \vec{F}$ is equal to that of $\overrightarrow{OP} \times \vec{F}$.

5.2.3 Torque and Angular Acceleration

Let us consider a rigid body rotating about a fixed axis. A point mass m in the body will execute a circular motion about a fixed axis as shown in Figure 5.11. A tangential force \vec{F} acting on the point mass produces the necessary torque for this rotation. This force \vec{F} is perpendicular to the position vector \vec{r} of the point mass.



Figure 5.11 Torque and Angular acceleration

The torque produced by the force on the point mass m about the axis can be written as,

$$\tau = r F \sin 90^\circ = r F \quad [\because \sin 90^\circ = 1]$$

$$\tau = r ma \qquad [\because (F = ma)]$$

$$\tau = r m r\alpha = mr^2 \alpha \qquad [\because (a = r\alpha)]$$

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

$$\tau = (mr^2)\alpha \qquad (5.14)$$

Hence, the torque of the force acting on the point mass produces an angular acceleration (α) in the point mass about the axis of rotation.

In vector notation,

$$\vec{\tau} = \left(mr^2\right)\vec{\alpha} \qquad (5.15)$$

The directions of τ and α are along the axis of rotation. If the direction of τ is in the direction of α , it produces angular acceleration. On the other hand if, τ is opposite to α , angular deceleration or retardation is produced on the point mass.

The term mr^2 in equations 5.14 and 5.15 is called moment of inertia (I) of the point mass. A rigid body is made up of many such point masses. Hence, the moment of inertia of a rigid body is the sum of moments of inertia of all such individual point masses that constitute the body $(I = \sum m_i r_i^2)$. Hence, torque for the rigid body can be written as,

$$\vec{\tau} = \left(\sum m_i r_i^2\right) \vec{\alpha} \qquad (5.16)$$

$$\vec{\tau} = I\vec{\alpha}$$
 (5.17)

We will learn more about the moment of inertia and its significance for bodies with different shapes in section 5.4.

5.2.4 Angular Momentum

The angular momentum in rotational motion is equivalent to linear momentum in translational motion. The angular

momentum of a point mass is defined as the moment of its linear momentum. In other words, the angular momentum L of a point mass having a linear momentum p at a position r with respect to a point or axis is mathematically written as,

$$\vec{L} = \vec{r} \times \vec{p} \tag{5.18}$$

The magnitude of angular momentum could be written as,

$$\mathbf{L} = \mathbf{r} \, \mathbf{p} \sin \theta \tag{5.19}$$

where, θ is the angle between \vec{r} and \vec{p} . \vec{L} is perpendicular to the plane containing \vec{r} and \vec{p} . As we have written in the case of torque, here also we can associate $\sin \theta$ with either \vec{r} or \vec{p} .

$$L = r(p\sin\theta) = r(p\perp)$$
(5.20)
$$L = (r\sin\theta)p = (r\perp)p$$
(5.21)

where, $p\perp$ is the component of linear momentum p perpendicular to r, and $r\perp$ is the component of position r perpendicular to p.

The angular momentum is zero (L=0), if the linear momentum is zero (p = 0) or if the particle is at the origin $(\vec{r} = 0)$ or if \vec{r} and \vec{p} are parallel or antiparallel to each other (θ = 0⁰ or 180⁰).

There is a misconception that the angular momentum is a quantity that is associated only with rotational motion. It is not true. The angular momentum is also associated with bodies in the linear motion. Let us understand the same with the following example.

EXAMPLE 5.11

A particle of mass (m) is moving with constant velocity (v). Show that its angular momentum about any point remains constant throughout the motion.

Solution



Let the particle of mass m move with constant velocity \vec{v} . As it is moving with constant velocity, its path is a straight line. Its momentum $(\vec{p} = m\vec{v})$ is also directed along the same path. Let us fix an origin (O) at a perpendicular distance (d) from the path. At a particular instant, we can connect the particle which is at position Q with a position vector $(\vec{r} = \overrightarrow{OQ})$.

Take, the angle between the \vec{r} and \vec{p} as θ . The magnitude of angular momentum of that particle at that instant is,

 $L = OQ p \sin \theta = OQ mv \sin \theta = mv (OQ \sin \theta)$

The term $(OQ \sin\theta)$ is the perpendicular distance (d) between the origin and line along which the mass is moving. Hence, the angular momentum of the particle about the origin is,

L = mvd

The above expression for angular momentum L, does not have the angle θ . As the momentum (p = mv) and the

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

perpendicular distance (d) are constants, the angular momentum of the particle is also constant. Hence, the angular momentum is associated with bodies with linear motion also. If the straight path of the particle passes through the origin, then the angular momentum is zero, which is also a constant.

5.2.5 Angular Momentum and Angular Velocity

Let us consider a rigid body rotating about a fixed axis. A point mass m in the body will execute a circular motion about the fixed axis as shown in Figure 5.12.



The point mass m is at a distance r from the axis of rotation. Its linear momentum at any instant is tangential to the circular path. Then the angular momentum \vec{L} is perpendicular to \vec{r} and \vec{p} . Hence, it is directed along the axis of rotation. The angle θ between \vec{r} and \vec{p} in this case is 90°. The magnitude of the angular momentum L could be written as,

 $L = r mv sin 90^{\circ} = r mv$

where, v is the linear velocity. The relation between linear velocity v and angular velocity ω in a circular motion is, v = r ω . Hence,

$$L = rmr\omega$$
$$L = (mr^{2})\omega \qquad (5.22)$$

The directions of L and ω are along the axis of rotation. The above expression can be written in the vector notation as,

$$\vec{L} = (mr^2)\vec{\omega}$$
 (5.23)

As discussed earlier, the term mr^2 in equations 5.22 and 5.23 is called moment of inertia (I) of the point mass. A rigid body is made up of many such point masses. Hence, the moment of inertia of a rigid body is the sum of moments of inertia of all such individual point masses that constitute the body $(I = \sum m_i r_i^2)$. Hence, the angular momentum of the rigid body can be written as,

$$\vec{L} = \left(\sum m_i r_i^2\right) \vec{\omega} \qquad (5.24)$$

$$\vec{L} = I\vec{\omega} \tag{5.25}$$

The study about moment of inertia (I) is reserved for Section 5.4.

5.2.6 Torque and Angular Momentum

We have the expression for magnitude of angular momentum of a rigid body as, $L = I\omega$. The expression for magnitude of torque on a rigid body is, $\tau = I\alpha$

We can further write the expression for torque as,

$$\tau = I \frac{d\omega}{dt} \quad \because \left(\alpha = \frac{d\omega}{dt}\right) \tag{5.26}$$

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

Where, ω is angular velocity and α is angular acceleration. We can also write equation 5.26 as,

$$\tau = \frac{d(I\omega)}{dt}$$
$$\tau = \frac{dL}{dt}$$
(5.27)

The above expression says that an external torque on a rigid body fixed to an axis produces rate of change of angular momentum in the body about that axis. This is the Newton's second law in rotational motion as it is in the form of $F = \frac{dp}{dt}$ which holds good for translational motion.

Conservation of angular momentum:

From the above expression we could conclude that in the absence of external torque, the angular momentum of the rigid body or system of particles is conserved.

If
$$\tau = 0$$
 then, $\frac{dL}{dt} = 0$; L = constant

The above expression is known as law of conservation of angular momentum. We will learn about this law further in section 5.5.

5.3

EQUILIBRIUM OF RIGID BODIES

When a body is at rest without any motion on a table, we say that there is no force acting on the body. Actually it is wrong because, there is gravitational force acting on the body downward and also the normal force exerted by table on the body upward. These two forces cancel each other and thus there is no net force acting on the body. There is a lot of difference between the terms "no force" and "no net force" acting on a body. The same argument holds good for rotational conditions in terms of torque or moment of force.

A rigid body is said to be in mechanical equilibrium when both its linear momentum and angular momentum remain constant.

When the linear momentum remains constant, the net force acting on the body is zero.

$$\vec{F}_{net} = 0$$
 (5.28)

In this condition, the body is said to be in translational equilibrium. This implies that the vector sum of different forces $\vec{F}_1, \vec{F}_2, \vec{F}_3...$ acting in different directions on the body is zero.

$$\vec{F}_1 + \vec{F}_2 + \vec{F}_3 + \dots + \vec{F}_n = 0$$
 (5.29)

If the forces $\vec{F}_1, \vec{F}_2, \vec{F}_3...$ act in different directions on the body, we can resolve them into horizontal and vertical components and then take the resultant in the respective directions. In this case there will be horizontal as well as vertical equilibria possible.

Similarly, when the angular momentum remains constant, the net torque acting on the body is zero.

$$\vec{\tau}_{net} = 0 \tag{5.30}$$

Under this condition, the body is said to be in rotational equilibrium. The vector sum of different torques $\vec{\tau}_1, \vec{\tau}_2, \vec{\tau}_3...$ producing different senses of rotation on the body is zero.

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

$$\vec{\tau}_1 + \vec{\tau}_2 + \vec{\tau}_3 + \dots + \vec{\tau}_n = 0$$
 (5.31)

Thus, we can also conclude that a rigid body is in mechanical equilibrium when the net force and net torque acts on the body is zero.

$$\vec{F}_{net} = 0$$
 and $\vec{\tau}_{net} = 0$ (5.32)

As the forces and torques are vector quantities, the directions are to be taken with proper sign conventions.

5.3.1 Types of Equilibrium

Based on the above discussions, we come to a conclusion that different types of equilibrium are possible based on the different conditions. They are consolidated in Table 5.2.

Table 5.2	Different types of Equilibrium and their Conditions.
Type of	Conditions
equilibrium	
Translational	Linear momentum is constant.
equilibrium	 Net force is zero.
Rotational	 Angular momentum is constant.
equilibrium	 Net torque is zero.
Static	 Linear momentum and angular momentum are zero.
equilibrium	 Net force and net torque are zero.
Dynamic	 Linear momentum and angular momentum are constant.
equilibrium	 Net force and net torque are zero.
Stable	 Linear momentum and angular momentum are zero.
equilibrium	• The body tries to come back to equilibrium if slightly disturbed and
	released.
	 The centre of mass of the body shifts slightly higher if disturbed from equilibrium.
	 Potential energy of the body is minimum and it increases if disturbed.
Unstable	Linear momentum and angular momentum are zero.
equilibrium	 The body cannot come back to equilibrium if slightly disturbed and released.
	The centre of mass of the body shifts slightly lower if disturbed from
	equilibrium.
	• Potential energy of the body is not minimum and it decreases if disturbed.
Neutral	 Linear momentum and angular momentum are zero.
equilibrium	• The body remains at the same equilibrium if slightly disturbed and
	released.
	• The centre of mass of the body does not shift higher or lower if disturbed
	from equilibrium.
	 Potential energy remains same even if disturbed.

۲



()

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

۲

EXAMPLE 5.12

Arun and Babu carry a wooden log of mass 28 kg and length 10 m which has almost uniform thickness. They hold it at 1 m and 2 m from the ends respectively. Who will bear more weight of the log? $[g = 10 \text{ ms}^{-2}]$

Solution

Let us consider the log is in mechanical equilibrium. Hence, the net force and net torque on the log must be zero. The gravitational force acts at the centre of mass of the log downwards. It is cancelled by the normal reaction forces R_A and R_B applied upwards by Arun and Babu at points A and B respectively. These reaction forces are the weights borne by them.

The total weight, $W = mg = 28 \times 10 = 280$ N, has to be borne by them together. The reaction forces are the weights borne by each of them separately. Let us show all the forces acting on the log by drawing a free body diagram of the log.

For translational equilibrium:

The net force acting on the log must be zero.

$$R_{A} + (-mg) + R_{B} = 0$$

Here, the forces R_A an R_B are taken positive as they act upward. The gravitational force acting downward is taken negative.

$$R_A + R_B = mg$$

For rotational equilibrium:



The net torque acting on the log must be zero. For ease of calculation, we can take the torque caused by all the forces about the point A on the log. The forces are perpendicular to the distances. Hence,

$$\left(0R_{A}\right)+\left(-4mg\right)+\left(7R_{B}\right)=0.$$

Here, the reaction force R_A cannot produce any torque as the reaction forces pass through the point of reference A. The torque of force mg produces a clockwise turn about the point A which is taken negative and torque of force R_B causes anticlockwise turn about A which is taken positive.

$$7R_{B} = 4mg$$
$$R_{B} = \frac{4}{7}mg$$
$$R_{B} = \frac{4}{7} \times 28 \times 10 = 160 N$$

By substituting for R_{B} we get,

$$R_A = mg - R_B$$

 $R_A = 28 \times 10 - 160 = 280 - 160 = 120 N$

As R_{B} is greater than R_{A} , it is concluded that Babu bears more weight than Arun. The one closer to centre of mass of the log bears more weight.

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

5.3.2 Couple

Consider a thin uniform rod AB. Its centre of mass is at its midpoint C. Let two forces which are equal in magnitude and opposite in direction be applied at the two ends A and B of the rod perpendicular to it. The two forces are separated by a distance of 2r as shown in Figure 5.13.



As the two equal forces are opposite in direction, they cancel each other and the net force acting on the rod is zero. Now the rod is in translational equilibrium. But, the rod is not in rotational equilibrium. Let us see how it is not in rotational equilibrium. The moment of the force applied at the end A taken with respect to the centre point C, produces an anticlockwise rotation. Similarly, the moment of the force applied at the end B also produces an anticlockwise rotation. The moments of both the forces cause the same sense of rotation in the rod. Thus, the rod undergoes a rotational motion or turning even though the rod is in translational equilibrium.

A pair of forces which are equal in magnitude but opposite in direction and separated by a perpendicular distance so that their lines of action do not coincide that causes a turning effect is called a couple. We come across couple in many of our daily activities as shown in Figure 5.14.

Note Note There are cases in which the two forces may not cancel each other. If the two forces are not equal or the direction of the forces is not exactly opposite, then the body will have both translational as well as rotational motion.

5.3.3 Principle of Moments

Consider a light rod of negligible mass which is pivoted at a point along its length. Let two parallel forces F_1 and F_2 act at the two ends at distances d_1 and d_2 from the point of pivot and the normal reaction force N at





UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

the point of pivot as shown in Figure 5.15. If the rod has to remain stationary in horizontal position, it should be in translational and rotational equilibrium. Then, both the net force and net torque must be zero.



Figure 5.15 Principle of Moments

For translational equilibrium, net force has to be zero, $-F_1 + N - F_2 = 0$

$$N = F_1 + F_2$$

For rotational equilibrium,

net torque has to be zero, $d_1F_1 - d_2F_2 = 0$

$$\mathbf{d}_{1}\mathbf{F}_{1} = \mathbf{d}_{2}\mathbf{F}_{2} \tag{5.33}$$

The above equation represents the *principle of moments*. This forms the principle for beam balance used for weighing goods with the condition $d_1 = d_2$; $F_1 = F_2$. We can rewrite the equation 5.33 as,

$$\frac{F_1}{F_2} = \frac{d_2}{d_1}$$
(5.34)

If F_1 is the load and F_2 is our effort, we get advantage when, $d_1 < d_2$. This implies that $F_1 > F_2$. Hence, we could lift a large load with small effort. The ratio $\left(\frac{d_2}{d_1}\right)$ is called mechanical advantage of the simple lever. The pivoted point is called fulcrum.

Mechanical Advantage(MA) =
$$\frac{d_2}{d_1}$$
 (5.35)

There are many simple machines that work on the above mentioned principle.

5.3.4 Centre of Gravity

۲

Each rigid body is made up of several point masses. Such point masses experience gravitational force towards the centre of Earth. As the size of Earth is very large compared to any practical rigid body we come across in daily life, these forces appear to be acting parallelly downwards as shown in Figure 5.16.



Figure 5.16. Centre of gravity

The resultant of these parallel forces always acts through a point. This point is called centre of gravity of the body (with respect to Earth). The centre of gravity of a body is the point at which the entire weight of the body acts irrespective of the position and orientation of the body. The centre of gravity and centre of mass of a rigid body coincide when the gravitational field is uniform across the body. The concept of gravitational field is dealt in Unit 6.

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES



We can also determine the centre of gravity of a uniform lamina of even an irregular shape by pivoting it at various points by trial and error. The lamina remains horizontal when pivoted at the point where the net gravitational force acts, which is the centre of gravity as shown in Figure 5.17. When a body is supported at the centre of gravity, the sum of the torques acting on all the point masses of the rigid body becomes zero. Moreover the weight is compensated by the normal reaction force exerted by the pivot. The body is in static equilibrium and hence it remains horizontal.



Figure 5.17. Determination of centre of gravity of plane lamina by pivoting

There is also another way to determine the centre of gravity of an irregular lamina. If we suspend the lamina from different



Figure 5.18 Determination of centre of gravity of plane lamina by suspending

points like P, Q, R as shown in Figure 5.18, the vertical lines PP', QQ', RR' all pass through the centre of gravity. Here, reaction force acting at the point of suspension and the gravitational force acting at the centre of gravity cancel each other and the torques caused by them also cancel each other.



5.3.5 Bending of Cyclist in Curves

Let us consider a cyclist negotiating a circular level road (not banked) of radius r with a speed v. The cycle and the cyclist are considered as one system with mass m. The centre gravity of the system is C and it goes in a circle of radius r with centre at O. Let us choose the line OC as X-axis and the vertical line through O as Z-axis as shown in Figure 5.19.



Figure 5.19 Bending of cyclist

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

UNIT-5(XI-Physics_Vol-1).indd 232

The system as a frame is rotating about Z-axis. The system is at rest in this rotating frame. To solve problems in rotating frame of reference, we have to apply a centrifugal force (pseudo force) on the system which will be $\frac{mv^2}{r}$. This force will act through the centre of gravity. The forces acting on the system are, (i) gravitational force (mg), (ii) normal force (N), (iii) frictional force (f) and (iv) centrifugal force $\left(\frac{mv^2}{r}\right)$. As the system is in equilibrium in the rotational frame of reference, the net external force and net external torque must be zero. Let us consider all torques about the point A in Figure 5.20.



Figure 5.20 Force diagrams for the cyclist in turns

For rotational equilibrium,

$$\vec{\tau}_{net} = 0$$

The torque due to the gravitational force about point A is (mgAB) which causes a clockwise turn that is taken as negative. The torque due to the centrifugal force is $\left(\frac{mv^2}{r}BC\right)$ which causes an anticlockwise turn that is taken as positive.

$$-mg AB + \frac{mv^{2}}{r}BC = 0$$
$$mg AB = \frac{mv^{2}}{r}BC$$

From
$$\Delta$$
 ABC,

 $(\mathbf{0})$

 $AB = AC\sin\theta$ and $BC = AC\cos\theta$

mg AC sin
$$\theta = \frac{mv^2}{r} AC \cos \theta$$

tan $\theta = \frac{v^2}{rg}$
 $\theta = \tan^{-1}\left(\frac{v^2}{rg}\right)$ (5.36)

While negotiating a circular level road of radius r at velocity v, a cyclist has to bend by an angle θ from vertical given by the above expression to stay in equilibrium (i.e. to avoid a fall).

EXAMPLE 5.13

A cyclist while negotiating a circular path with speed 20 m s⁻¹ is found to bend an angle by 30° with vertical. What is the radius of the circular path? (given, $g = 10 \text{ m s}^{-2}$)

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES



()

Solution

Speed of the cyclist, $v = 20 \text{ m s}^{-1}$ Angle of bending with vertical, $\theta = 30^{\circ}$ Equation for angle of bending, $\tan \theta = \frac{v^2}{rg}$ Rewriting the above equation for radius $r = \frac{v^2}{\tan \theta g}$

Substituting,

$$r = \frac{(20)^2}{(\tan 30^\circ) \times 10} = \frac{20 \times 20}{(\tan 30^\circ) \times 10}$$
$$= \frac{400}{\left(\frac{1}{\sqrt{3}}\right) \times 10}$$
$$r = (\sqrt{3}) \times 40 = 1.732 \times 40$$
$$r = 69.28 \text{ m}$$

5.4 MOMENT OF INERTIA

In the expressions for torque and angular momentum for rigid bodies (which are considered as bulk objects), we have come across a term $\sum m_i r_i^2$. This quantity is called moment of inertia (I) of the bulk object. For point mass m_i at a distance r_i from the fixed axis, the moment of inertia is given as, $m_i r_i^2$.

Moment of inertia for point mass,

$$I = m_i r_i^2$$
 (5.37)

Moment of inertia for bulk object,

$$I = \sum m_i r_i^2 \qquad (5.38)$$

In translational motion, mass is a measure of inertia; in the same way, for rotational

234

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

motion, moment of inertia is a measure of rotational inertia. The unit of moment of inertia is, kg m². Its dimension is ML^2 . In general, mass is an invariable quantity of matter (except for motion comparable to that of light). But, the moment of inertia of a body is not an invariable quantity. It depends not only on the mass of the body, but also on the way the mass is distributed around the axis of rotation.

To find the moment of inertia of a uniformly distributed mass; we have to consider an infinitesimally small mass (dm) as a point mass and take its position (r) with respect to an axis. The moment of inertia of this point mass can now be written as,

$$dI = (dm)r^2 \qquad (5.39)$$

We get the moment of inertia of the entire bulk object by integrating the above expression.

$$I = \int dI = \int (dm) r^{2}$$
$$I = \int r^{2} dm \qquad (5.40)$$

We can use the above expression for determining the moment of inertia of some of the common bulk objects of interest like rod, ring, disc, sphere etc.

5.4.1 Moment of Inertia of a Uniform Rod

Let us consider a uniform rod of mass (M) and length (ℓ) as shown in Figure 5.21. Let us find an expression for moment of inertia of this rod about an axis that passes through the centre of mass and perpendicular to



the rod. First an origin is to be fixed for the coordinate system so that it coincides with the centre of mass, which is also the geometric centre of the rod. The rod is now along the x axis. We take an infinitesimally small mass (dm) at a distance (x) from the origin. The moment of inertia (dI) of this mass (dm) about the axis is,

$dI = (dm)x^2$

As the mass is uniformly distributed, the mass per unit length (λ) of the rod is, $\lambda = \frac{M}{\ell}$

The (dm) mass of the infinitesimally small length as, $dm = \lambda dx = \frac{M}{\ell} dx$

The moment of inertia (I) of the entire rod can be found by integrating dI,

$$I = \int dI = \int (dm) x^{2} = \int \left(\frac{M}{\ell} dx\right) x^{2}$$
$$I = \frac{M}{\ell} \int x^{2} dx$$

As the mass is distributed on either side of the origin, the limits for integration are taken from $-\ell/2$ to $\ell/2$.

$$I = \frac{M}{\ell} \int_{-\ell/2}^{\ell/2} x^2 dx = \frac{M}{\ell} \left[\frac{x^3}{3} \right]_{-\ell/2}^{\ell/2}$$
$$I = \frac{M}{\ell} \left[\frac{\ell^3}{24} - \left(-\frac{\ell^3}{24} \right) \right] = \frac{M}{\ell} \left[\frac{\ell^3}{24} + \frac{\ell^3}{24} \right]$$
$$I = \frac{M}{\ell} \left[2 \left(\frac{\ell^3}{24} \right) \right]$$
$$I = \frac{1}{12} M \ell^2$$
(5.41)

EXAMPLE 5.14

Find the moment of inertia of a uniform rod about an axis which is perpendicular to the rod and touches any one end of the rod.

Solution

The concepts to form the integrand to find the moment of inertia could be borrowed from the earlier derivation. Now, the origin is fixed to the left end of the rod and the limits are to be taken from 0 to ℓ .



UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

235

 \bigcirc

The moment of inertia of the same uniform rod is different about different axes of reference. The reference axes could be even outside the object. We have two useful theorems to calculate the moments of inertia about different axes. We shall see these theorems in Section 5.4.5.

5.4.2 Moment of Inertia of a Uniform Ring

Let us consider a uniform ring of mass M and radius R. To find the moment of inertia of the ring about an axis passing through its centre and perpendicular to the plane, let us take an infinitesimally small mass (dm) of length (dx) of the ring. This (dm) is located at a distance R, which is the radius of the ring from the axis as shown in Figure 5.22.



The moment of inertia (dI) of this small mass (dm) is,

 $dI = (dm)R^2$

The length of the ring is its circumference $(2\pi R)$. As the mass is uniformly

distributed, the mass per unit length (λ) is,

$$\lambda = \frac{\text{mass}}{\text{length}} = \frac{M}{2\pi R}$$

The mass (dm) of the infinitesimally small length is, dm = $\lambda dx = \frac{M}{2\pi R} dx$

Now, the moment of inertia (I) of the entire ring is,

$$I = \int dI = \int (dm) R^{2} = \int \left(\frac{M}{2\pi R} dx\right) R^{2}$$
$$I = \frac{MR}{2\pi} \int dx$$

To cover the entire length of the ring, the limits of integration are taken from 0 to $2\pi R$.

$$I = \frac{MR}{2\pi} \int_{0}^{2\pi R} dx$$
$$I = \frac{MR}{2\pi} [x]_{0}^{2\pi R} = \frac{MR}{2\pi} [2\pi R - 0]$$
$$I = MR^{2}$$
(5.42)

5.4.3 Moment of Inertia of a Uniform Disc

Consider a disc of mass M and radius R. This disc is made up of many infinitesimally small rings as shown in Figure 5.23. Consider one such ring of mass (dm) and thickness (dr) and radius (r). The moment of inertia (dI) of this small ring is,

$$dI = (dm)r^2$$

As the mass is uniformly distributed, the mass per unit area (σ) is, $\sigma = \frac{\text{mass}}{\text{area}} = \frac{M}{\pi R^2}$

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

236

 (\bullet)

()





The mass of the infinitesimally small ring is,

$$dm = \sigma 2\pi r dr = \frac{M}{\pi R^2} 2\pi r dr$$

where, the term $(2\pi r dr)$ is the area of this elemental ring $(2\pi r \text{ is the length and } dr \text{ is}$ the thickness). $dm = \frac{2M}{R^2} r dr$

$$dI = \frac{2M}{R^2}r^3dr$$

The moment of inertia (I) of the entire disc is,

$$I = \int dI$$

$$I = \int_{0}^{R} \frac{2M}{R^{2}} r^{3} dr = \frac{2M}{R^{2}} \int_{0}^{R} r^{3} dr$$

$$I = \frac{2M}{R^{2}} \left[\frac{r^{4}}{4} \right]_{0}^{R} = \frac{2M}{R^{2}} \left[\frac{R^{4}}{4} - 0 \right]$$

$$I = \frac{1}{2} MR^{2}$$
(5.43)

5.4.4 Radius of Gyration

For bulk objects of regular shape with uniform mass distribution, the expression for moment of inertia about an axis involves their total mass and geometrical features like radius, length, breadth, which take care of the shape and the size of the objects. But, we need an expression for the moment of inertia which could take care of not only the mass, shape and size of objects, but also its orientation to the axis of rotation. Such an expression should be general so that it is applicable even for objects of irregular shape and non-uniform distribution of mass. The general expression for moment of inertia is given as,

$$I = M K^2 \tag{5.44}$$

where, M is the total mass of the object and K is called the radius of gyration.

The radius of gyration of an object is the perpendicular distance from the axis of rotation to an equivalent point mass, which would have the same mass as well as the same moment of inertia of the object.

As the radius of gyration is distance, its unit is m. Its dimension is [L].

A rotating rigid body with respect to any axis, is considered to be made up of point masses $m_1, m_2, m_3, \ldots, m_n$ at perpendicular distances (or positions) $r_1, r_2, r_3 \ldots r_n$ respectively as shown in Figure 5.24.

The moment of inertia of that object can be written as,

$$I = \sum_{i=1}^{n} m_{i} r_{i}^{2} = m_{1} r_{1}^{2} + m_{2} r_{2}^{2} + m_{3} r_{3}^{2} + \dots + m_{n} r_{n}^{2}$$

If we take all the n number of individual masses to be equal,

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES





$$m = m_1 = m_2 = m_3 = \ldots = m_n$$

then,

$$I = mr_1^2 + mr_2^2 + mr_3^2 + \dots + mr_n^2$$
$$= m(r_1^2 + r_2^2 + r_3^2 + \dots + r_n^2)$$
$$= nm\left(\frac{r_1^2 + r_2^2 + r_3^2 + \dots + r_n^2}{n}\right)$$
$$I = MK^2$$

where, nm is the total mass M of the body and K is the radius of gyration.

$$K = \sqrt{\frac{r_1^2 + r_2^2 + r_3^2 + \dots + r_n^2}{n}} \quad (5.45)$$

The expression for radius of gyration indicates that it is the root mean square (rms) distance of the particles of the body from the axis of rotation. In fact, the moment of inertia of any object could be expressed in the form, $I = MK^2$.

۲

For example, let us take the moment of inertia of a uniform rod of mass M and length ℓ . Its moment of inertia with respect to a perpendicular axis passing through the centre of mass is, $I = \frac{1}{12}M\ell^2$

In terms of radius of gyration, $I = MK^2$ Hence, $MK^2 = \frac{1}{12}M\ell^2$ $K^2 = \frac{1}{12}\ell^2$ $K = \frac{1}{\sqrt{12}}\ell$ or $K = \frac{1}{2\sqrt{3}}\ell$ or $K = (0.289)\ell$

EXAMPLE 5.15

Find the radius of gyration of a disc of mass M and radius R rotating about an axis passing through the centre of mass and perpendicular to the plane of the disc.

Solution

The moment of inertia of a disc about an axis passing through the centre of mass and perpendicular to the disc is, $I = \frac{1}{2}MR^2$ In terms of radius of gyration, $I = MK^2$ Hence, $MK^2 = \frac{1}{2}MR^2$; $K^2 = \frac{1}{2}R^2$ $K = \frac{1}{\sqrt{2}}R$ or $K = \frac{1}{1.414}R$ or K = (0.707)R

From the case of a rod and also a disc, we can conclude that the radius of gyration of the rigid body is always a geometrical feature like length, breadth, radius or their combinations with a positive numerical value multiplied to it.

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

238



Obesity and associated ailments like back pain, joint pain etc. are due to the shift in centre of mass of the body. Due to this shift in centre of mass, unbalanced torque acting on the body leads to ailments. As the mass is spread away from centre of the body the moment of inertia is more and turning will also be difficult.

5.4.5 Theorems of Moment of Inertia

As the moment of inertia depends on the axis of rotation and also the orientation of the body about that axis, it is different for the same body with different axes of rotation. We have two important theorems to handle the case of shifting the axis of rotation.

(i) Parallel axis theorem:

Parallel axis theorem states that the moment of inertia of a body about any axis is equal to the sum of its moment of inertia about a parallel axis through its centre of mass and the product of the mass of the body and the square of the perpendicular distance between the two axes. If I_c is the moment of inertia of the body of mass M about an axis passing through the centre of mass, then the moment of inertia I about a parallel axis at a distance d from it is given by the relation,

$$I = I_{c} + Md^{2}$$
 (5.46)

Let us consider a rigid body as shown in Figure 5.25. Its moment of inertia about an axis AB passing through the centre of mass is I_c . DE is another axis parallel to AB at a perpendicular distance d from AB. The moment of inertia of the body about DE is I. We attempt to get an expression for I in terms of I_c . For this, let us consider a point mass m on the body at position x from its centre of mass.



The moment of inertia of the point mass about the axis DE is, $m(x+d)^2$.

The moment of inertia I of the whole body about DE is the summation of the above expression.

$$I = \sum m(x+d)^2$$

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

This equation could further be written as,

$$I = \sum m(x^{2} + d^{2} + 2xd)$$
$$I = \sum (mx^{2} + md^{2} + 2dmx)$$
$$I = \sum mx^{2} + \sum md^{2} + 2d\sum mx$$

Here, $\sum mx^2$ is the moment of inertia of the body about the centre of mass. Hence, $I_c = \sum mx^2$

The term, $\sum mx = 0$ because, x can take positive and negative values with respect to the axis AB. The summation $(\sum mx)$ will be zero.

Thus,
$$I = I_{c} + \sum md^{2} = I_{c} + (\sum m)d^{2}$$

Here, $\sum m$ is the entire mass M of the object $(\sum m = M)$

 $I = I_{C} + Md^{2}$

Hence, the parallel axis theorem is proved.

(ii) Perpendicular axis theorem:

This perpendicular axis theorem holds good only for plane laminar objects.

The theorem states that the moment of inertia of a plane laminar body about an axis perpendicular to its plane is equal to the sum of moments of inertia about two perpendicular axes lying in the plane of the body such that all the three axes are mutually perpendicular and have a common point.

Let the X and Y-axes lie in the plane and Z-axis perpendicular to the plane of the laminar object. If the moments of inertia of the body about X and Y-axes are I_x and I_y respectively and I_z is the moment of inertia about Z-axis, then the perpendicular axis theorem could be expressed as,

$$I_{z} = I_{x} + I_{y} \tag{5.47}$$

To prove this theorem, let us consider a plane laminar object of negligible thickness on which lies the origin (O). The X and Y-axes lie on the plane and Z-axis is perpendicular to it as shown in Figure 5.26. The lamina is considered to be made up of a large number of particles of mass m. Let us choose one such particle at a point P which has coordinates (x, y) at a distance r from O.



Figure 5.26 Perpendicular axis theorem

The moment of inertia of the particle about Z-axis is, mr^2

The summation of the above expression gives the moment of inertia of the entire lamina about Z-axis as, $I_z = \sum mr^2$

Here,
$$r^2 = x^2 + y^2$$

Then, $I_z = \sum m(x^2 + y^2)$

$$I_{Z} = \sum mx^{2} + \sum my^{2}$$

In the above expression, the term $\sum mx^2$ is the moment of inertia of the body about the

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

Y-axis and similarly the term $\sum my^2$ is the moment of inertia about X-axis. Thus,

$$I_x = \sum my^2$$
 and $I_y = \sum mx^2$

Substituting in the equation for I_{a} gives,

$$\mathbf{I}_{Z} = \mathbf{I}_{X} + \mathbf{I}_{Y}$$

Thus, the perpendicular axis theorem is proved.



EXAMPLE 5.16

Find the moment of inertia of a disc of mass 3 kg and radius 50 cm about the following axes.

- (i) axis passing through the centre and perpendicular to the plane of the disc,
- (ii) axis touching the edge and perpendicular to the plane of the disc and
- (iii) axis passing through the centre and lying on the plane of the disc.

Solution

The mass, M = 3 kg, radius R = 50 cm = 50×10^{-2} m = 0.5 m

(i) The moment of inertia (I) about an axis passing through the centre and perpendicular to the plane of the disc is,



$$I = \frac{1}{2}MR^{2}$$
$$I = \frac{1}{2} \times 3 \times (0.5)^{2} = 0.5 \times 3 \times 0.5 \times 0.5$$
$$I = 0.375 \text{ kg m}^{2}$$

(ii) The moment of inertia (I) about an axis touching the edge and perpendicular to the plane of the disc by parallel axis theorem is,



$$I = I_{C} + M d^{2}$$

where,
$$I_C = \frac{1}{2}MR^2$$
 and $d = R$

$$I = \frac{1}{2}MR^{2} + MR^{2} = \frac{3}{2}MR^{2}$$
$$I = \frac{3}{2} \times 3 \times (0.5)^{2} = 1.5 \times 3 \times 0.5 \times 0.5$$
$$I = 1.125 \text{ kg m}^{2}$$

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

241

۲

(iii) The moment of inertia (I) about an axis passing through the centre and lying on the plane of the disc is,



 $\mathbf{I}_{Z} = \mathbf{I}_{X} + \mathbf{I}_{Y}$

where,
$$I_X = I_Y = I$$
 and $I_Z = \frac{1}{2}MR^2$

$$I_{z} = 2I; I = \frac{1}{2}I_{z}$$

$$I = \frac{1}{2} \times \frac{1}{2}MR^{2} = \frac{1}{4}MR^{2}$$

$$I = \frac{1}{4} \times 3 \times (0.5)^{2} = 0.25 \times 3 \times 0.5 \times 0.5$$

$$I = 0.1875 \text{ kg m}^{2}$$

- About which of the above axis it is easier to rotate the disc?
- It is easier to rotate the disc about an axis about which the moment of inertia is the least. Hence, it is case (iii).

EXAMPLE 5.17

Find the moment of inertia about the geometric centre of the given structure made up of one thin rod connecting two similar solid spheres as shown in Figure.



242

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

Solution

 $(\mathbf{0})$

The structure is made up of three objects; one thin rod and two solid spheres.

The mass of the rod, M = 3 kg and the total length of the rod, $\ell = 80$ cm = 0.8 m

The moment of inertia of the rod about its centre of mass is, $I_{rod} = \frac{1}{12}M\ell^2$ $I_{rod} = \frac{1}{12} \times 3 \times (0.8)^2 = \frac{1}{4} \times 0.64$ $I_{rod} = 0.16 \text{ kg m}^2$

The mass of the sphere, M = 5 kg and the radius of the sphere, R = 10 cm = 0.1 m

The moment of inertia of the sphere about its centre of mass is, $I_{c} = \frac{2}{5}MR^{2}$

The moment of inertia of the sphere about geometric centre of the structure is, $I_{sph} = I_{c} + Md^{2}$

Where, d = 40 cm + 10 cm = 50 cm = 0.5 m

$$I_{sph} = \frac{2}{5}MR^{2} + Md^{2}$$

$$I_{sph} = \frac{2}{5} \times 5 \times (0.1)^{2} + 5 \times (0.5)^{2}$$

$$I_{sph} = (2 \times 0.01) + (5 \times 0.25) = 0.02 + 1.25$$

$$I_{sph} = 1.27 \text{ kg m}^{2}$$

As there are one rod and two similar solid spheres we can write the total moment of inertia (I) of the given geometric structure as, $I = I_{rod} + (2 \times I_{sph})$

 $I = (0.16) + (2 \times 1.27) = 0.16 + 2.54$ $I = 2.7 \text{ kg m}^2$

5.4.6 Moment of Inertia of

Different Rigid Bodies

The moment of inertia of different objects about different axes is given in the Table 5.3.

UNIT-5(XI-Physics_Vol-1).indd 242

()

5.5

ROTATIONAL DYNAMICS

The relations among torque, angular acceleration, angular momentum, angular velocity and moment of inertia were seen in Section 5.2. In continuation to that, in this section, we will learn the relations among the other dynamical quantities like work, kinetic energy in rotational motion of rigid bodies. Finally a comparison between the translational and rotational quantities is made with a tabulation.

5.5.1 Effect of Torque on Rigid Bodies

A rigid body which has non zero external torque (τ) about the axis of rotation would have an angular acceleration (α) about that axis. The scalar relation between the torque and angular acceleration is,

 $\tau = I \alpha \tag{5.48}$

where, I is the moment of inertia of the rigid body. The torque in rotational motion is equivalent to the force in linear motion.

EXAMPLE 5.18

A disc of mass 500 g and radius 10 cm can freely rotate about a fixed axis as shown in figure. light and inextensible string is wound several turns around it and 100 g body is suspended at its free end. Find the acceleration of this mass. [Given: The string makes the disc to rotate and does not slip over it. $g = 10 \text{ m s}^{-2}$.]



Solution

Let the mass of the disc be m_1 and its radius R. The mass of the suspended body is m_2 .

 $m_1 = 500 \text{ g} = 500 \times 10^{-3} \text{ kg} = 0.5 \text{ kg}$ $m_2 = 100 \text{ g} = 100 \times 10^{-3} \text{ kg} = 0.1 \text{ kg}$ $R = 10 \text{ cm} = 10 \times 10^{-2} \text{ m} = 0.1 \text{ m}$

As the light inextensible string is wound around the disc several times it makes the disc rotate without slipping over it. The translational acceleration of m_2 and tangential acceleration of m_1 will be the same. Let us draw the free body diagram (*FBD*) of m_1 and m_2 separately.

FBD of the disc:



UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES
Table	5.3 Moment of Inertia d	of Different Rigid Bodies				
No.	Object	About an axis	Diagram	Moment of Inertia (I) kg m ²	Radius of Gyration (K)	$ \begin{array}{c} \textbf{Ratio} \\ \left(\frac{K^2}{R^2} \right) \end{array} $
	Thin Uniform Rod	Passing through the centre and perpendicular to the length		$\frac{1}{12}M\ell^2$	$\frac{\ell}{\sqrt{12}}$	
i	Mass = M Length = ℓ	Touching one end and perpendicular to the length		$\frac{1}{3}M\ell^2$	ر ع ا	:
5	Thin Uniform Rectangular Sheet Mass = M; Length = ℓ ; Breadth = b	Passing through the centre and perpendicular to the plane of the sheet	┨	$\frac{1}{12} M(\ell^2 + b^2)$	$\sqrt{\frac{(\ell^2+b^2)}{12}}$;
		Passing through the centre and perpendicular to the plane	€	MR^2	R	1
	Thin Uniform Ring	Touching the edge perpendicular to the plane (perpendicular tangent)	0	$2MR^2$	$\left(\sqrt{2} ight)R$	2
3.	Mass = M Radius = R	Passing through the centre lying on the plane (along diameter)		$rac{1}{2}MR^2$	$\left(rac{1}{\sqrt{2}} ight)R$	$\frac{1}{2}$
		Touching the edge parallel to the plane (parallel tangent)	0	$\frac{3}{2}MR^2$	$\left(\sqrt{rac{3}{2}} ight)R$	$\omega \mid \alpha$
		Passing through the centre and perpendicular to the plane	-	$\frac{1}{2}$ MR ²	$\left(\frac{1}{\sqrt{2}}\right)$ R	7 1
~	Thin Uniform Disc	Touching the edge perpendicular to the plane (perpendicular tangent to the plane)		$\frac{3}{2}$ MR ²	$\left(\sqrt{\frac{3}{2}}\right)$ R	<u>5 3</u>
.	Mass = M Radius = R	Passing through the centre lying on the plane (along diameter)		$\frac{1}{4}$ MR ²	$\left(\frac{1}{2}\right)$ R	1 4
		Touching the edge parallel to the plane (parallel tangent to the plane)		$\frac{5}{4}$ MR ²	$\left(\sqrt{\frac{5}{4}}\right)$ R	സ 4

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

1	1	2 1	1	0 N	ω I Ω	<u>5</u> 75	212
ы	$\sqrt{\frac{R^2}{2} + \frac{\ell^2}{12}}$	$\left(rac{1}{\sqrt{2}} ight)R$	$\sqrt{\frac{R^2}{4}+\frac{\ell^2}{12}}$	$\left(\sqrt{\frac{2}{3}}\right)$ R	$\left(\sqrt{\frac{5}{3}}\right)$ R	$\left(\sqrt{\frac{2}{5}}\right)$ R	$\left(\sqrt{\frac{7}{5}}\right)$ R
MR ²	$M\left(\frac{R^2}{2} + \frac{\ell^2}{12}\right)$	$\frac{1}{2}$ MR ²	$M\left(\frac{R^2}{4} + \frac{\ell^2}{12}\right)$	$\frac{2}{3}$ MR ²	$\frac{5}{3}$ MR ²	$\frac{2}{5}$ MR ²	$\frac{7}{5}$ MR ²
	S		S				
Passing through the centre and along the axis of the cylinder	Passing perpendicular to the length and passing through the centre	Passing through the centre and along the axis of the cylinder	Passing perpendicular to the length and passing through the centre	Passing through the centre (along diameter)	Touching the edge (tangent)	Passing through the centre (along diameter)	Touching the edge (tangent)
Thin Uniform Hollow Cvlinder	Mass = M Length = ℓ ; Radius = R	Uniform Solid Cylinder	Mass = M Length = ℓ ; Radius = R	Thin Hollow Sphere (Thin Spherical Shell)	Mass = M Radius = R	Uniform Solid Sphere	Mass = M Radius = R
	ν	v	; ;	1	:		∞.

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

Its gravitational force (m_1g) acts downward and normal force N exerted by the fixed support at the centre acts upward. The tension T acts downward at the edge. The gravitational force (m_1g) and the normal force (N) cancel each other. $m_1g = N$ $(\mathbf{0})$

The tension T produces a torque (R T), which produces a rotational motion in the disc with angular acceleration, $\left(\alpha = \frac{a}{R}\right)$. Here, a is the linear acceleration of a point at the edge of the disc. If the moment of inertia of the disc is I and its radius of gyration is K, then

$$RT = I\alpha;$$
 $RT = (m_1K^2)\frac{a}{R}$
 $T = (m_1K^2)\frac{a}{R^2}$

FBD of the body:

Its gravitational force (m_2g) acts downward and the tension T acts upward. As $(T < m_2g)$, there is a resultant force (m_2a) acting on it downward.



Substituting for T from the equation for disc,

246

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

$$m_2 g - \left(m_1 K^2\right) \frac{a}{R^2} = m_2 a$$
$$m_2 g = \left(m_1 K^2\right) \frac{a}{R^2} + m_2 a$$
$$m_2 g = \left[\left(m_1 \frac{K^2}{R^2}\right) + m_2\right] a$$
$$a = \frac{m_2}{\left[\left(m_1 \frac{K^2}{R^2}\right) + m_2\right]} g$$

The expression $\left(\frac{K^2}{R^2}\right)$ for a disc rotating about an axis passing through the centre and perpendicular to the plane is, $\frac{K^2}{R^2} = \frac{1}{2}$. (Ref Table 5.3) Now the expression for acceleration further simplifies as,

$$a = \frac{m_2}{\left[\left(\frac{m_1}{2}\right) + m_2\right]}g; \quad a = \frac{2m_2}{\left[m_1 + 2m_2\right]}g$$

substituting the values,

$$a = \frac{2 \times 0.1}{[0.5 + 0.2]} \times 10 = \frac{0.2}{0.7} \times 10$$
$$a = 2.857 \,\mathrm{m\,s^{-2}}$$

5.5.2 Conservation of Angular Momentum

When no external torque acts on the body, the net angular momentum of a rotating rigid body remains constant. This is known as law of conservation of angular momentum.

$\tau = \frac{\mathrm{dL}}{\mathrm{dt}}$	
If $\tau = 0$ then, L = constant	(5.49)

As the angular momentum is $L = I\omega$, the conservation of angular momentum could further be written for initial and final situations as,

$$I_i \omega_i = I_f \omega_f \text{ (or) } I\omega = \text{constant}$$
 (5.50)

The above equations say that if I increases ω will decrease and vice-versa to keep the angular momentum constant.

There are several situations where the principle of conservation of angular momentum is applicable. One striking example is an ice dancer as shown in Figure 5.27. The dancer spins slowly when the hands are stretched out and spins faster when the hands are brought close to the body. Stretching of hands away from body increases moment of inertia, thus the angular velocity decreases resulting in slower spin. When the hands are brought close to the body, the moment of inertia decreases, and thus the angular velocity increases resulting in faster spin.

A diver while in air as in Figure 5.28 curls the body close to decrease the moment of inertia, which in turn helps to increase the number of somersaults in air.









UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES



EXAMPLE 5.19

A jester in a circus is standing with his arms extended on a turn table rotating with angular velocity ω . He brings his arms closer to his body so that his moment of inertia is reduced to one third of the original value. Find his new angular velocity. [Given: There is no external torque on the turn table in the given situation.]

 $(\mathbf{0})$

Solution

Let the moment of inertia of the jester with his arms extended be I. As there is no external torque acting on the jester and the turn table, his total angular momentum is conserved. We can write the equation,

$$I_{i}\omega_{i} = I_{f}\omega_{f}$$

$$I_{i}\omega_{i} = \frac{1}{3}I_{i}\omega_{f} \quad \left(\because I_{f} = \frac{1}{3}I_{i}\right)$$

$$\omega_{f} = 3\omega_{i}$$

The above result tells that the final angular velocity is three times that of initial angular velocity.

5.5.3 Work done by Torque

Let us consider a rigid body rotating about a fixed axis. Figure 5.29 shows a point P on the body rotating about an axis perpendicular to the plane of the page. A tangential force F is applied on the body.

It produces a small displacement ds on the body. The work done (dw) by the force is,





$$dw = F ds$$

As the distance ds, the angle of rotation $d\theta$ and radius r are related by the expression,

$$ds = r d\theta$$

The expression for work done now becomes,

$$dw = F ds; \quad dw = F r d\theta$$

The term (Fr) is the torque τ produced by the force on the body.

$$dw = \tau d\theta \tag{5.51}$$

This expression gives the work done by the external torque τ , which acts on the body rotating about a fixed axis through an angle d θ .

The corresponding expression for work done in translational motion is,

dw = F ds

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

5.5.4 Kinetic Energy in Rotation

Let us consider a rigid body rotating with angular velocity ω about an axis as shown in Figure 5.30. Every particle of the body will have the same angular velocity ω and different tangential velocities v based on its positions from the axis of rotation.





Let us choose a particle of mass m_i situated at distance r_i from the axis of rotation. It has a tangential velocity v_i given by the relation, $v_i = r_i \omega$. The kinetic energy KE_i of the particle is,

$$\mathrm{KE}_i = \frac{1}{2}\mathrm{m}_i\mathrm{v}_i^2$$

Writing the expression with the angular velocity,

$$\mathrm{KE}_{i} = \frac{1}{2}\mathrm{m}_{i}(\mathrm{r}_{i}\omega)^{2} = \frac{1}{2}(\mathrm{m}_{i}\mathrm{r}_{i}^{2})\omega^{2}$$

For the kinetic energy of the whole body, which is made up of large number of such particles, the equation is written with summation as,

$$\mathrm{KE} = \frac{1}{2} \left(\sum m_i r_i^2 \right) \omega^2$$

where, the term $\sum m_i r_i^2$ is the moment of inertia I of the whole body. $I = \sum m_i r_i^2$

 $(\mathbf{0})$

Hence, the expression for KE of the rigid body in rotational motion is,

$$KE = \frac{1}{2}I\omega^2 \qquad (5.52)$$

This is analogous to the expression for kinetic energy in translational motion.

$$KE = \frac{1}{2}Mv^2$$

Relation between rotational kinetic energy and angular momentum

Let a rigid body of moment of inertia I rotate with angular velocity ω .

The angular momentum of a rigid body is, $L = I\omega$

The rotational kinetic energy of the rigid

body is,
$$KE = \frac{1}{2}I\omega^2$$

By multiplying the numerator and denominator of the above equation with I, we get a relation between L and KE as,

$$KE = \frac{1}{2} \frac{I^2 \omega^2}{I} = \frac{1}{2} \frac{(I\omega)^2}{I}$$
$$KE = \frac{L^2}{2I}$$
(5.53)

EXAMPLE 5.20

Find the rotational kinetic energy of a ring of mass 9 kg and radius 3 m rotating with 240 rpm about an axis passing through its centre and perpendicular to its plane. (rpm is a unit of speed of rotation which means revolutions per minute)

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES



UNIT-5(XI-Physics_Vol-1).indd 249

Solution

The rotational kinetic energy is, $KE = \frac{1}{2}I\omega^2$ The moment of inertia of the ring is, $I = MR^2$

 $I = 9 \times 3^2 = 9 \times 9 = 81 \text{ kg m}^2$

The angular speed of the ring is,

$$\omega = 240 \text{ rpm} = \frac{240 \times 2\pi}{60} \text{ rad s}^{-1}$$

$$\text{KE} = \frac{1}{2} \times 81 \times \left(\frac{240 \times 2\pi}{60}\right)^2 = \frac{1}{2} \times 81 \times (8\pi)^2$$

$$\text{KE} = \frac{1}{2} \times 81 \times 64 \times (\pi)^2 = 2592 \times (\pi)^2$$

$$\text{KE} \approx 25920 \text{ J} \qquad \because (\pi)^2 \approx 10$$

$$\text{KE} = 25.920 \text{ kJ}$$

5.5.5 Power Delivered by Torque

Power delivered is the work done per unit time. If we differentiate the expression for work done with respect to time, we get the instantaneous power (P).

$$P = \frac{dw}{dt} = \tau \frac{d\theta}{dt} \quad \because (dw = \tau d\theta)$$
$$P = \tau \omega \tag{5.54}$$

The analogous expression for instantaneous power delivered in translational motion is,

$$\mathbf{P} = \vec{F} \cdot \vec{v}$$

5.5.6 Comparison of Translational and Rotational Quantities

Many quantities in rotational motion have expressions similar to that of translational motion. The rotational terms are compared with the translational equivalents in Table 5.4.

Table 5.4 Comparison of Translational and Rotational Quantities				
S.No	Translational Motion	Rotational motion about a fixed axis		
1	Displacement, x	Angular displacement, θ		
2	Time, t	Time, t		
3	Velocity, $v = \frac{dx}{dt}$	Angular velocity, $\omega = \frac{d\theta}{dt}$		
4	Acceleration, $a = \frac{dv}{dt}$	Angular acceleration, $\alpha = \frac{d\omega}{dt}$		
5	Mass, m	Moment of inertia, I		
6	Force, F = ma	Torque, $\tau = I \alpha$		
7	Linear momentum, p = mv	Angular momentum, $L = I\omega$		
8	Impulse, $F \Delta t = \Delta p$	Angular impulse, $\tau \Delta t = \Delta L$		
9	Work done, $w = F s$	Work done, $w = \tau \theta$		
10	Kinetic energy, $KE = \frac{1}{2}mv^2$	Kinetic energy, $KE = \frac{1}{2}I\omega^2$		
11	Power, $P = F v$	Power, $P = \tau \omega$		

۲

250

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

 (\bullet)

5.6 ROLLING MOTION

The rolling motion is the most commonly observed motion in daily life. The motion of wheel is an example of rolling motion. Round objects like ring, disc, sphere etc. are most suitable for rolling.

Let us study the rolling of a disc on a horizontal surface. Consider a point P on the edge of the disc. While rolling, the point undergoes translational motion along with its centre of mass and rotational motion with respect to its centre of mass.

5.6.1 Combination of Translation and Rotation

We will now see how these translational and rotational motions are related in rolling. If the radius of the rolling object is R, in one full rotation, the centre of mass is displaced by $2\pi R$ (its circumference). One would agree that not only the centre of mass, but all the points on the disc are displaced by the same $2\pi R$ after one full rotation. The only difference is that the centre of mass takes a straight path; but, all the other points undergo a path which has a combination of the translational and rotational motion. Especially the point on the edge undergoes a path of a cycloid as shown in the Figure 5.31.



As the centre of mass takes only a straight line path, its velocity $v_{_{CM}}$ is only translational velocity $v_{TRANS} (v_{CM} = v_{TRANS})$. All the other points have two velocities. One is the translational velocity v_{TRANS} , (which is also the velocity of centre of mass) and the other is the rotational velocity v_{ROT} ($v_{ROT} = r\omega$). Here, r is the distance of the point from the centre of mass and ω is the angular velocity. The rotational velocity $\boldsymbol{v}_{_{ROT}}$ is perpendicular to the instantaneous position vector from the centre of mass as shown in Figure 5.32(a). The resultant of these two velocities is v. This resultant velocity v is perpendicular to the position vector from the point of contact of the rolling object



UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES



(a) with respect to centre of mass



with the surface on which it is rolling as shown in Figure 5.32(b).

We shall now give importance to the point of contact. In pure rolling, the point of the rolling object which comes in contact with the surface is at momentary rest. This is the case with every point that is on the edge of the rolling object. As the rolling proceeds, all the points on the edge, one by one come in contact with the surface; remain at momentary rest at the time of contact and then take the path of the cycloid as already mentioned.

Hence, we can consider the pure rolling in two different ways.

(i) The combination of translational motion and rotational motion about the centre of mass.

(or)

(ii) The momentary rotational motion about the point of contact.

As the point of contact is at momentary rest in pure rolling, its resultant velocity v is zero (v = 0). For example, in Figure 5.33, at the point of contact, v_{TRANS} is forward (to right) and v_{ROT} is backwards (to the left).



۲

Figure 5.33 In pure rolling, the point of contact is at rest

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

2.52

()

That implies that, v_{TRANS} and v_{ROT} are equal in magnitude and opposite in direction $(v = v_{\text{TRANS}} - v_{\text{ROT}} = 0)$. Hence, we conclude that in pure rolling, for all the points on the edge, the magnitudes of v_{TRANS} and v_{ROT} are equal $(v_{\text{TRANS}} = v_{\text{ROT}})$. As $v_{\text{TRANS}} = v_{\text{CM}}$ and $v_{\text{ROT}} = R\omega$, in pure rolling we have,

$$\mathbf{v}_{\rm CM} = \mathbf{R} \,\boldsymbol{\omega} \tag{5.55}$$

We should remember the special feature of the equation 5.55. In rotational motion, as per the relation $v = r\omega$, the centre point will not have any velocity as r is zero. But in rolling motion, it suggests that the centre point has a velocity v_{CM} given by equation 5.55.

For the topmost point, the two velocities v_{TRANS} and v_{ROT} are equal in magnitude and in the same direction (to the right). Thus, the resultant velocity v is the sum of these two velocities, $v = v_{TRANS} + v_{ROT}$. In other form, $v = 2 v_{CM}$ as shown in Figure 5.34.



Figure 5.34 Velocity of different point in pure rolling

5.6.2 Slipping and Sliding

When the round object moves, it always tends to roll on any surface which has a coefficient of friction any value greater than zero ($\mu > 0$). The friction that enabling the rolling motion is called rolling friction. In pure rolling, there is no relative motion of the point of contact with the surface. When the rolling object speeds up or slows down,



UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

it must accelerate or decelerate respectively. If this suddenly happens it makes the rolling object to slip or slide.

Sliding

Sliding is the case when $v_{_{\rm CM}} > R\omega$ (or $v_{\text{TRANS}} > v_{\text{ROT}}$). The translation is more than the rotation. This kind of motion happens when sudden break is applied in a moving vehicles, or when the vehicle enters into a slippery road. In this case, the point of contact has more of v_{TRANS} than v_{ROT} . Hence, it has a resultant velocity v in the forward direction as shown in Figure 5.35. The kinetic frictional force (f_k) opposes the relative motion. Hence, it acts in the opposite direction of the relative velocity. This frictional force reduces the translational velocity and increases the rotational velocity till they become equal and the object sets on pure rolling. Sliding is also referred as forward slipping.



Figure 5.35 Sliding

Slipping

Slipping is the case when $v_{CM} < R\omega$ (or $v_{TRANS} < v_{ROT}$). The rotation is more than the translation. This kind of motion happens when we suddenly start the vehicle from rest or the vehicle is stuck in mud. In this case, the point of contact has more of v_{ROT} than v_{TRANS} . It has a resultant velocity v in the backward direction as shown in Figure 5.36. The kinetic frictional force (f_k) opposes the relative motion. Hence it acts in the opposite direction of the relative velocity. This frictional force reduces the rotational velocity and increases the translational velocity till they become equal and the object sets pure rolling. Slipping is sometimes empahasised as backward slipping.



Figure 5.36 Slipping



EXAMPLE 5.21

A rolling wheel has velocity of its centre of mass as 5 m s⁻¹. If its radius is 1.5 m and angular velocity is 3 rad s⁻¹, then check whether it is in pure rolling or not.

254

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

UNIT-5(XI-Physics_Vol-1).indd 254

Solution

Translational velocity (v_{TRANS}) or velocity of centre of mass, $v_{CM} = 5 \text{ m s}^{-1}$

۲

The radius is, R = 1.5 m and the angular velocity is, $\omega = 3$ rad s⁻¹

Rotational velocity, $v_{ROT} = R\omega$

$$v_{ROT} = 1.5 \times 3$$

 $v_{ROT} = 4.5 \text{ m s}^{-1}$

As $v_{CM} > R\omega$ (or) $v_{TRANS} > R\omega$, It is not in pure rolling, but sliding.

5.6.3 Kinetic Energy in Pure Rolling

In genreal pure rolling is the combination of translational and rotational motion, we can write the total kinetic energy (KE) as the sum of kinetic energy due to translational motion (KE_{TRANS}) and kinetic energy due to rotational motion (KE_{ROT}).

$$KE = KE_{TRANS} + KE_{ROT}$$
 (5.56)

If the mass of the rolling object is M, the velocity of centre of mass is v_{CM} , its moment of inertia about centre of mass is I_{CM} and angular velocity is ω , then

$$KE = \frac{1}{2}Mv_{CM}^{2} + \frac{1}{2}I_{CM}\omega^{2} \qquad (5.57)$$

With centre of mass as reference:

The moment of inertia (I_{CM}) of a rolling object about the centre of mass is,

 $I_{CM} = MK^2$ and $v_{CM} = R\omega$. Here, K is radius of gyration.

$$KE = \frac{1}{2}Mv_{CM}^{2} + \frac{1}{2}(MK^{2})\frac{v_{CM}^{2}}{R^{2}}$$
$$KE = \frac{1}{2}Mv_{CM}^{2} + \frac{1}{2}Mv_{CM}^{2}\left(\frac{K^{2}}{R^{2}}\right) \quad (5.58)$$

$$KE = \frac{1}{2} M v_{CM}^2 \left(1 + \frac{K^2}{R^2} \right)$$
 (5.59)

With point of contact as reference:

We can also arrive at the same expression by taking the momentary rotation happening with respect to the point of contact (another approach to rolling). If we take the point of contact as O, then,

$$KE = \frac{1}{2}I_{o}\omega^{2}$$

Here, I_o is the moment of inertia of the object about the point of contact. By parallel axis theorem, $I_o = I_{CM} + MR^2$. Further we can write, $I_o = MK^2 + MR^2$. With $v_{CM} = R\omega$ or $\omega = \frac{V_{CM}}{R}$

$$KE = \frac{1}{2} \left(MK^{2} + MR^{2} \right) \frac{v_{CM}^{2}}{R^{2}}$$
$$KE = \frac{1}{2} Mv_{CM}^{2} \left(1 + \frac{K^{2}}{R^{2}} \right)$$
(5.60)

As the two equations 5.59 and 5.60 are the same, it is once again confirmed that the



pure rolling problems could be solved by considering the motion as any one of the following two cases. ۲

- (i) The combination of translational motion and rotational motion about the centre of mass. (or)
- (ii) The momentary rotational motion about the point of contact.

EXAMPLE 5.22

A solid sphere is undergoing pure rolling. What is the ratio of its translational kinetic energy to rotational kinetic energy?

Solution

The expression for total kinetic energy in pure rolling is,

 $KE = KE_{TRANS} + KE_{ROT}$

For any object the total kinetic energy as per equation 5.58 and 5.59 is,

$$KE = \frac{1}{2}Mv_{CM}^{2} + \frac{1}{2}Mv_{CM}^{2}\left(\frac{K^{2}}{R^{2}}\right)$$
$$KE = \frac{1}{2}Mv_{CM}^{2}\left(1 + \frac{K^{2}}{R^{2}}\right)$$

Then,

$$\frac{1}{2}Mv_{CM}^{2}\left(1+\frac{K^{2}}{R^{2}}\right) = \frac{1}{2}Mv_{CM}^{2} + \frac{1}{2}Mv_{CM}^{2}\left(\frac{K^{2}}{R^{2}}\right)$$

The above equation suggests that in pure rolling the ratio of total kinetic energy, translational kinetic energy and rotational kinetic energy is given as,

$$KE : KE_{TRANS} : KE_{ROT} :: \left(1 + \frac{K^2}{R^2}\right) : 1 : \left(\frac{K^2}{R^2}\right)$$

$$Now, KE_{TRANS} : KE_{ROT} :: 1 : \left(\frac{K^2}{R^2}\right)$$

$$For a solid sphere, \frac{K^2}{R^2} = \frac{2}{5}$$

$$Then, KE_{TRANS} : KE_{ROT} :: 1 : \frac{2}{5} \quad or$$

$$KE_{TRANS} : KE_{ROT} :: 5 : 2$$

5.6.4 Rolling on Inclined Plane

Let us assume a round object of mass m and radius R is rolling down an inclined plane without slipping as shown in Figure 5.37. There are two forces acting on the object along the inclined plane. One is the component of gravitational force (mg sin θ) and the other is the static frictional force (f). The other component of gravitation force (mg cos θ) is cancelled by the normal force (N) exerted by the plane. As the motion is happening along the incline, we shall write the equation for motion from the free body diagram (*FBD*) of the object.





256

۲

For translational motion, mg sin θ is the supporting force and f is the opposing force,

$$mg \sin\theta - f = ma \qquad (5.61)$$

For rotational motion, let us take the torque with respect to the centre of the object. Then mg sin θ cannot cause torque as it passes through it but the frictional force f can set torque of Rf.

$$Rf = I\alpha$$

By using the relation, $a = r \alpha$, and moment of inertia $I = mK^2$, we get,

$$Rf = mK^2 \frac{a}{R}; \quad f = ma\left(\frac{K^2}{R^2}\right)$$

Now equation (5.61) becomes,

mg sin
$$\theta$$
 - ma $\left(\frac{K^2}{R^2}\right)$ = ma
mg sin θ = ma + ma $\left(\frac{K^2}{R^2}\right)$
a $\left(1 + \frac{K^2}{R^2}\right)$ = g sin θ

After rewriting it for acceleration, we get,

$$a = \frac{g \sin \theta}{\left(1 + \frac{K^2}{R^2}\right)}$$
(5.62)

We can also find the expression for final velocity of the rolling object by using third equation of motion for the inclined plane. $v^2 = u^2 + 2as$. If the body starts rolling from rest, u = 0. When h is the vertical height of the incline, the length of the incline s is, $s = \frac{h}{sin\theta}$

$$v^{2} = 2 \frac{g \sin \theta}{\left(1 + \frac{K^{2}}{R^{2}}\right)} \left(\frac{h}{\sin \theta}\right) = \frac{2gh}{\left(1 + \frac{K^{2}}{R^{2}}\right)}$$

By taking square root,

$$v = \sqrt{\frac{2gh}{\left(1 + \frac{K^2}{R^2}\right)}}$$
(5.63)

The time taken for rolling down the incline could also be written from first equation of motion as, v = u + at. For the object which starts rolling from rest, u = 0. Then,

$$t = \frac{v}{a}$$
$$t = \left(\sqrt{\frac{2gh}{\left(1 + \frac{K^2}{R^2}\right)}}\right) \left(\frac{\left(1 + \frac{K^2}{R^2}\right)}{g\sin\theta}\right)$$
$$t = \sqrt{\frac{2h\left(1 + \frac{K^2}{R^2}\right)}{g\sin^2\theta}}$$
(5.64)

The equation suggests that for a given incline, the object with the least value of radius of gyration K will reach the bottom of the incline first.

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES



EXAMPLE 5.23

Four round objects namely a ring, a disc, a hollow sphere and a solid sphere with same radius R start to roll down an incline at the same time. Find out which object will reach the bottom first.

Solution

For all the four objects namely the ring, disc, hollow sphere and solid sphere, the

radii of gyration K are R, $\sqrt{\frac{1}{2}}$ R, $\sqrt{\frac{2}{3}}$ R, $\sqrt{\frac{2}{5}}$ R (ref Table (5.3)). With numerical values the radius of gyration K are 1R, 0.707R, 0.816R, 0.632R respectively. The expression for time taken for rolling has the radius of gyration K in the numerator as per equation 5.63



The one with least value of radius of gyration K will take the shortest time to reach the bottom of the inclined plane. The order of objects reaching the bottom is first, solid sphere; second, disc; third, hollow sphere and last, ring.



SUMMARY

• A rigid body is the one in which the distances between different particles remain constant.

 $(\mathbf{0})$

- For regular shaped bodies with uniform mass distribution, centre of mass always lies at the geometrical centre.
- Net torque produces turning motion in rigid object.
- A rigid body is in translational equilibrium if the total external force on it is zero. It is in rotational equilibrium if the total external torque on it is zero.
- The centre of gravity of an extended body is that point where the total gravitational torque on the body is zero.
- If the external torque acting on the body is zero, the component of angular momentum along the axis of rotation is constant.
- There are rotational equivalents for all the translational quantities.
- Rolling motion is the combination of translational and rotational motions.
- Rolling can also be treated as the momentary rotation about the point of contact.
- In pure rolling, the total kinetic energy is the sum of kinetic energies of translational and rotational motions.
- In sliding the translational motion is more than rotational motion.
- In slipping the rotational motion is more than translational motion.

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

258

 (\bullet)



UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

EVALUATION

I. Multi Choice Question

- **1.** The centre of mass of a system of particles does not depend upon,
 - (a) position of particles
 - (b) relative distance between particles
 - (c) masses of particles
 - (d) force acting on particle
 - [AIPMT 1997, AIEEE 2004]
- 2. A couple produces,
 - (a) pure rotation
 - (b) pure translation
 - (c) rotation and translation
 - (d) no motion

[AIPMT 1997]

3. A particle is moving with a constant velocity along a line parallel to positive X-axis. The magnitude of its angular momentum with respect to the origin is,

(a) zero

- (b) increasing with x
- (c) decreasing with x
- (d) remaining constant

[IIT 2002]

- **4.** A rope is wound around a hollow cylinder of mass 3 kg and radius 40 cm. What is the angular acceleration of the cylinder if the rope is pulled with a force 30 N?
 - (a) 0.25 rad s^{-2} (b) 25 rad s^{-2}
 - (c) 5 m s^{-2} (d) 25 m s^{-2} .
 - [NEET 2017]
- **5.** A closed cylindrical container is partially filled with water. As the container rotates in a horizontal plane

about a perpendicular **3BC** bisector, its moment of inertia,

- (b) decreases
- (c) remains constant

(a) increases

(d) depends on direction of rotation.

[IIT 1998]

- **6.** A rigid body rotates with an angular momentum L. If its kinetic energy is halved, the angular momentum becomes,
 - (a) L (b) L/2
 - (c) **2L** (d) $L/\sqrt{2}$

[AFMC 1998, AIPMT 2015]

7. A particle undergoes uniform circular motion. The angular momentum of the particle remain conserved about,

(a) the centre point of the circle.

- (b) the point on the circumference of the circle.
- (c) any point inside the circle.
- (d) any point outside the circle.

[IIT 2003]

- 8. When a mass is rotating in a plane about a fixed point, its angular momentum is directed along,
 - (a) a line perpendicular to the plane of rotation
 - (b) the line making an angle of 45° to the plane of rotation
 - (c) the radius
 - (d) tangent to the path

[AIPMT 2012]

9. Two discs of same moment of inertia rotating about their regular axis passing through centre and perpendicular to

۲

260



the plane of disc with angular velocities ω_1 and ω_2 . They are brought in to contact face to face coinciding the axis of rotation. The expression for loss of energy during this process is,

۲

(a)
$$\frac{1}{4} I(\omega_1 - \omega_2)^2$$
 (b) $I(\omega_1 - \omega_2)^2$
(c) $\frac{1}{8} I(\omega_1 - \omega_2)^2$ (d) $\frac{1}{2} I(\omega_1 - \omega_2)^2$
[NEET 2017]

10. A disc of moment of inertia I_a is rotating in a horizontal plane about its symmetry axis with a constant angular speed ω . Another discinitially at rest of moment of inertia I_b is dropped coaxially on to the rotating disc. Then, both the discs rotate with same constant angular speed. The loss of kinetic energy due to friction in this process is,

(a)
$$\frac{1}{2} \frac{I_b^2}{(I_a + I_b)} \omega^2$$

(b)
$$\frac{I_b^2}{(I_a + I_b)} \omega^2$$

(c)
$$\frac{(I_b - I_a)^2}{(I_a + I_b)} \omega^2$$

(d)
$$\frac{1}{2} \frac{I_b I_b}{(I_a + I_b)} \omega^2$$
 [AIPMT 2001]

11. The ratio of the acceleration for a solid sphere (mass m and radius R) rolling down an incline of angle θ without slipping and slipping down the incline without rolling is,

12. From a disc of radius R a mass M, a circular hole of diameter R, whose rim passes through the centre is cut. What is the moment of inertia of the remaining

part of the disc about a perpendicular axis passing through it

- (a) 15MR²/32
 (b) 13MR²/32
 (c) 11MR²/32
 (d) 9MR²/32
 [NEET 2016]
- **13.** The speed of a solid sphere after rolling down from rest without sliding on an inclined plane of vertical height h is,

(a)
$$\sqrt{\frac{4}{3}gh}$$
 (b) $\sqrt{\frac{10}{7}gh}$
(c) $\sqrt{2gh}$ (d) $\sqrt{\frac{1}{2}gh}$

14. The speed of the centre of a wheel rolling on a horizontal surface is v_o . A point on the rim in level with the centre will be moving at a speed of speed of,

(a) zero (b)
$$v_0$$

(c)
$$\sqrt{2} v_{o}$$
 (d) $2v_{o}$

[PMT 1992, PMT 2003, IIT 2004]

- **15.** A round object of mass M and radius R rolls down without slipping along an inclined plane. The frictional force,
 - (a) dissipates kinetic energy as heat.
 - (b) decreases the rotational motion.
 - (c) decreases the rotational and transnational motion
 - (d) converts transnational energy into rotational energy

[PMT 2005]

Answers:

1) d	2) a	3) d	4) b
5) a	6) d	7) a	8) a
9) a	10) d	11) a	12) b
13) b	14) c	15) d	

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

261

۲

II. Short Answer Questions

- 1. Define centre of mass.
- **2.** Find out the centre of mass for the given geometrical structures.
 - a) Equilateral triangle
 - b) Cylinder c) Square
- 3. Define torque and mention its unit.
- **4.** What are the conditions in which force can not produce torque?
- **5.** Give any two examples of torque in day-to-day life.
- **6.** What is the relation between torque and angular momentum?
- 7. What is equilibrium?
- **8.** How do you distinguish between stable and unstable equilibrium?

III. Long Answer Questions

- **1.** Explain the types of equilibrium with suitable examples.
- **2.** Explain the method to find the centre of gravity of a irregularly shaped lamina.
- **3.** Explain why a cyclist bends while negotiating a curve road? Arrive at the expression for angle of bending for a given velocity.
- **4.** Derive the expression for moment of inertia of a rod about its centre and perpendicular to the rod.
- 5. Derive the expression for moment of inertia of a uniform ring about an

IV. Numerical Problems

 A uniform disc of mass 100g has a diameter of 10 cm. Calculate the total energy of the disc when rolling along a horizontal table with a velocity of 20 cms⁻¹. (take the surface of table as reference)

Ans: 0.005 J

262

9. Define couple.

 (\bullet)

- **10.** State principle of moments.
- **11.** Define centre of gravity.
- **12.** Mention any two physical significance of moment of inertia
- **13.** What is radius of gyration?
- **14.** State conservation of angular momentum.
- **15.** What are the rotational equivalents for the physical quantities, (i) mass and (ii) force?
- **16.** What is the condition for pure rolling?
- 17. What is the difference between sliding and slipping?

axis passing through the centre and perpendicular to the plane.

- 6. Derive the expression for moment of inertia of a uniform disc about an axis passing through the centre and perpendicular to the plane.
- 7. Discuss conservation of angular momentum with example.
- **8.** State and prove parallel axis theorem.
- **9.** State and prove perpendicular axis theorem.
- **10.** Discuss rolling on inclined plane and arrive at the expression for the acceleration.
- 2. A particle of mass 5 units is moving with a uniform speed of $v = 3\sqrt{2}$ units in the XOY plane along the line y = x + 4. Find the magnitude of angular momentum.

Ans: 60 units

UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

3. A fly wheel rotates with a uniform angular acceleration. If its angular velocity increases from 20π rad/s to 40π rad/s in 10 seconds. Find the number of rotations in that period.

Ans: 150 rotations

۲

4. A uniform rod of mass m and length ℓ makes a constant angle θ with an axis of rotation which passes through one end of the rod. Find the moment of inertia about this axis.

Ans:
$$\frac{1}{3}M\ell^2\sin^2\theta$$

5. Two particles P and Q of mass 1kg and 3 kg respectively start moving towards each other from rest under mutual attraction. What is the velocity of their centre of mass?

Ans: Zero

6. Find the moment of inertia of a hydrogen molecule about an axis passing through its centre of mass and perpendicular to the inter-atomic axis. Given: mass of hydrogen atom 1.7×10^{-27} kg and inter atomic distance is equal to 4×10^{-10} m.

Ans: 1.36×10^{-46} kg m²

 (\bullet)

BOOKS FOR REFERENCE

1. Michael Nelkon and Philip Parker, Advanced Level Physics, 7th Edition, CBS Publishers & Distributers Pvt. Ltd, (2006).

۲

- 2. David Halliday, Robert Resnick and Jearl Walker, Fundamentals of Physics, 6th Edition, John Wiley & Sons Inc., (2004).
- **3.** H.C. Verma, Concepts of Physics [Part 1], 1st Edition, BharathiBhawan Publishers & Distributers Pvt. Ltd., (2008).
- **4.** Igor Irodov, Problems in General Physics, 3rd Edition, Mir Publishers, Mascow, (2006).
- 5. Roger A. Freedman, Hugh D. Young, Sears and Zemansky's University Physics: Mechanics, 12th Edition, Pearson, (2011).



۲



۲

STEPS:

()

- Open the browser and type the given URL to open the PhET simulation on Torque. Click the picture link or the download button. Once downloaded, click ok to open the java applet.
- Set platform mass 0.1 kg, Outer radius 4 m. (Keep inner radius = 0). Now it is a circular disc. Click the button 'go' to get the value of moment of inertia.
- Adjust the values of mass and radius and then observe how moment of inertia changes in the middle graph.
- Keep the inner and outer radius same (say R = r = 4 m.) and mass 0.1 kg. Now it becomes circular ring. Click the button 'go' to start the calculation.
- Observe the moment of inertia from the middle graph. Compare the moment of inertia of a circular disc and circular ring with same mass and radius.

Hint: If moment of inertia is relatively large, it is very difficult to accelerate in angular direction.



UNIT 5 MOTION OF SYSTEM OF PARTICLES AND RIGID BODIES

۲

APPENDIX 1

۲



SOLVED EXAMPLE UNIT-1

1. Find the dimensions of a and b in the formula $[P + \frac{a}{V^2}][V - b] = RT$ where P is pressure and V is the volume of the gas

Solution:

By the principle of homogeneity, a/V^2 is of the dimensions of pressure and b is of the dimensions of volume.

$$[a] = [pressure] [V2] = [ML-1T-2] [L6]$$
$$= [ML5T-2]$$
$$[b] = [V] = [L3]$$

2. Show that $(P^{-5/6}\rho^{1/2}E^{1/3})$ is of the dimension of time. Here P is the pressure, ρ is the density and E is the energy of a bubble)

Solution:

Dimension of Pressure = $[ML^{-1}T^{-2}]$

Dimension of density = $[ML^{-3}]$

Dimension of Energy = $[ML^2T^{-2}]$

By substituting in the given equation,

$$= [ML^{-1}T^{-2}]^{-5/6} [ML^{-3}]^{1/2} [ML^{2}T^{-2}]^{1/3}$$
$$= M^{-5/6+1/2+1/3} L^{5/6-3/2+2/3} T^{5/3-2/3}$$
$$= M^{0}L^{0}T^{1} = [T]$$

3. Find the dimensions of mass in terms of Energy, length and time

Solution:

Let the dimensions of Energy, Length and Time be [E], [L], [T] respectively.

We know that Force = mass x acceleration

$$Mass = \frac{Force}{acceleration}$$
$$= \frac{Workdone (or) Energy}{acceleration \times displacement}$$
$$[m] = \frac{Energy}{[acceleration][displacement]}$$
$$= \frac{[E]}{[LT^{-2}][L]} = \frac{[E]}{L^2T^{-2}]} = [EL^{-2}T^2]$$

4. A physical quantity Q is found to depend on quantities x,y,z obeying



 (\bullet)

relation Q = $\frac{x^2 y^3}{z^1}$. The percentage errors in x, y and z are 2%, 3% and 1% respectively. Find the percentage error in Q.

Solution:

Let,
$$Q = \frac{x^2 y^3}{z}$$
.
It is given, $\frac{\Delta x}{x} = 2\% \frac{\Delta y}{y} = 3\% \frac{\Delta z}{z} = 1\%$
 $\frac{\Delta Q}{Q} = 2\left(\frac{\Delta x}{x}\right) + 3\left(\frac{\Delta y}{y}\right) + 1\left(\frac{\Delta z}{z}\right)$
 $= 2(2\%) + 3(3\%) + 1(1\%)$
 $\frac{\Delta Q}{Q} = 4\% + 9\% + 1\% = 14\%$

5. The mass and volume of a body are found to be $4\pm.03$ kg and $5\pm.01$ m³ respectively. Then find the maximum possible percentage error in density.

Solution:

Mass m = 4 ± 0.03 kg (m +
$$\Delta$$
m)
Volume V = 5 ± .01 m³ (V + Δ V)
Density = ?
Error in mass = $\frac{\Delta m}{m} = \frac{0.03}{4} \times 100$
= 0.75%
Error in volume = $\frac{\Delta V}{V} = \frac{0.01}{5} \times 100$
= 0.2%
Density = $\frac{mass}{volume}$.

Error in density = error in mass + error in volume

= 0.75% + 0.2% = 0.95%

 Using a Vernier Callipers, the length of a cylinder in different measurements is found to be 2.36 cm, 2.27 cm, 2.26 cm, 2.28 cm, 2.31 cm, 2.28 cm and 2.29 cm. Find the mean value, absolute error, the relative error and the percentage error of the cylinder.

Solution:

۲

The given readings are 2.36 cm, 2.27 cm, 2.26 cm, 2.28 cm, 2.31 cm, 2.28 cm and 2.29 cm

The Mean value
$$\overline{l} =$$

$$\frac{2.36 + 2.27 + 2.26 + 2.28 + 2.31 + 2.28 + 2.29}{7}$$

$$\frac{16.05}{7} = 2.29 \text{ cm}$$

Absolute errors in the measurement are,

$$\begin{split} \left| \Delta l_1 \right| &= \left| 2.29 - 2.36 \right| = 0.07 \\ \left| \Delta l_2 \right| &= \left| 2.29 - 2.27 \right| = 0.02 \\ \left| \Delta l_3 \right| &= \left| 2.29 - 2.26 \right| = 0.03 \\ \left| \Delta l_4 \right| &= \left| 2.29 - 2.28 \right| = 0.01 \\ \left| \Delta l_5 \right| &= \left| 2.29 - 2.31 \right| = 0.02 \\ \left| \Delta l_6 \right| &= \left| 2.29 - 2.28 \right| = 0.01 \\ \left| \Delta l_7 \right| &= \left| 2.29 - 2.29 \right| = 0.00 \end{split}$$

Mean Absolute error

$$\Delta l_{mean} = \frac{0.07 + 0.02 + 0.03 + 0.01 + 0.02 + 0.01 + 0.00}{7}$$
$$= \frac{.16}{7} = .02$$

APPENDIX 1

 (\bullet)

Relative error

$$=\frac{\Delta lmean}{\overline{l}} = \pm \frac{.02}{2.29} = \pm 8.7 \times 10^{-3}$$

Percentage error = $\pm 8.7 \times 10^{-3} \times 100 =$
 $0.87\% \times 100 = \pm (8.7 \times 10^{-1}) = 0.9\%$

7. The shadow of a pole standing on a level ground is found to be 45 m longer when the sun's altitude is 30° than when it was 60°. Determine the height of the pole. [Given $\sqrt{3} = 1.73$]

Solution:

Let the height of the pole be h.



Substituting the values of x in the above equation

$$h = \frac{h \cot 60^\circ + 45}{\cot 30^\circ}$$

$$h \cot 30^\circ = h \cot 60^\circ + 45$$

$$h(\cot 30^\circ - \cot 60^\circ) = 45$$

$$h = \frac{45}{\cot 30^\circ - \cot 60^\circ} = \frac{45}{\sqrt{3} - \frac{1}{\sqrt{3}}} = 38.97 \text{ m}$$

APPENDIX 1

 Calculate the number of times a human heart beats in the life of 100 years old man. Time of one heart beat = 0.8s.

Solution:

۲

Life of the man = 100 years 100 years includes 76 normal years and 24 leap years

Total no of days = $76 \times 365 + 24 \times 366$ = 36524 days

Number of seconds = $36524 \times 24 \times$ $3600 = 3.155 \times 10^9$ second



9. The parallax of a heavenly body measured from two points diametrically opposite on equator of earth is 2'. Calculate the distance of the heavenly body. [Given radius of the earth = 6400km] $[1'' = 4.85 \times 10^{-6} \text{ rad}]$

Solution:

Angle $\theta = 2^1 = 2 \ge 60'' = 120'' = 120 \times 4.85 \times 10^{-6}$ rad

$$\theta = 5.82 \times 10^{-4} \, rad;$$

The distance of heavenly body

D =
$$\frac{d}{\theta} = \frac{12800 \times 10^3}{5.82 \times 10^{-4}}$$

D = 2.19 × 10¹⁰ m

268

10. Convert a velocity of 72 kmh⁻¹ into m s⁻¹ with the help of dimensional analysis.

۲

Solution:

$$n_{1} = 72 \text{ kmh}^{-1} \quad n_{2} = ? \text{ m s}^{-1}$$

$$L_{1} = 1 \text{ Km} \quad L_{2} = 1 \text{ m}$$

$$T_{1} = 1 \text{ h} \quad T_{2} = 1 \text{ s}$$

$$n_{2} = n_{1} \left[\frac{L_{1}}{L_{2}} \right]^{a} \left[\frac{T_{1}}{T_{2}} \right]^{b}$$

The dimensional formula for velocity is $[L T^{-1}]$

$$a = 1 b = -1$$

$$n_{2} = 72 \left[\frac{1Km}{1m} \right]^{1} \left[\frac{1h}{1s} \right]^{-1}$$

$$n_{2} = 72 \left[\frac{1000m}{1m} \right]^{1} \left[\frac{3600s}{1s} \right]^{-1}$$

$$= 72 \times 1000 \times 1/3600 = 20 \text{ m s}^{-1}$$

$$72 \text{ kmh}^{-1} = 20 \text{ m s}^{-1}$$

11. Check the correctness of the following equation using dimensional analysis. Make a comment on it.

 $S = ut + 1/4 at^2$ where s is the displacement, u is the initial velocity, t is the time and a is the acceleration produced.

Solution:

Dimension for distance s = [L] Dimension for initial velocity

 $\mathbf{v} = [\mathbf{L}\mathbf{T}^{-1}]$

Dimension for time t = [T] Dimension for acceleration

 $\mathbf{a} = [\mathbf{L}\mathbf{T}^{-2}]$

According to the principle of homogeneity,

Dimensions of LHS = Dimensions of RHS

Substituting the dimensions in the given formula

S = ut + 1/4 at², $\frac{1}{4}$ is a number. It has no dimensions

$$[L] = [LT^{-1}] [T^{1}] + [LT^{-2}] [T^{2}]$$
$$[L] = [L] + [L]$$

As the dimensional formula of LHS is same as that of RHS, the equation is dimensionally correct. Comment:

But actually it is a *wrong* equation. We know that the equation of motion is $s = ut + 1/2 at^2$

So, a dimensionally correct equation *need not* be the true (or) actual equation

But a true equation is *always* dimensionally correct.

- 12. Round off the following numbers as indicated.
 - a) 17.234 to 3 digits
 - b) 3.996×10^5 to 3 digits
 - c) 3.6925×10^{-3} to 2 digits
 - d) 124783 to 5 digits.

Solution:

a) 17.2 b) 4.00×10^5

- c) 3.7×10^{-3} d) 124780
- 13. Solve the following with regard to significant figures.

a)
$$\sqrt{4.5 - 3.31}$$

b) $5.9 \times 10^5 - 2.3 \times 10^4$

APPENDIX 1

269

Appendix-1.indd 269

c) 7.18 + 4.3

d) 6.5 + .0136

Solution:

a) Among the two, the least number of significant after decimal is one

 $\sqrt{4.5 - 3.31} = \sqrt{1.19} = 1.09$

b) The number of minimum significant figures is 2

$$5.9 \times 10^{5} - 2.3 \times 10^{4}$$
$$= 5.9 \times 10^{5} - 0.23 \times 10^{5}$$
$$= 5.67 \times 10^{5} = 5.7 \times 10^{5}$$

c) The lowest least number of significant digit after decimal is one

7.18 + 4.3 = 11.48 Rounding off we get 11.5

d) The lowest least number of significant digit after decimal is one

6.5 +.0136 = 6.5136 = 6.5

14. Arrive at Einstein's mass-energy relation by dimensional method ($E = mc^2$)

Solution:

Let us assume that the Energy E depends on mass m and velocity of light c.

 $E \alpha m^a c^b$

 $E = km^a c^b$ where K a constant

Dimensions of $E = [ML^2T^{-2}]$

Dimensions of m = [M]

Dimensions of $c = [LT^{-1}]$

Substituting the values in the above equation

$[ML^2T^{-2}] = K [M]^a [LT^{-1}]^b$

By equating the dimensions,

۲

a = 1 b = 2 -b = -2 $E = k.mc^{2}$

The value of constant k = 1

 $E = mc^2$ This is Einstein's mass energy relation

15. The velocity of a body is given by the equation $v = b/t + ct^2+dt^3$. Find the dimensional formula for b.

Solution:

(b/t) should have the dimensions of velocity

b has the dimensions of (velocity x time)

$$[b] = [LT^{-1}][T] = [L] = [M^0 L^1 T^0]$$

16. The initial and final temperatures of a liquid in a container are observed to be 75.4 \pm 0.5°C and 56.8 \pm 0.2°C. Find the fall in the temperature of the liquid.

Solution:

 $t_1 = (75.4 \pm 0.5)^{\circ}C$ $t_2 = (56.8 \pm 0.2)^{\circ}C$ Fall in temperature = (75.4 ± 0.5°C) – (56.8 ± 0.2°C)

 $t = (18.6 \pm 0.7)^{\circ}C$

17. Two resistors of resistances $R_1 = 150$ ± 2 Ohm and $R_2 = 220 \pm 6$ Ohm are connected in parallel combination. Calculate the equivalent resistance.

Hint:
$$\frac{1}{R'} = \frac{1}{R_1} + \frac{1}{R_2}$$

Solution:

The equivalent resistance of a parallel combination

$$R' = \frac{R_1 R_2}{R_1 + R_2}$$
$$= \frac{150 \times 220}{150 + 220} = \frac{33000}{370} = 89.1 \text{ Ohm}$$

We know that,
$$\frac{1}{R'} = \frac{1}{R_1} + \frac{1}{R_2}$$

$$\frac{\Delta R'}{(R')^2} = \frac{\Delta R_1}{R_1^2} + \frac{\Delta R_2}{R_2^2}$$
$$\Delta R' = (R')^2 \frac{\Delta R_1}{R_1^2} + (R')^2 \frac{\Delta R_2}{R_2^2}$$
$$= \left(\frac{R'}{R_1}\right)^2 \Delta R_1 + \left(\frac{R'}{R_2}\right)^2 \Delta R_2$$

Substituting the value,

$$\Delta R' = \left[\frac{89.1}{150}\right]^2 \times 2 + \left[\frac{89.1}{220}\right]^2 \times 6$$
$$= 0.070 + 0.098 = 0.168$$
$$R' = 89.1 \pm 0.168 \text{ Ohm.}$$

18. A capacitor of capacitance $C = 3.0 \pm 0.1 \mu F$ is charged to a voltage of $V = 18 \pm 0.4 Volt$. Calculate the charge Q [Use Q= CV]

Solution:

۲

$$(C + \Delta C) = (3.0 \pm 0.1) \,\mu f$$

 $(V + \Delta V) = (18 \pm 0.4) \, V$
 $Q = CV$

 $Q=3.0\times10^{\text{-6}}\times18=54\times10^{\text{-6}}$ coulomb

Error in C =
$$\frac{\Delta C}{C} \times 100$$

= $\frac{0.1}{3} \times 100 = 3.3\%$
Error in V = $\frac{\Delta V}{V} \times 100$
= $\frac{0.4}{18} \times 100 = 2.2\%$

Error in Q = Error in C + Error in V = 3.3% + 2.2% = 5.5%

 $\therefore \text{Charge } Q = (54 \times 10^{-6} \pm 5.5\%) \text{ coulomb}$

SOLVED EXAMPLE UNIT-2

1. The position vector for a particle is represented be $\vec{r} = 3t^2\hat{i} + 5t\hat{j} + 6\hat{k}$, find the velocity and speed of the particle at t = 3 sec?

Solution:

$$\vec{v} = \frac{\vec{dr}}{dt} = 6t\hat{i} + 5\hat{j}.$$

The velocity at any time 't' is given by $\vec{v} = 6t\hat{i} + 5\hat{j}$.

The magnitude of velocity is speed. The speed at any time 't' is then given by

APPENDIX 1

()

Speed =
$$\sqrt{(6t)^2 + 5^2} = \sqrt{36t^2 + 25}$$

Now the velocity at t = 3sec is given by

$$\vec{v} = 6(3)\hat{i} + 5\hat{j} = 18\hat{i} + 5\hat{j}.$$

and speed at t = 3 sec, is given by

speed =
$$\sqrt{349} m s^{-1}$$

2. A gun is fired from a place which is at distance 1.2 km from a hill. The echo of the sound is heard back at the same place of firing after 8 second. Find the speed of sound.

Solution:

The echo will be heard when the sound reaches back at the place of firing. So, the total distance travelled by sound is 2×1.2 km = 2.4 km = 2400 m.

speed =
$$\frac{2400 \text{ m}}{8s}$$
 = 300 m s⁻¹

 A train 100 m long is moving with a speed of 60 kmh⁻¹. In how many seconds will it cross a bridge of 1 km long?

Solution:

Total distance to be covered = 1 km + 100 m = 1100 m (including both bridge and time)

Then, Speed = 60 km h⁻¹
=
$$60 \times \frac{5}{18}$$
 m s⁻¹ = $\frac{150}{9}$ m s⁻¹

APPENDIX 1

Then, Time taken to cover this 1100

distance =
$$\frac{1100}{150/9}$$
 s = 66 s

6

4. Draw the resultant direction of the two unit vectors \hat{i} and \hat{j} . Use a 2-dimensional Cartesian co-ordinate system. Is $\hat{i} + \hat{j}$ a unit vector?

By using the triangular law of addition $\hat{i} + \hat{j}$ as shown in the following figure,



The definition of unit vector is $\hat{A} \cdot \hat{A} = 1$

But here, $(\hat{i} + \hat{j}).(\hat{i} + \hat{j}) = \hat{i}.\hat{i} + \hat{i}.\hat{j} + \hat{j}.\hat{i} + \hat{j}.\hat{j}$ = 1 + 0 + 0 + 1 = 2

So, $\hat{i} + \hat{j}$ is not a unit vector.

To make any vector to a unit vector, must divide the vector by its magnitude,

$$\hat{A} = \frac{A}{\left|\vec{A}\right|}$$

The norm of the vector $\hat{i} + \hat{j} = \sqrt{2}$. Hence, the unit vector is $\frac{\hat{i} + \hat{j}}{\sqrt{2}}$

- 5. A swimmer moves across the Cauvery river of 750 m wide. The velocity of the swimmer relative to water (\vec{v}_{sw}) is 1.5 m s⁻¹ and directed perpendicular to the water current. The velocity of water relative to the bank (\vec{v}_{wb}) is 1 m s⁻¹. Calculate the
 - (a) velocity of the swimmer with respect to the bank of the river (\vec{v}_{sb}) .
 - (b) time taken by the swimmer to cross the Cauvery river.

Solution:

(a) We can draw the following picture from the given data in the problem.

(



The velocity of the swimmer relative to the bank $\vec{v}_{sb} = \vec{v}_{sw} + \vec{v}_{wb}$

Since the swimmer travels in the perpendicular direction against the water current

The magnitude is given by

$$\left| \vec{v}_{sb} \right| = \sqrt{v_{sw}^2 + v_{wb}^2} =$$

 $\sqrt{1.5^2 + 1^2} = \sqrt{3.25} \, m \, s^{-1} \cong 1.802 \, m \, s^{-1}$

The direction of the swimmer relative to the bank is given by

$$tan\theta = \frac{v_{sw}}{v_{wb}} = \frac{1.5}{1} = 1.5$$
$$\theta = tan^{-1}(1.5) \approx 56^{\circ}$$

(c) The time taken by the swimmer to cross the river is equal to the total distance covered by the swimmer with velocity 1.802 ms⁻¹.

The total distance covered by him,

 $d = \frac{width \ of \ the \ river}{\sin 56^{\circ}} = \frac{750}{0.829} = 904.7 \ m$

The time taken by the swimmer,

$$T = \frac{d}{v_{sb}} = \frac{904.7}{1.802} \approx 502 \, s$$

6. A monkey hangs on a tree. A hunter aims a gun at the monkey and fires the bullet with velocity v₀ which makes angle θ with horizontal direction. At the instant gun fires, monkey leaves the branch and falls straight down to escape from the bullet as shown in the figure. Will bullet hit the monkey or will the monkey escape the bullet? (ignore air resistance)



As soon as the monkey begins to fall, it will have downward vertical motion with acceleration due to gravity g.

Its equation of motion at any time t is

given by

$$y_m = h - \frac{1}{2}gt^2 \tag{1}$$

When the bullet comes out of the gun, it has both vertical and horizontal components of velocity given by

$$v_{0x} = v_0 \cos\theta; v_{0y} = v_0 \sin\theta \qquad (2)$$

Let us assume the horizontal distance between the monkey and hunter is 'd'.

At time t, the horizontal distance travelled by the bullet $x = v_0 \cos\theta t$.



273

Appendix-1.indd 273

When the horizontal position of bullet, x = d, the time $d = v_{0x}T$. It implies that $T = d / v_{0x}$

At this time T, the vertical distance covered by the bullet is

$$y_{b} = v_{0y}T - \frac{1}{2}gT^{2} = \frac{v_{0y}d}{v_{0x}} - \frac{1}{2}gT^{2}.$$
$$y_{b} = \frac{dv_{0}\sin\theta}{v_{0}\cos\theta} - \frac{1}{2}gT^{2}$$
$$= d\tan\theta - \frac{1}{2}gT^{2}$$
(3)

But from the figure we can write, $tan\theta = \frac{h}{d}$.

 $h = d \tan \theta$.

By substituting this in the equation (3), we get,

$$y_b = h - \frac{1}{2}gT^2 \tag{4}$$

At this same time T, the vertical position of the monkey can be calculated from the equation (1)

$$y_m = h - \frac{1}{2}gT^2 \tag{5}$$

Note that at the time T, the y coordinate of both monkey and bullet is same. It implies that the bullet will hit the monkey.

7. A three storey building of height 100 m is located on Earth and a similar building

is also located on Moon. If two persons jump from the top of these buildings on Earth and Moon simultaneously, when they reach the ground, what will be their speed? ($g = 10 \text{ m s}^{-2}$)

Solution:

۲



For both persons, the Kinematic equations are the same, with u = 0, $a_e = g$ and $a_{moon} = \frac{g}{6}$. Then

$$a_e = g and a_m = \frac{g}{6}$$

For a person on earth, $V_{earth} = \sqrt{2gh}$ = $\sqrt{2g100} = \sqrt{2 \times 10 \times 100}$

Hence, $V_{earth} = \sqrt{2000} \ m \ s^{-1}$ gives the velocity at the ground, on earth.

Similarly, for a person on the moon,

$$V_{moon} = \sqrt{\frac{2gh}{6}} = \frac{\sqrt{2000}}{\sqrt{6}} m \ s^{-1}$$

The person on earth reaches ground with greater velocity than the person on the moon

The following graphs represent position

 time graphs. Arrange the graphs in ascending order of increasing speed.



APPENDIX 1

Appendix-1.indd 274

274



The slope in the position – time graph will give the speed of the particle.

In the graph (a) slope is zero. Graph (c) has higher slope than graphs (b) and (d). So we can arrange the speeds in ascending order as

$$v_a < v_d < v_b < v_c$$

SOLVED EXAMPLE UNIT-3

 A body of mass 100 kg is moving with an acceleration of 50 cm s⁻². Calculate the force experienced by it.

Solution:

Mass m = 100 kg Acceleration a = 50 cm s⁻² = 0.5 m s⁻² Using Newton's second law,

> F = ma $F = 100 \text{ kg x } 0.5 \text{ m s}^{-2} = 50 \text{ N}$

2. Identify the free body diagram that represents the particle accelerating in positive *x* direction in the following.

The relative magnitude of forces should be indicated when the free body diagram for mass m is drawn.



Case (a):

۲

The forces F_1 and F_2 have equal length but opposite direction. So net force along y-direction is zero. Since the force is zero, acceleration is also zero along Y-direction (Newton's second law). Similarly in the x direction, F_3 and F_4 have equal length and opposite in direction. So net force is zero in the x direction. So there is no acceleration in x direction.

Case (b):

The forces F_1 and F_2 are not equal in length and act opposite to each other. The figure (b) shows that there are unbalanced forces along the y-direction. So the particle has acceleration in the -y direction. The forces F_3 and F_4 are having equal length and act in opposite directions. So there is no net force along the x direction. So the particle has no acceleration in the x direction.

Case (c):

The forces F_1 and F_2 are equal in magnitude and act opposite to each

APPENDIX 1



 (\bullet)

other. The net force is zero in y direction. So in y-direction there is no acceleration. The forces F_3 and F_4 are not equal in magnitude and F_3 is greater than F_4 . So there is a net acceleration in negative x direction

Case (d):

The forces F_1 and F_2 are equal in magnitude and act opposite to each other. The net force is zero in y direction. So there is no acceleration in y-direction. The forces F_3 and F_4 are not equal in magnitude. The force F_4 is greater than the force F_3 . So there is a net acceleration in the positive x direction.

 A gun weighing 25 kg fires a bullet weighing 30 g with the speed of 200 ms⁻¹. What is the speed of recoil of the gun.

Solution:

Mass of the gun M = 25 kg Mass of the bullet m = 30 g = 30×10^{-3} kg Speed of bullet v = 200 m s⁻¹ Speed of gun V = ? The motion is in one dimension. As per law of conservation of momentum,

$$MV + mv = 0$$
$$V = \frac{-mv}{M}$$
$$V = \frac{-30 \times 10^{-3} \times 200}{25} = -240 \times 10^{-3} m s^{-1}$$

The negative sign shows that the gun moves in the opposite direction of the bullet. Further the magnitude of the recoil speed is very small compared to the bullet's speed.

276

APPENDIX 1

 A wooden box is lying on an inclined plane. What is the coefficient of friction if the box starts sliding when the angle of inclination is 45°.

Solution:

Angle of inclination $\Theta = 45^{\circ}$ \therefore Coefficient of friction $\mu = \tan \Theta = \tan 45^{\circ} = 1$

5. Two masses $m_1 = 5$ kg and $m_2 = 4$ kg tied to a string are hanging over a light frictionless pulley. What is the acceleration of each mass when left free to move? (g = 10 m s⁻²)

$$a = \frac{m_1 - m_2}{m_1 + m_2} \times g$$
$$= \frac{5 - 4}{5 + 4} \times 10 = \frac{1}{9} \times 10 = 1.1 \ ms^{-2}$$



6. A block of mass m is pushed momentarily along a horizontal surface with an initial velocity u. If μ_k is the coefficient of kinetic friction between the object and surface, find the time at which the block comes to rest. \bigcirc

Solution:



When the block slides, the force acting on the block is kinetic friction which is equal to $f_k = \mu_k mg$

From Newton's second law $ma = -\mu_k mg$

The negative sign implies that force acts on the opposite direction of motion.

The acceleration of the block while sliding $a = -\mu_k g$.

The negative sign implies that the acceleration is in opposite direction of the velocity.

Note that the acceleration depends only on g and the coefficient of kinetic friction μ_k

We can apply the following kinematic equation

v = u + at

The final velocity is zero.

$$0 = u - \mu_k gt$$
$$t = \frac{u}{\mu_k g}$$

7. Three blocks of masses 10 kg, 7 kg and 2 kg are placed in contact with each other on a frictionless table. A force of 50 N is applied on the heaviest mass. What is the acceleration of the system?

Solution:

We know that

$$a = \left[\frac{F}{m_1 + m_2 + m_3}\right] = \frac{50N}{10 \, kg + 7 \, kg + 2 \, kg}$$
$$= \frac{50}{19} = 2.63 \, m \, s^{-2}$$

8. The coefficient of friction between a block and plane is $\frac{1}{\sqrt{3}}$. If the inclination of the plane gradually increases, at what angle will the object begin to slide? Since the coefficient of friction is $\frac{1}{\sqrt{3}}$

$$\operatorname{Tan} \Theta = \frac{1}{\sqrt{3}} \Longrightarrow \Theta = 30^{\circ}$$

9. Find the maximum speed at which a car can turn round a curve of 36 m radius on a level road. Given the coefficient of friction between the tyre and the road is 0.53.

Radius of the curve r = 36 m

Coefficient of friction $\mu = 0.53$

Acceleration due to gravity $g = 10 \text{ ms}^{-2}$

$$v_{max} = \sqrt{\mu rg} = \sqrt{0.53 \times 36 \times 10}$$
$$= 13.81 m s^{-1}$$

10. Calculate the centripetal acceleration of the Earth which orbits around the

APPENDIX 1



Appendix-1.indd 277

Sun. The Sun to Earth distance is appriximately 150 million km. (Assume the orbit of Earth to be circular)

The centripetal acceleration $a_c = \frac{v^2}{r}$

V - velocity of Earth around the orbit

r - radius of orbit or distance of Earth to Sun

Velocity of Earth is written in terms of angular velocity (ω) as

 $v = \omega r$

By substituting in the centripetal acceleration formula, $a_c = \frac{\omega^2 r^2}{r} = \omega^2 r$

But $\omega = \frac{2\pi}{T}$ where T is time for the Earth to orbit around the sun, which is one year.

$$T = 365 \text{ days} = 365 \times 24 \times 60 \times 60$$
$$s = 3.1 \times 10^7 s$$

$$\omega = 2.02 \times 10^{-7} rad per sec$$
$$a_{c} = (2.02 \times 10^{-7})^{2} \times (150 \times 10^{9})$$
$$a_{c} = 6.12 \times 10^{-3} m s^{-2}$$

11. A block 1 of mass m_1 , constrained to move along a plane inclined at an angle θ to the horizontal, is connected via a frictionless, massless and inextensible string that passes over a massless pulley, to a second block 2 of mass m_2 . Assume the coefficient of static friction between the block and the inclined

278

plane is μ_s and the coefficient of kinetic friction is μ_k



What is the relation between the masses of block 1 and block 2 such that the system just starts to slip?

Solution:

 $(\mathbf{0})$

For all parts of this problem, it will be convenient to use different coordinate systems for the two different blocks. For block 1, take the positive x -direction to be up the incline, parallel to the plane, and the positive y -direction to be perpendicular to the plane, directed with a positive upward component. Take the positive direction of the position of block 2 to be downward.

The normal component *N* of the contact force between block 1 and the ramp will be

$$N = m_1 g \cos \theta \,. \tag{1}$$

The net x -component of the force on block 1 is then

$$F_{1x} = T - f_{\text{friction}} - m_1 g \sin \theta \qquad (2)$$

where *T* is the tension in the string

For the just-slipping condition, the frictional force has magnitude

$$f_{\rm friction} = \mu_s N = \mu_s m_1 g \cos \theta.$$
 (3)

The tension in the string is the gravitational force of the suspended mass,

$$T = m_2 g \,. \tag{4}$$

(

For the just-slipping condition, the net force on block 1 must be zero. Equations (2), (3) and (4) gives

 $0 = m_2 g - \mu_s m_1 g \cos \theta - m_1 g \sin \theta$ $m_2 = m_1 (\mu_s \cos \theta + \sin \theta)$

- 12. Consider two objects of masses 5 kg and20 kg which are initially at rest. A force100 N is applied on the two objects for5 second.
 - a) What is the momentum gained by each object after 5 s.
 - b) What is the speed gained by each object after 5 s.

Final momentum on each object $\Delta P = F\Delta t = 100 \text{ X} 5 = 500 \text{ kgms}^{-1}$

Final speed on the object of mass $5 \text{ kg} = 500 / 5 = 100 \text{ m s}^{-1}$

Final speed on the object of mass $20 \text{ kg} = 500/20 = 25 \text{ m s}^{-1}$

Note that momentum on each object is the same after 5 seconds but speed is not the same after 5 seconds. The heavier mass acquires lesser speed than the one with lower mass.

13. An object of mass 5 kg is initially at rest on the surface. The surface has coefficient of kinetic friction $\mu_k = 0.6$. What initial velocity must be given to the object so that it travels 10 m before coming to rest?

When the object moves on the surface it will experience three forces.

- a) Downward gravitational force (mg)
- b) Upward normal force (N)
- c) Frictional force opposite to the motion of the object.

Since there is no motion along the vertical direction, magnitude of normal force is equal to the magnitude of gravitational force.

$$N = mg$$

Applying Newton's second law along the *x* direction

$$m\vec{a} = -\mu_k mg\hat{i}$$

The acceleration is $\vec{a} = -\mu_k mg\hat{i}$

Note that the acceleration is along the *x* direction since the frictional force acts along the negative *x* direction.

Or
$$a = -\mu_k g$$

Note that the acceleration is uniform during the entire motion. We can use Newton's kinematic equation to find the final velocity.

Along the *x* direction
$$v^2 = u^2 + 2as$$

Here v = final velocity and u = initial velocity to be given to travel a distance s.

In this problem s = 10 m

Since the particle comes to rest, the final velocity v = 0

$$0 = u^{2} - 2\mu_{k}gs$$
$$u = \sqrt{2\mu_{k}gs}$$
$$u = \sqrt{2 \times 0.6 \times 9.8 \times 10} = 10.8 \ ms^{-1}$$

APPENDIX 1

Appendix-1.indd 279

 (\bullet)
14. In the section 3.7.3 (Banking of road) we have not included the friction exerted by the road on the car. Suppose the coefficient of static friction between the car tyre and the surface of the road is μ_s , calculate the minimum speed with which the car can take safe turn?

6

When the car takes turn in the banked road, the following three forces act on the car.

- (1) The gravitational force mg acting downwards
- (2) The normal force N acting perpendicular to the surface of the road
- (3) The static frictional force f acting on the car along the surface.

The following figure shows the forces acting on the horizontal and vertical direction.



When the car takes turn with the speed v, the centripetal force is exerted by horizontal component of normal force and static frictional force. It is given by

$$N\,\sin\theta + f\cos\theta = \frac{mv^2}{r} \qquad (1)$$

In the vertical direction, there is no acceleration. It implies that the vertical component of normal force is balanced by downward gravitational force and downward vertical component of frictional force. This can be expressed as



APPENDIX 1

$$N\cos\theta = mg + f\sin\theta$$

Or
$$N\cos\theta - f\sin\theta = mg$$
 (2)

Diving the equation (1) by equation (2), we get

$$\frac{N\sin\theta + f\cos\theta}{N\cos\theta - f\sin\theta} = \frac{v^2}{rg}$$
(3)

To calculate the maximum speed for the safe turn, we can use the maximum static friction is given by $f = \mu_s N$. By substituting this relation in equation (3), we get

$$\frac{N\sin\theta + \mu_s N\cos\theta}{N\cos\theta - \mu_s N\sin\theta} = \frac{v_{\max}^2}{rg}$$

By simplifying this equation,

$$\frac{N\cos\theta\left\{\left(\frac{N\sin\theta}{N\cos\theta}\right) + \mu_s\right\}}{N\cos\theta\left(1 - \mu_s\frac{N\sin\theta}{N\cos\theta}\right)} = \frac{v_{\max}^2}{rg}$$
$$\frac{\left(\tan\theta + \mu_s\right)}{1 - \mu_s\tan\theta} = \frac{v_{\max}^2}{rg}$$

The Maximum speed for safe turn is given

by
$$v_{\text{max}} = \sqrt{rg \frac{(\tan\theta + \mu_s)}{(1 - \mu_s \tan\theta)}}$$
 (4)

Suppose we neglect the effect of friction $(\mu_s = 0)$, then safe speed

$$v_{safe} = \sqrt{rg\tan\theta} \tag{5}$$

Note that the maximum speed with which the car takes safe turn is increased by friction (equation (4)). Suppose the car turns with speed $v < v_{safe}$, then the static friction acts up in the slope to prevent from inward skidding. If the car turns with the speed little greater than, then the static friction acts down the slope to prevent outward skidding. But if the car turns with the speed much greater than v_{safe} then static friction cannot prevent from outward skidding.

SOLVED EXAMPLE UNIT-4

1. A force $\vec{F} = \hat{i} + 2\hat{j} + 3\hat{k}$ N acts on a particle and displaces it through a distance $\vec{S} = 4\hat{i} + 6\hat{j}$ m. Calculate the work done.

Solution:

Force $\vec{F} = \hat{i} + 2\hat{j} + 3\hat{k}N$

Distance $\vec{S} = 4\hat{i} + 6\hat{j}m$

Work done = $\vec{F} \cdot \vec{S} = (\hat{i} + 2\hat{j} + 3\hat{k}) \cdot (4\hat{i} + 6\hat{j})$ = 4+12+0 = 16 J

2. A particle moves along X- axis from x=0 to x=8 under the influence of a force given by $F= 3x^2 - 4x + 5$. Find the work done in the process.

Solution:

Work done in moving a particle from x=0 to x=8 will be

$$W = \int_{0}^{8} F dx = \int_{0}^{8} (3x^{2} - 4x + 5) dx$$
$$= \left[\frac{3x^{3}}{3} - \frac{4x^{2}}{2} + 5x \right]_{0}^{8}$$
$$W = \left[3\frac{(8)^{3}}{3} - 4\left(\frac{8^{2}}{2}\right) + 40 \right]$$
$$= [512 - 128 + 40] = 424J$$

3. A body of mass 10kg at rest is subjected to a force of 16N. Find the kinetic energy at the end of 10 s.

Solution:

 $(\mathbf{0})$

Mass m = 10 kgForce F = 16 Ntime t = 10 s

$$a = F/m = \frac{16}{10} = 1.6ms^{-2}$$

we know that, v = u + at

$$= 0 + 1.6 \times 10 = 16 \text{ m s}^{-1}$$

Kinetic energy K.E
$$= \frac{1}{2} \text{mv}^{2}$$
$$= \frac{1}{2} \times 10 \times 16 \times 16$$
$$= 1280 \text{ J}$$

4. A body of mass 5kg is thrown up vertically with a kinetic energy of 1000 J. If acceleration due to gravity is $10 m s^{-2}$, find the height at which the kinetic energy becomes half of the original value.

Solution:

At a height 'h', mgh =
$$\frac{E}{2}$$

 $5 \times 10 \times h = \frac{1000}{2}$
 $h = \frac{500}{50} = 10 m$

5. Two bodies of masses 60 kg and 30 kg moving inthesame direction along straight line with velocity 40 cm s⁻¹ and 30 cm s⁻¹



respectively suffer one dimensional elastic collision. Find their velocities after collision.

Solution:

Mass $m_1 = 60 \text{ kg}$ Mass $m_2 = 30 \text{ kg}$ $V_1 = 40 \text{ cms}^{-1}$ $V_2 = 30 \text{ cms}^{-1}$

Solution:

$$v_{1} = \left(\frac{m_{1} - m_{2}}{m_{1} + m_{2}}\right)u_{1} + \left(\frac{2m_{2}}{m_{1} + m_{2}}\right)u_{2}$$
$$v_{2} = \frac{(m_{2} - m_{1})}{m_{1} + m_{2}}u_{2} + \frac{2m_{1}}{m_{1} + m_{2}}u_{1}$$

Substituting the values, we get,

$$v_1 = \frac{(60-30)}{90} \times 40 + \frac{2 \times 30}{90} \times 30$$

$$v_1 = \frac{1}{90} [1200 + 1800]$$
$$= \frac{3000}{90} = 33.3 cm s^{-1}$$

Likewise,

$$v_{2} = \frac{(30-60)}{90} \times 30 + \frac{2 \times 60}{90} \times 40$$
$$v_{2} = \frac{1}{90} [-900 + 4800]$$
$$= \frac{3900}{90} = 43.3 \, cm \, s^{-1}$$

6. A particle strikes a horizontal frictionless floor with a speed u at an angle θ with the vertical and rebounds with the speed v at an angle ϕ with the vertical. The coefficient

APPENDIX 1

of restitution between the particle and floor is e. What is the magnitude of v?



Solution:

۲

Applying component of velocities,



The x - component of velocity is

usin
$$\theta = vsin \phi$$
 (1)

The magnitude of y – component of velocity is not same, therefore, using coefficient of restitution,

$$e = \frac{v \cos \varphi}{u \cos \theta} \tag{2}$$

Squaring (1) and (2) and adding we get

$$v^{2} \sin^{2} \varphi = u^{2} \sin^{2} \theta$$

$$v^{2} \cos^{2} \varphi = e^{2} u^{2} \cos^{2} \theta$$

$$adding$$

$$v^{2} = u^{2} \sin^{2} \theta + e^{2} u^{2} \cos^{2} \theta$$

$$\therefore v^{2} = u^{2} \left[\sin^{2} \theta + e^{2} \cos^{2} \theta \right]$$

$$v = u \sqrt{\sin^{2} \theta + e^{2} \cos^{2} \theta}$$

()

7. A particle of mass m is fixed to one end of a light spring of force constant k and un-stretched length *l*. It is rotated with an angular velocity ω in horizontal circle. What will be the length increase in the spring?

Solution:

Mass of particle = m Force constant = k Un-stretched length = lAngular velocity = ω



Let 'x' be the increase in the length of the spring.

The new length = (l+x) = r

When the spring is rotated in a horizontal circle,

Spring force = centripetal force.

$$kx = m\omega^{2}(l+x)$$
$$x = \frac{m\omega^{2}l}{k-m\omega^{2}}$$

8. A gun fires 8 bullets per second into a target X. If the mass of each bullet is 3 g and its speed 600 ms⁻¹, then calculate the power delivered by the bullets.

Solution:

Power = work done per second = total kinetic energy of 8 bullets per second

$$P = 8 \times (\text{kinetic energy of each} \\ \text{bullet per second})$$
$$= 8 \times \frac{1}{2} \times (3 \times 10^{-3}) \times (600)^{2}$$
$$P = 4320 \text{ W}$$
$$P = 4.320 \text{ kW}$$

SOLVED EXAMPLE UNIT-5

1. Three particles of masses $m_1 = 1$ kg, $m_2 = 2$ kg and $m_3 = 3$ kg are placed at the corners of an equilateral triangle of side 1m as shown in Figure. Find the position of centre of mass.

Solution:

 $(\mathbf{0})$



The centre of mass of an equilateral triangle lies at its geometrical centre G.

The positions of the mass m_1 , m_2 and m_3 are at positions A, B and C as shown in the Figure.

From the given position of the masses, the coordinates of the masses m_1 and m_2 are easily marked as (0,0) and (1,0) respectively.

APPENDIX 1



 (\bullet)

To find the position of m_3 the Pythagoras theorem is applied. As the ΔDBC is a right angle triangle,

 $BC^{2} = CD^{2} + DB^{2}$ $CD^{2} = BC^{2} - DB^{2}$

$$CD^{2} = 1^{2} - \left(\frac{1}{2}\right)^{2} = 1 - \left(\frac{1}{4}\right) = \frac{3}{4}$$
$$CD = \frac{\sqrt{3}}{2}$$

$$\left(\frac{1}{2},\frac{\sqrt{3}}{2}\right) \text{ or } \left(0.5,0.5\sqrt{3}\right)$$

X Coordinate of centre of mass,

$$x_{CM} = \frac{m_1 x_1 + m_2 x_2 + m_3 x_3}{m_1 + m_2 + m_3}$$

$$x_{CM} = \frac{(1 \times 0) + (2 \times 1) + (3 \times 0.5)}{1 + 2 + 3} = \frac{3.5}{6}$$
$$x_{CM} = \frac{7}{12} \text{ m}$$

Y Coordinate of centre of mass,

$$y_{CM} = \frac{m_1 y_1 + m_2 y_2 + m_3 y_3}{m_1 + m_2 + m_3}$$

$$y_{CM} = \frac{(1 \times 0) + (2 \times 0) + (3 \times 0.5 \times \sqrt{3})}{1 + 2 + 3} = \frac{1.5\sqrt{3}}{6}$$
$$y_{CM} = \frac{\sqrt{3}}{4} \text{ m.}$$

.: The coordinates of centre of mass G

$$(x_{CM}, y_{CM})$$
 is $\left(\frac{7}{12}, \frac{\sqrt{3}}{4}\right)$

2. An electron of mass $9 \times 10^{-31} kg$ revolves around a nucleus in a circular orbit of radius 0.53 Å. What is the angular momentum of the electron? (Velocity of electron is, v = $2.2 \times 10^6 m s^{-1}$)

Solution:

۲

Mass of the electron, $m = 9 \times 10^{-31} kg$

Radius of the electron, $r = 0.53 \text{ Å} = 0.53 \times 10^{-10} m$

Velocity of the electron, v = 2.2 \times 10⁶ ms⁻¹

Angular momentum of electron is, $L = I \omega$

Electron is considered as a point mass. Hence, its moment of inertia is, $I = m r^2$

The relation, $\omega = \frac{v}{r}$ could be used. Angular momentum, $L = mr^2 \times \frac{v}{r}$ = mvr

$$= 9.1 \times 10^{-31} \times 2.2 \times 10^{6} \times 0.53 \times 10^{-10}$$
$$L = 1.06 \times 10^{-34} kg m^{2} s^{-1}$$

3. A solid sphere of mass 20 kg and radius 0.25 m rotates about an axis passing through the centre. What is the angular momentum if the angular velocity is 5 rad s^{-1}

Solution:

Mass of the sphere, m = 20 kgRadius r = 0.25 m

APPENDIX 1

()

()

Angular velocity
$$\omega = 5 \text{ rad s}^{-1}$$

Solution:

Angular momentum $L = I\omega = \frac{2}{5}mr^2\omega$

$$= \frac{2}{5} \times 20 \times (0.25)^2 \times 5 = 40 \times (0.0625) = 2.5$$

L = 2.5 kg m²s⁻¹

4. A solid cylinder when dropped from a height of 2 m acquires a velocity while reaching the ground. If the same cylinder is rolled down from the top of an inclined plane to reach the ground with same velocity, what must be the height of the inclined plane? Also compute the velocity.

Solution:

۲



In the first case,

potential energy = kinetic energy

$$mgh = \frac{1}{2}mv^{2}$$

$$mg \times 2 = \frac{1}{2}mv^{2}$$
(1)

In second case,

potential energy = translational kinetic energy + rotational kinetic energy $mgh' = \frac{1}{2}mv^2 + \frac{1}{2}I\omega^2$ $mgh' = \frac{1}{2}mv^2 + \frac{1}{2}\left(\frac{mr^2}{2}\right)\left(\frac{v^2}{r^2}\right)$

$$\therefore \,\mathrm{mgh}' = \frac{3}{4}mv^2 \qquad (2)$$

Dividing (2) by (1),

۲

$$\frac{mgh'}{mg \times 2} = \frac{\frac{3}{4}mv^2}{\frac{1}{2}mv^2} = \frac{3}{4} \times \frac{2}{1} = \frac{3}{2}$$
$$h' = 3m$$

From equation (1), $2mg = \frac{1}{2}mv^2$

$$v = \sqrt{4g} = 2\sqrt{g}$$
$$v = 2 \times \sqrt{9.81}$$
$$v = 6.3 \, m \, s^{-1}$$

 A small particle of mass m is projected with an initial velocity v at an angle θ with x axis in X-Y plane as shown in Figure. Find the angular momentum of the particle.

Solution:



Let the particle of mass m cross a horizontal distance x in time t.

Angular momentum $\vec{L} = \int \vec{\tau} dt$ But $\vec{\tau} = \vec{r} \times \vec{F}$ $\vec{r} = x\hat{i} + y\hat{j}$ and $\vec{F} = -mg\hat{j}$

$$\therefore \vec{\tau} = (x\hat{i} + y\hat{j}) \times (-mg\hat{j})$$
$$\vec{\tau} = -mgx(\hat{i} \times \hat{j}) = -mgx\hat{k}$$
$$\vec{L} = -mg\int (xdt)\hat{k} = -mgv\cos\theta(\int tdt)\hat{k}$$

Let initial time t = 0 and final time $t = t_f$

$$\therefore \vec{L} = -mgv\cos\theta \left(\int_{0}^{t_{f}} tdt\right) \hat{k} = -\frac{1}{2}mgv\cos\theta t_{f}^{2} \hat{k}$$

Negative sign indicates, \vec{L} point inwards

6. From a complete ring of mass M and radius R, a sector angle θ is removed. What is the moment of inertia of the incomplete ring about axis passing through the centre of the ring and perpendicular to the plane of the ring?

APPENDIX 1

Solution:

Let R be the radius of the ring and M be the total mass of the complete ring.

Let m be the mass of the section removed from the ring then, mass of the incomplete ring is M-m



Let us introduce a positive integer (n), such that, $n\theta = 360^\circ$, or $n = \frac{360^\circ}{\theta}$

mass of incomplete ring = M - m

$$m = \frac{M}{360} \times \theta$$

$$\therefore$$
 mass of incomplete ring = $M - \frac{M}{360} \times \theta$

mass of incomplete ring = $M - \frac{M}{n} = M \frac{(n-1)}{n}$

For example, *a*) when $\theta = 60^\circ$; $n = \frac{360^\circ}{60^\circ} = 6$

$$\therefore n-1=5$$

mass of incomplete ring $=\frac{5}{6}M$ b) when $\theta = 30^{\circ}$, $n = \frac{360^{\circ}}{30^{\circ}} = 12$ n - 1 = 11mass of incomplete ring $=\frac{11}{12}M$

286

 (\bullet)

The moment of inertia of the incomplete ring is, $I = M \frac{(n-1)}{n} R^2$

7. A massless right angled triangle is suspended with its right angle corner. A mass of 100 kg is suspended from another corner B which subtends an angle 53°. Find the mass m that should be suspended from other corner C so that BC (hypotenuse) remains horizontal.

Solution:



From the principle of moments,

$$100 \times g \times x_1 = m \times g \times x_2$$
$$100 \times \cos 53^\circ = m \times \cos 37^\circ \qquad (1)$$

Where, x_1 and x_2 are the arm lengths.

The right angle triangle with angles 37°, 53° and 90° is a special triangle which has the respective sides in the ratio, 3:4:5 as shown in the diagram.



Substituting the values in equation (1),

$$100 \times \cos 53^\circ = m \times \cos 37^\circ$$
$$100 \times \frac{3}{5} = m \times \frac{4}{5}$$
$$m = 100 \times \frac{3}{4}$$
$$m = 75 \, kg$$

8. If energy of 1000 J is spent in increasing the speed of a flywheel from 30 rpm to 720 rpm, find the moment of inertia of the wheel.

Solution:

۲

$$\omega_1 = 30rpm = 2\pi \times \frac{30}{60} rads^{-1} = \pi rads$$
$$\omega_2 = 720rpm$$
$$= 2 \pi \times \frac{720}{60} rads^{-1} = 24\pi rads$$

Change in kinetic energy,

$$\Delta \mathrm{KE} = \frac{1}{2} I(\omega_2^2 - \omega_1^2)$$

$$I = \frac{2 \times \Delta KE}{(\omega_2^2 - \omega_1^2)} = \frac{2 \times 1000}{(24\pi)^2 - (\pi)^2}$$
$$I = \frac{2000}{25\pi \times 23\pi}$$
Remember:
$$a^2 - b^2 = (a + b) (a - b)$$
$$I \approx 0.35 \text{ kg m}^2 \qquad \text{as} \quad \pi^2 \approx 10$$

9. Consider two cylinders with same radius and same mass. Let one of the cylinders be solid and another one be hollow. When subjected to same torque, which one among them gets more angular acceleration than the other?

APPENDIX 1



Solution:

Moment of inertia of a solid cylinder about its axis $I_s = \frac{1}{2}MR^2$

Moment of inertia of a hollow cylinder about its axis $I_h = MR^2$

$$I_{s} = \frac{1}{2} I_{h} \text{ or } I_{h} = 2I_{s}$$

$$torque \ \tau = I \alpha$$

$$\alpha = \frac{\tau}{I}$$

$$\alpha_{s} = \frac{\tau}{I_{s}} \text{ and } \alpha_{h} = \frac{\tau}{I_{h}}$$

$$\alpha_{s} I_{s} = \alpha_{h} I_{h} \Rightarrow \alpha_{s} = \alpha_{h} \frac{I_{h}}{I_{s}}$$

$$\alpha_{s} I_{s} = \alpha_{h} I_{h} \Rightarrow \alpha_{s} = \alpha_{h} \frac{I_{h}}{I_{s}}$$

Since,

$$I_{h} > I_{s} \Rightarrow \frac{I_{h}}{I_{s}} > 1$$

$$\therefore \alpha_{s} > \alpha_{h}$$

For the same torque, a solid cylinder gets more acceleration than a hollow cylinder.

Note: The above two cylinders must be made up of materials of different density. (Say why?)

10. A thin horizontal circular disc is rotating about a vertical axis passing through its centre. An insect goes from A to point B along its diameter as shown in Figure. Discuss how the angular speed of the circular disc changes?

Solution:

As the disc is freely rotating, with the insect on it, the angular momentum of the system is conserved.

$$L = I \omega = \text{constant}$$



When the insect moves towards the centre (from A to O), the moment of inertia (I) decreases. Thus, the angular velocity (ω) increases. When it moves away from centre (from O to B), the moment of inertia (I) increases. Thus, the angular velocity (ω) decreases.

- 11. (i) What is the shape of the graph between $\sqrt{E_{kr}}$ and L? (E_{kr} is the rotational kinetic energy and L is angular momentum)
 - (ii) What information can you get from the slope of the graph?
 - (iii) You are given the graph of $\sqrt{E_{kr}}$ and L for two bodies A and B. Which one has more moment of inertia?

Solution:

i) We know that, Rotational kinetic Energy

$$E_{kr} = \frac{1}{2}I\omega^{2}$$

$$= \frac{1}{2}I\omega \times \omega = \frac{1}{2}.L.\omega = \frac{1}{2}\frac{L^{2}}{I} \qquad \therefore L = I\omega$$

$$\omega = L/I$$

$$E_{kr} = \frac{L^{2}}{2I}$$

$$L^{2} = 2IE_{kr}$$

$$L = \sqrt{2IE_{kr}} = \sqrt{2I}.\sqrt{E_{kr}}$$

()

 \bigcirc

Graph of $\sqrt{E_{kr}}$ and L:



The shape of the graph is a straight line

- ii) The slope of the graph gives the value of moment of inertia I.
- iii) We know that the slope gives the value of moment of Inertia. The line A has higher slope and hence more moment of Inertia.



12. Consider a thin uniform circular ring rolling down in an inclined plane without slipping. Compute the linear acceleration along the inclined plane if the angle of inclination is 45°.

Solution:

The linear acceleration along the inclined plane can be computed by

$$a = \frac{g\sin\theta}{1 + \frac{K^2}{R^2}}$$

For a thin uniform circular ring, axis passing through its centre is $I = MR^2$

$$\therefore K^2 = R^2 \Longrightarrow \frac{K^2}{R^2} = 1.$$

And the angle of inclination, $\theta = 45^{\circ}$

$$\Rightarrow (\sin 45^\circ = \frac{1}{\sqrt{2}})$$

Hence,

$$a = \frac{\frac{g}{\sqrt{2}}}{1+1}$$
$$a = \frac{g}{2\sqrt{2}} ms^{-2}$$





Table A1.1 Systematic developments in P	hysics over centuries
Observation of motion of Sun, Stars, Planets and Moon	Around 3000 BC (Early Greeks)
In the universe everything is changing. Nothing remains in the same state indefinitely. The idea of 'time' started with this understanding.	Around 500 BC (Heraclitus).
Everything is composed of entirely small indivisible elements called 'atoms'. Development of theory of 'atomism'. But that time it is a hypothesis. No experimental proof.	End of 500 BC (Democritus and Leucippus)
 Idea of natural laws behind every day phenomena 	Around 3 rd century BC (Aristotle)
 Idea of motion with gravity 	
 Theory of four elements(Everything is made up of Earth, water, fire, air able to inter-transform into each other) 	
• Earth is centre of universe(Hypothesis)	
• Force is required to move the object	
 Heavier object falls faster towards Earth than lighter object 	
• Earth is sphere	Around 240 BC (Eratosthenes)
 Measurement of radius of the Earth almost accurately 	

Та	ble A1.1 Systematic developments in p	hysics over centuries (Cont)											
-	Sun is centre of the solar system (Hypothesis. Could not be proven by experimental evidence)	Around 2 nd century BC (Aristarchus of Samos)											
-	Idea of Earth rotation around its own axis.	Around 2 nd century BC (Seleucia)											
-	Foundation of hydrostatics	Around 3 rd century BC (Archimedes)											
•	Idea of lever												
-	Mechanical work using pulleys												
-	Law of Buoyancy known as a Archimedes principle												
•	First accurate value of the number 'pi'												
•	Focused on motion of planets and stars	End of 2 nd century BC (Hippachrus)											
•	Prediction of solar eclipses												
-	Calculation of distance of Earth to Moon, Earth to Sun												
	Astronomical observation were recorded												
-	Geo centric model (Not hypothesis. Explained a lot of naked eye observation)	Around 100 AD(CE) (Ptolemy)											
-	Explanation of Planets 'retrograde motion'												
•	"Almagest" - First book on astronomy												
•	Idea of Earth's rotation about its own axis	5 th Century AD (Aryabhatta-India)											
•	Idea of zero												
•	Contribution to mathematics												
•	Understanding of early optics	9 th century AD (Ibn al-Hayatham- Arabia)											
•	Boon on 'Treasury of astronomy'- Accurate astronomical table than Ptolemy's data	12 th Century AD (Nasir al-Din- Persian astronomer)											
-	From 7 th century to 14 th century major development in science happened in muslim countries (Arabia, Persia, Iran etc.)												

۲

|

Та	ble A1.1 Systematic developments in p	hysics over centuries (Cont)
	Copernicun Revolution	15 th Century AD
•	Heliocentric model (Not hypothesis.	AD 1543 (Copernicus)
	It provides simplest explanation than	
	Ptolemy model for motion of stars and	
	Planets)	
•	Accurate astronomical datas	Tycho Brahe
•	Laws of Planetary motion	Kepler
•	Law of inertia	Gallieo Galilei (1564- 1642)
•	Telescope observation(Founder of	
_	modern observational astronomy)	
Ξ.	of the Jupiter	
	Earth is not flat	
	All object fall to Earth at the same rate	
	(Disproved Aristotle's argument)	
•	Law of inertia(Force need not required	
	to maintain the motion- disproved	
	Aristotle's argument)	
•	Pendulum, inclined plane experiments	
•	Study of projectile motion	
•	Introduction of controlled experiments'	
•	Introduction of Cartesian coordinate	Rane Descarte (1596-1650)
_	system	
÷	17 th and 18 th contury Development	
-	Less fraction	$\mathbf{L}_{\mathbf{r}} = \mathbf{N}_{\mathbf{r}} = \mathbf{L}_{\mathbf{r}} = (1 (\mathbf{A} 2 1 7 2 7)$
	Laws of motion	Isaac Newton (1642-1/2/)
	Law of gravitation	
	Development of calculus independent of	
	Leibnitz	
•	Founder of modern optics (reflection,	
	dispersion, prism)	
	Light consists of minute particles	
	'corpuscules'	
	Derivation of Kepler laws	
•	Greatest book 'The principia	
_	mathematica (1687)	
	wave theory of light	Christian Huygens; Father of modern optics

292 APPENDIX 2

۲

۲

Та	ble A1.1 Systematic developments in p	hysics over centuries (Cont)
•	Work on magnetism	William Gilbert (Around 1600)
•	Behavior of gases	Robert Boyle (1627- 1691)& Robert Hooke
1	Fluid dynamics - Bernoulli's theorem (1734)	Daniel Bernoulli(1700- 1782)
•	Early ideas of kinetic theory of gases	Daniel Bernoulli (1700 - 1782)
•	Study of spring motion(Hooke's law)	Robert Hooke
•	Derivation of frequency of vibration in strings(1714)	Taylor
•	Reformulation of Newtonian mechanics using Energy approach (Lagrangian mechanics)	De Alembert, Lagrange
•	Invention of steam engine(1781)-	James Watt
•	Force between charges (Coulomb's law)	Coulomb
•	19th century development	
•	Early ideas of Thermodynamics(1840s)	James Joule, Carnot
•	Caloric theory	
•	Laws of thermodynamics(1850s)	Kelvin, Clausius
1	Behavior of gases, velocity and speed(1860s)	James Clark Maxwell
•	Foundation of statistical mechanics and entropy formula (around 1870s)	Boltzmann
•	Wave nature of light- Experiments	Young and Fresnel
•	Behavior of electric charges	
•	Magnetic effect of electric current(1820s)	Oersted
•	Force between two parallel currents	Ampere
1	Principle of Least action, Hamilton mechanics (1821)	William Hamilton
•	Electric powered motor, electricity demonstration	Micheal Faraday
•	Theory of electromagnetism(1873)- Bridge between electricity and magnetism	James Clerk Maxwell
•	Maxwell equations –Paved way to modern technology	
•	Alternating current	Tesla

Та	ble A1.1 Systematic developments in p	hysics over centuries (Cont)
	20 th century developments	
•	Study of black body radiation	Max planck(around 1900)
•	Discovery of an electron	J.J.Thomson
•	Rutherford atomic model	Rutherford(1910s)
•	Study on radioactivity	Marie Curie(1920s and 30s)
-	Special theory of relativity, Photo electric effect, Existence of atom(1905), $E=mc^2$	Albert Einstein
•	Revolution of physics after Newton	
•	New Idea of space and time	
-	The General theory of relativity(Greatest theory of 20 th century)- 1915	
	Study of specific heat capacities	
•	Study of atoms	
-	Bohr atom model (1912)	Niels Bohr
-	Behavior of electron, proton – Schrodinger equation	Schrodinger
-	Uncertainty principle	Heisenberg
-	Formulation of Quantum Mechanics	Paul Dirac
-	Formulation of quantum field theory	Dirac, Feynman, Schwinger
-	Particle physics, standard model	Gellman, Weinberg, Abdus salam
-	X-ray diffraction(1930s)- Paved way to understanding the materials	
-	Raman effect	C.V. Raman(India)
-	Study of stars and black holes	Chandrasekhar(Indian origin)
-	Invention of transistor(1947)	John Bardeen, Walter Brattain,William
-	Classification of stars using temperature	Schokley
	(Astro thermodynamics), Saha ionization formula	Megnad Saha(India)
-	Field of Cosmology (1920s)	Eddington, Schwarchild
	Expanding universe model(1922)	Thomas Friedmann
	Discovery of redshift	Edwin Hubble



۲

|___

۲

Table A1.1 Systematic developments in p	hysics over centuries (Cont)
 Birth of materials science 	
 Nanotechnology, Condensed matter physics 	
 Gravitational waves, Dark energy, Dark matter, String theory 	

APPENDIX A1.2

vi) Error involving the division of two quantities (using the method of differentiation)

Consider $Z = \frac{A^n}{B^m}$

Taking logarithms of both the sides,

 $\log Z = \log A^{n} - \log B^{m}$ $\log Z = n \log A - m \log B$

Differentiating both sides, we get,

$$\frac{dZ}{Z} = n\frac{dA}{A} - m\frac{dB}{B}$$

In terms of fractional error, this may be written as,

$$\pm \frac{\Delta Z}{Z} = \pm n \frac{\Delta A}{A} \mp m \frac{\Delta B}{B}$$

Maximum possible relative error in z is given by

$$\frac{\Delta Z}{Z} = n\frac{\Delta A}{A} + m\frac{\Delta B}{B}$$

vii) Error involving the product of three quantities (using calculus method) let $u = x^m y^n Z^p$

Taking logarithms on both sides, we get

$$\log u = \log x^{m} + \log y^{n} + \log Z^{p}$$
$$\log u = m \log x + n \log y + p \log Z$$

Differentiating both sides, we get

$$\frac{du}{u} = m\frac{dx}{x} + n\frac{dy}{y} + p\frac{dz}{z}$$

In terms of fractional error, the equation maybe rewritten as,

$$\pm \frac{\Delta u}{u} = \pm m \frac{\Delta x}{x} \pm n \frac{\Delta y}{y} \pm p \frac{\Delta z}{z}$$

APPENDIX A2.1

Parallelogram Law of Vector addition:

If two non-zero vectors \vec{A} and \vec{B} are represented by the two adjacent sides of a parallelogram then the resultant is given by the diagonal of the parallelogram passing through the point of intersection of the two vectors.

Consider the figure 2.19 below. Here the two vectors \vec{A} and \vec{B} are connected by a common tail at an angle θ . The parallelogram OACB is next constructed.



APPENDIX 2

Then the diagonal OC is the resultant (\hat{R}) passing through the common tail O.



We next find the magnitude and direction of this resultant vector.

(i) Magnitude:

()

First extend OA to the point N, so that we get ON. Then CN is drawn perpendicular to this ON, from C. Then ONC is a right angled triangle. We can write $R^2 = ON^2 + CN^2$

 $R^{2} = (OA + AN)^{2} + CN^{2}$ $\Rightarrow R^{2} = A^{2} + B^{2} + 2AB\cos\theta$ $\therefore R = \left|\vec{R}\right| = \left|\vec{A} + \vec{B}\right| = \sqrt{A^{2} + B^{2} + 2AB\cos\theta}$

Special cases: When $\theta = 0^\circ$, then R = A+BWhen $\theta = 180^\circ$, then R = A-BWhen $\theta = 90^\circ$, then $R = \sqrt{A^2 + B^2}$

(ii) Direction

۲

Let β be the angle between the vectors \vec{A} and \vec{R} . Then

$$\tan\beta = \frac{CN}{ON} = \frac{B\sin\theta}{A + B\cos\theta}$$

APPENDIX 3

۲

Some important formulae for Integral
(1)
$$\int dx = x$$
; $\frac{d}{dx}(x) = 1$

(2)
$$\int x^n dx = \left(\frac{x^{n+1}}{n+1}\right); \ \frac{d}{dx}\left(\frac{x^{n+1}}{n+1}\right) = x^n$$

- (3) $\int cudx = c \int udx$ where c is a constant
- (4) $\int (u \pm v \pm w) dx = \int u dx \pm \int v dx \pm \int w dx$

(5)
$$\int \frac{1}{x} dx = \ln x + C$$

(6)
$$\int e^x dx = e^x + C$$

۲

(7)
$$\int \cos\theta d\theta = \sin\theta + C$$

(8) $\int \sin\theta d\theta = -\cos\theta + C$

Some important formulae in Differential calculus

- 1. $\frac{d}{dx}(c) = 0$, if c is a constant
- 2. If y = cu, where c is a constant

and u is a function of x then

$$\frac{dy}{dx} = \frac{d}{dx}(cu) = c\frac{du}{dx}$$

3. If $y = u \pm v \pm w$ where u,v and w are functions of x then

$$\frac{dy}{dx} = \frac{d}{dx}(u \pm v \pm w) = \frac{du}{ds} \pm \frac{dv}{dx} \pm \frac{dw}{dx}$$

4. If $y = x^n$, where n is the real number then

$$\frac{dy}{dx} = \frac{d}{dx}(x^n) = nx^{n-1}$$

5. If y = uv, where u and v are functions of x then

$$\frac{dy}{dx} = \frac{d}{dx}(uv) = u\frac{dv}{dx} + v\frac{du}{dx}$$

6. If y is a function of x, then
$$dy = \frac{dy}{dx} dx$$

7.
$$\frac{d}{dx}(e^x) = e^x$$

8.
$$\frac{d}{dx}(\ln x) = \frac{1}{x}$$

9.
$$\frac{d}{d\theta}(\sin\theta) = \cos\theta$$

10.
$$\frac{d}{d\theta}(\cos\theta) = -\sin\theta$$

11. If y is a trigonometric function of θ and θ is the function of t, then

$$\frac{d}{dt}(\sin\theta) = \cos\theta \frac{d\theta}{dt}$$
$$\frac{d}{dt}(\cos\theta) = -\sin\theta \frac{d\theta}{dt}$$

Appendix-2.indd 297

۲



(THE GREEK ALPHABET)

(கிரேக்க எழுத்துகள்)

The Greek Alphabet	Upper Case	Lower Case
Alpha	А	α
Beta	В	β
Gamma	Γ	γ
Delta	Δ	δ
Epsilon	Е	3
Zeta	Z	ζ
Eta	Н	η
Theta	Θ	θ
Iota	Ι	l
Карра	K	К
Lambda	Λ	λ
Mu	М	μ
Nu	Ν	ν
Xi	€	ξ
Omicron	О	0
Pi	Π	π
Rho	Р	ρ
Sigma	Σ	σ
Tau	Т	τ
Upsilon	Y	υ
Phi	Φ	φ
Chi	X	χ
Psi	Ψ	Ψ
Omega	Ω	ω



Appendix-3.indd 298

۲

SOME IMPORTANT CONSTANTS IN PHYSICS

Name	Symbols	Value
Speed of light in vacuum	С	$2.9979 \times 10^8 \mathrm{m\ s^{-1}}$
Gravitational constant	G	$6.67 \times 10^{-11} \text{ N m}^2 \text{ kg}^{-2}$
Acceleration due to gravity (sea level, at 45° latitude)	g	9.8 m s ⁻²
Planck constant	h	$6.626 \times 10^{-34} \text{ J s}$
Boltzmann constant	k	$1.38 \times 10^{-23} \text{ J K}^{-1}$
Avogadro number	N_{A}	$6.023 \times 10^{23} \text{ mol}^{-1}$
Universal gas constant	R	8.31 J mol ⁻¹ K ⁻¹
Stefan – Boltmann constant	σ	$5.67 \times 10^{-8} \text{ W m}^{-2} \text{ K}^{-4}$
Wien's constant	Ь	$2.898 \times 10^{-3} \text{ m K}$
Permeability of free space	μ_{0}	$4\pi \times 10^{-7} \text{ H m}^{-1}$
Standard atmospheric pressure	1 atm	1.013×10^5 Pa

۲

APPENDIX 4

۲

۲

GLOSSARY கலைச்சொற்கள்

۲



- 1. Acceleration
- 2. Angular Momentum
- 3. Astro physics
- 4. Average Velocity
- 5. Angular displacement
- 6. Angular velocity
- 7. Angular acceleration
- 8. Angle of friction
- 9. Angle of repose
- 10. Centripetal acceleration
- 11. Circular Motion
- 12. Concurrent forces
- 13. Coplanar force
- 14. Centripetal force
- 15. Centrifugal force
- 16. Coefficient of friction
- 17. Centre of mass
- 18. Couple
- 19. Centre of gravity
- 20. Circular Motion
- 21. Collision
- 22. Conservative force
- 23. Dimensional Analysis
- 24. Displacement
- 25. Escape -Speed
- 26. Elastic potential energy
- 27. Elastic collision
- 28. Free body diagram
- 29. Gravitational Constant
- **30**. Gravitational field
- **31**. Gravitational potential
- **32**. Gravitational Potential energy
- **33**. Gross Error
- 34. Geo stationary satellite
- 35. Horizontal plane
- **36**. Horse power

- முடுக்கம்
- கோண உந்தம்
- வானியற்பியல்
- சராசரித் திசைவேகம்
- கோண இடப்பெயர்ச்சி
- கோணத் திசைவேகம்
- கோண முடுக்கம்
- உராய்வுக் கோணம்
- ச<u>ற</u>ுக்குக் கோணம்
- ைய நோக்கு முடுக்கம்
- வட்ட இயக்கம்
- பைய விசைகள்
- ஒரு தள விசைகள்
- மையநோக்கு விசை
- மையவிலக்கு விசை
- உராய்வுக் குணகம்
- நிறை மையம்
- இரட்டை
- ஈர்ப்பு மையம்
- வட்ட இயக்கம்
- மோதல்
- _____________ ஆற்றல் மாற்றா விசை
- ் பரிமாண பகுப்பாய்வு
- இடப்பெயர்ச்சி
- விடுபடு வேகம்
- மீட்சியழுத்த ஆற்றல்
- மீட்சி மோதல்
- தனித்த பொருளின் விசைப்படம்
- ஈர்ப்பியல் மாறிலி
- ஈர்ப்புப்புலம்
- *ஈர்ப்ப(ழத்தம்*
- ஈர்ப்ப(ழத்த ஆற்றல்
- மொத்த பிழை
- பவி நிலைத் துணைக்கோள்/
- செயற்கைக்கோள்
- கிடைத்தளம்
- குதிரைத்திறன்
- 300

37. Instantaneous Velocity 38. Inclined plane 39. Inertial frame 40. Impulse 41. Instantaneous power **42**. Kinetic friction 43. Linear motion 44. Linear density 45. Linear momentum 46. Least Count error 47. Motion 48. Moment of inertia 49. Non conservative force 50. Orbital speed 51. One dimensional motion 52. accuracy 53. Parallax Method

- 54. Projectile
- 55. Point mass
- 56. Precison
- 57. Planetary Motion
- 58. Polar satellite
- 59. Precession
- 60. Pulley

()

- 61. Rolling
- 62. Random error
- 63. Rounding off
- 64. Rest
- 65. Retardation
- 66. Relative velocity
- 67. Range
- 68. Rolling friction
- 69. Rigid body
- 70. Radius of gyration
- 71. Rotational Motion
- 72. Spring Constant
- 73. Sliping
- 74. Sliding
- 75. Systematic error
- 76. Static friction
- 77. Significant Number
- 78. Time of flight
- 79. Torque
- 80. Translational Motion
- 81. Tension
- 82. Velocity

உடனடி / கணத் திசைவேகம்

சாய்தளம்

۲

- நிலைமக்குறிப்பாயம்
- கணத்தாக்கு
- உடனடித்திறன்
- இயக்க உராய்வு
- நேர்கோட்டு இயக்கம்
- நீள் அடர்த்தி
- நேர்கோட்டு உந்தம்
- மீச்சிற்றளவு பிழை
- இயக்கம்

_

- நிலைமத்திருப்புத் திறன்
- ஆற்றல் மாற்றும் விசை
- சுற்றியக்க வேகம்
 - ஒரு பரிமாண இயக்கம்
 - துல்லியத்தன்மை
 - ___________தொற்றமுறை
 - எறியம்
- புள்ளி நிறை
- நுட்பத்தன்மை
- கோள்களின் இயக்கம்
- துருவ மைய துணைக்கோள்/
- செயற்கைக்கோள்
- அச்சுச் சுழற்சி
- கப்பி
- உருளுதல்
- ் சமவாய்ப்பு பிழை
- முழுமைபடுத்துதல்
- ஓய்வு
- எதிர் முடுக்கம்
- சார்புத்திசைவேகம்
- கிடைத்தள தூரம்
- உருள்தலில் உராய்வு
- திண்மப்பொருள்
- சுழற்சி ஆரம்
- சுழற்சி இயக்கம்
- சுருள் மாறிலி
- நழுவுதல்
- சறுக்குதல் - முறையான பி
- முறையான பிழை
- நிலை உராய்வு
- முக்கிய எண்ணுரு
- பறக்கும் நேரம்
- திருப்பு விசை
- இடம்பெயர்வு இயக்கம்
- இழுவிசை
- திசைவேகம்

GLOSSARY



Glossary.indd 301

LOGARITHM TABLE

													Me	ean	Diffe	erer	ice		
	0	1	2	3	4	5	6	7	8	9	1	2	3	4	5	6	7	8	9
10	0.000	0.004	0.009	0.013	0.017	0.021	0.025	0.029	0.033	0.037	4	8	11	17	21	25	29	33	37
11	0.041	0.045	0.049	0.053	0.057	0.061	0.064	0.068	0.072	0.076	4	8	11	15	19	23	26	30	34
12	0.079	0.083	0.086	0.090	0.093	0.097	0.100	0.104	0.107	0.111	3	7	10	14	17	21	24	28	31
13	0.114	0.117	0.121	0.124	0.127	0.130	0.134	0.137	0.140	0.143	3	6	10	13	16	19	23	26	29
14	0.146	0.149	0.152	0.155	0.158	0.161	0.164	0.167	0.170	0.173	3	6	9	12	15	18	21	24	27
15	0.176	0.179	0.182	0.185	0.188	0.190	0.193	0.196	0.199	0.201	3	6	8	11	14	17	20	22	25
16	0.204	0.207	0.210	0.212	0.215	0.217	0.220	0.223	0.225	0.228	3	5	8	11	13	16	18	21	24
17	0.230	0.233	0.236	0.238	0.241	0.243	0.246	0.248	0.250	0.253	2	5	7	10	12	15	17	20	22
18	0.255	0.258	0.260	0.262	0.265	0.267	0.270	0.272	0.274	0.276	2	5	7	9	12	14	16	19	21
19	0.279	0.281	0.283	0.286	0.288	0.290	0.292	0.294	0.297	0.299	2	4	7	9	11	13	16	18	20
20	0.301	0.303	0.305	0.307	0.310	0.312	0.314	0.316	0.318	0.320	2	4	6	8	11	13	15	17	19
21	0.322	0.324	0.326	0.328	0.330	0.332	0.334	0.336	0.338	0.340	2	4	6	8	10	12	14	16	18
22	0.342	0.344	0.346	0.348	0.350	0.352	0.354	0.356	0.358	0.360	2	4	6	8	10	12	14	15	17
23	0.362	0.364	0.365	0.367	0.369	0.371	0.373	0.375	0.377	0.378	2	4	6	7	9	11	13	15	17
24	0.380	0.382	0.384	0.386	0.387	0.389	0.391	0.393	0.394	0.396	2	4	5	7	9	11	12	14	16
25	0.398	0.400	0.401	0.403	0.405	0.407	0.408	0.410	0.412	0.413	2	3	5	7	9	10	12	14	15
26	0.415	0.417	0.418	0.420	0.422	0.423	0.425	0.427	0.428	0.430	2	3	5	7	8	10	11	13	15
27	0.431	0.433	0.435	0.436	0.438	0.439	0.441	0.442	0.444	0.446	2	3	5	6	8	9	11	13	14
28	0.447	0.449	0.450	0.452	0.453	0.455	0.456	0.458	0.459	0.461	2	3	5	6	8	9	11	12	14
29	0.462	0.464	0.465	0.467	0.468	0.470	0.471	0.473	0.474	0.476		3	4	6		9	10	12	13
30	0.477	0.479	0.480	0.481	0.483	0.484	0.486	0.487	0.489	0.490		3	4	6		9	10	11	13
31	0.491	0.493	0.494	0.496	0.497	0.498	0.500	0.501	0.502	0.504		3		6		8		11	12
32	0.505	0.507	0.506	0.509	0.511	0.512	0.513	0.515	0.510	0.517		2		5		0	9	10	12
34	0.519	0.520	0.521	0.522	0.524	0.520	0.520	0.520	0.529	0.530		2		5	6	0	9	10	12
35	0.531	0.535	0.534	0.535	0.537	0.550	0.555	0.540	0.542	0.545		2		5	6		9	10	11
36	0.556	0.545	0.547	0.540	0.543	0.550	0.563	0.555	0.554	0.555		2	3	5	6		8	10	11
37	0.568	0.569	0.571	0.572	0.573	0.574	0.575	0.576	0.577	0.579		2	3	5	6	7	8	9	10
38	0.580	0.581	0.582	0.583	0.584	0.585	0.587	0.588	0.589	0.590		2	3	5	6	7	8	9	10
39	0.591	0.592	0.593	0.594	0.595	0.597	0.598	0.599	0.600	0.601	1	2	3	4	5	7	8	9	10
40	0.602	0.603	0.604	0.605	0.606	0.607	0.609	0.610	0.611	0.612	1	2	3	4	5	6	8	9	10
41	0.613	0.614	0.615	0.616	0.617	0.618	0.619	0.620	0.621	0.622	1	2	3	4	5	6	7	8	9
42	0.623	0.624	0.625	0.626	0.627	0.628	0.629	0.630	0.631	0.632	1	2	3	4	5	6	7	8	9
43	0.633	0.634	0.635	0.636	0.637	0.638	0.639	0.640	0.641	0.642	1	2	3	4	5	6	7	8	9
44	0.643	0.644	0.645	0.646	0.647	0.648	0.649	0.650	0.651	0.652	1	2	3	4	5	6	7	8	9
45	0.653	0.654	0.655	0.656	0.657	0.658	0.659	0.660	0.661	0.662	1	2	3	4	5	6	7	8	9
46	0.663	0.664	0.665	0.666	0.667	0.667	0.668	0.669	0.670	0.671	1	2	3	4	5	6	7	7	8
47	0.672	0.673	0.674	0.675	0.676	0.677	0.678	0.679	0.679	0.680	1	2	3	4	5	5	6	7	8
48	0.681	0.682	0.683	0.684	0.685	0.686	0.687	0.688	0.688	0.689	1	2	3	4	4	5	6	7	8
49	0.690	0.691	0.692	0.693	0.694	0.695	0.695	0.696	0.697	0.698	1	2	3	4	4	5	6	7	8
50	0.699	0.700	0.701	0.702	0.702	0.703	0.704	0.705	0.706	0.707	1	2	3	4	4	5	6	7	8
51	0.708	0.708	0.709	0.710	0.711	0.712	0.713	0.713	0.714	0.715	1	2	3	4	4	5	6	7	8
52	0.716	0.717	0.718	0.719	0.719	0.720	0.721	0.722	0.723	0.723	1	2	2	4	4	5	6	7	7
53	0.724	0.725	0.726	0.727	0.728	0.728	0.729	0.730	0.731	0.732	1	2	2	4	4	5	6	6	7
54	0.732	0.733	0.734	0.735	0.736	0.736	0.737	0.738	0.739	0.740	1	2	2	4	4	5	6	6	7

LOGARITHM TABLE

													Me	ean	Diffe	eren	ce		
55	0.740	0.741	0.742	0.743	0.744	0.744	0.745	0.746	0.747	0.747	1	2	2	4	4	5	5	6	7
56	0.748	0.749	0.750	0.751	0.751	0.752	0.753	0.754	0.754	0.755	1	2	2	4	4	5	5	6	7
57	0.756	0.757	0.757	0.758	0.759	0.760	0.760	0.761	0.762	0.763	1	2	2	4	4	5	5	6	7
58	0.763	0.764	0.765	0.766	0.766	0.767	0.768	0.769	0.769	0.770	1	1	2	4	4	4	5	6	7
59	0.771	0.772	0.772	0.773	0.774	0.775	0.775	0.776	0.777	0.777	1	1	2	3	4	4	5	6	7
60	0.778	0.779	0.780	0.780	0.781	0.782	0.782	0.783	0.784	0.785	1	1	2	3	4	4	5	6	6
61	0.785	0.786	0.787	0.787	0.788	0.789	0.790	0.790	0.791	0.792	1	1	2	3	4	4	5	6	6
62	0.792	0.793	0.794	0.794	0.795	0.796	0.797	0.797	0.798	0.799	1	1	2	3	3	4	5	6	6
63	0.799	0.800	0.801	0.801	0.802	0.803	0.803	0.804	0.805	0.806	1	1	2	3	3	4	5	5	6
64	0.806	0.807	0.808	0.808	0.809	0.810	0.810	0.811	0.812	0.812	1	1	2	3	3	4	5	5	6
65	0.813	0.814	0.814	0.815	0.816	0.816	0.817	0.818	0.818	0.819	1		2	3	3	4	5	5	6
66	0.820	0.820	0.821	0.822	0.822	0.823	0.823	0.824	0.825	0.825	1	1	2	3	3	4	5	5	6
67	0.826	0.827	0.827	0.828	0.829	0.829	0.830	0.831	0.831	0.832	1	1	2	3	3	4	5	5	6
68	0.833	0.833	0.834	0.834	0.835	0.836	0.836	0.837	0.838	0.838	1	1	2	3	3	4	4	5	6
69	0.839	0.839	0.840	0.841	0.841	0.842	0.843	0.843	0.844	0.844	1	1	2	2	3	4	4	5	6
70	0.845	0.846	0.846	0.847	0.848	0.848	0.849	0.849	0.850	0.851			2	2	3	4	4	5	6
71	0.851	0.852	0.852	0.853	0.854	0.854	0.855	0.856	0.856	0.857	1		2	2	3	4	4	5	5
72	0.857	0.858	0.859	0.859	0.860	0.860	0.861	0.862	0.862	0.863	1	1	2	2	3	4	4	5	5
73	0.863	0.864	0.865	0.865	0.866	0.866	0.867	0.867	0.868	0.869	1		2	2	3		4	5	5
74	0.869	0.870	0.870	0.871	0.872	0.872	0.873	0.873	0.874	0.874	1		2	2	3		4	5	5
75	0.875	0.876	0.876	0.877	0.877	0.878	0.870	0.070	0.880	0.880			2	2	3	⁻	1	5	5
76	0.881	0.881	0.882	0.883	0.883	0.884	0.884	0.885	0.885	0.886			2	2	3	2		5	5
77	0.886	0.887	0.002	0.000	0.000	0.004	0.004	0.000	0.000	0.000			2	2	3	3	7	1	5
78	0.000	0.007	0.000	0.000	0.003	0.005	0.030	0.000	0.031	0.032			2	2	3	3	7		5
70	0.032	0.000	0.000	0.004	0.004	0.000	0.000	0.030	0.007	0.007			2	2	3	3	7		5
80	0.000	0.000	0.000	0.905	0.905	0.906	0.906	0.907	0.907	0.908	1		2	2	3	3	4	4	5
81	0.908	0.001	0.910	0.910	0.000	0.000	0.912	0.912	0.913	0.913			2	2	3	3	4	4	5
82	0.914	0.914	0.915	0.915	0.916	0.916	0.917	0.918	0.918	0.919	1	1	2	2	3	3	4	4	5
83	0.919	0.920	0.920	0.921	0.921	0.922	0.922	0.923	0.923	0.924	1	1	2	2	3	3	4	4	5
84	0.924	0.925	0.925	0.926	0.926	0.927	0.927	0.928	0.928	0.929	1	1	2	2	3	3	4	4	5
85	0.929	0.930	0.930	0.931	0.931	0.932	0.932	0.933	0.933	0.934	1		2	2	3	3	4	4	5
86	0.934	0.935	0.936	0.936	0.937	0.937	0.938	0.938	0.939	0.939	1		2	2	3	3	4	4	5
87	0.940	0.940	0.000	0.000	0.942	0.942	0.943	0.943	0.943	0.000	0		1	2	2	3	3	4	5
88	0.944	0.945	0.945	0.946	0.946	0.947	0.947	0.948	0.948	0.949	0			2	2	3	3	4	4
89	0.949	0.950	0.950	0.951	0.951	0.952	0.952	0.953	0.953	0.954	0	1		2	2	3	3	4	4
90	0.954	0.955	0.955	0.956	0.956	0.957	0.957	0.958	0.958	0.959	0			2	2	3	3	4	4
91	0.959	0.960	0.960	0.960	0.961	0.961	0.962	0.962	0.963	0.963	0			2	2	3	3	4	4
92	0.000	0.000	0.000	0.000	0.966	0.966	0.002	0.002	0.000	0.000				2	2	3	3	4	4
93	0.968	0.969	0.969	0.970	0.970	0.971	0 971	0.972	0.972	0.973	0			2	2	3	3	4	4
94	0.973	0.974	0.974	0.975	0.975	0.975	0.976	0.976	0.977	0.977	0			2	2	3	3	4	4
95	0.978	0.978	0.979	0.979	0.980	0.980	0.980	0.981	0.981	0.982	0			2	2	3	3	4	4
96	0.982	0.983	0.983	0.984	0.984	0.985	0.985	0.985	0.986	0.986	0			2	2	3	3	4	4
97	0.987	0.987	0.988	0.988	0 989	0.989	0 989	0.990	0 990	0.901	0			2	2	3	3	4	4
98	0.991	0.992	0.992	0.993	0.993	0.993	0.994	0.994	0.995	0.995	0			2	2	3	3	4	4
99	0.996	0.996	0.997	0.997	0.997	0.998	0.998	0.999	0.999	1.000	0	1	1	2	2	3	3	3	4

ANTILOG TABLE

												Mean Differe							
	0	1	2	3	4	5	6	7	8	9	1	2	3	4	5	6	7	8	9
0.00	1.000	1.002	1.005	1.007	1.009	1.012	1.014	1.016	1.019	1.021	0	0	1	1	1	1	2	2	2
0.01	1.023	1.026	1.028	1.030	1.033	1.035	1.038	1.040	1.042	1.045	0	0	1	1	1	1	2	2	2
0.02	1.047	1.050	1.052	1.054	1.057	1.059	1.062	1.064	1.067	1.069	0	0	1	1	1	1	2	2	2
0.03	1.072	1.074	1.076	1.079	1.081	1.084	1.086	1.089	1.091	1.094	0	0	1	1	1	1	2	2	2
0.04	1.096	1.099	1.102	1.104	1.107	1.109	1.112	1.114	1.117	1.119	0	1	1	1	1	2	2	2	2
0.05	1.122	1.125	1.127	1.130	1.132	1.135	1.138	1.140	1.143	1.146	0	1	1	1	1	2	2	2	2
0.06	1.148	1.151	1.153	1.156	1.159	1.161	1.164	1.167	1.169	1.172	0	1	1	1	1	2	2	2	2
0.07	1.175	1.178	1.180	1.183	1.186	1.189	1.191	1.194	1.197	1.199	0	1	1	1	1	2	2	2	2
0.08	1.202	1.205	1.208	1.211	1.213	1.216	1.219	1.222	1.225	1.227	0	1	1	1	1	2	2	2	3
0.09	1.230	1.233	1.236	1.239	1.242	1.245	1.247	1.250	1.253	1.256	0	1	1	1	1	2	2	2	3
0.10	1.259	1.262	1.265	1.268	1.271	1.274	1.276	1.279	1.282	1.285	0	1	1	1	1	2	2	2	3
0.11	1.288	1.291	1.294	1.297	1.300	1.303	1.306	1.309	1.312	1.315	0	1	1	1	2	2	2	2	3
0.12	1.318	1.321	1.324	1.327	1.330	1 334	1.337	1.340	1 343	1.346	0	1	1	1	2	2	2	2	3
0.12	1.349	1.352	1 355	1.358	1.361	1.365	1.368	1.371	1.374	1.377	0			1	2	2	2	3	3
0.10	1 380	1 384	1 387	1 390	1 393	1 396	1 400	1 403	1 406	1 409	0	1	1	1	2	2	2	3	3
0.14	1 413	1 416	1 419	1 422	1.000	1 429	1 432	1 435	1 430	1 442	0				2	2	2	3	3
0.15	1 445	1 449	1 452	1.422	1.420	1.423	1.452	1.455	1 472	1.442	0				2	2	2	с С	с С
0.10	1 /70	1 /83	1 / 86	1 / 80	1 /03	1 /06	1.400	1.403	1.507	1.470	0				2	2	2	3	3
0.17	1.473	1.403	1.400	1.403	1.433	1.430	1.500	1.505	1.507	1.510	0				2	2	2	3	2
0.10	1.514	1.517	1.521	1.524	1.520	1.551	1.555	1.550	1.542	1.545	0				2	2	2	3	с С
0.19	1.549	1.552	1.550	1.500	1.505	1.507	1.570	1.574	1.570	1.501	0				2	2	2	с С	2
0.20	1.505	1.009	1.592	1.590	1.000	1.005	1.007	1.011	1.014	1.010	0				2	2	3 2	о 2	ა ი
0.21	1.622	1.020	1.629	1.033	1.037	1.041	1.044	1.040	1.002	1.000	0			2	2	2	3	ა ი	ა ი
0.22	1.000	1.005	1.007	1.071	1.075	1.079	1.005	1.007	1.090	1.094	0						3	о 0	3
0.23	1.090	1.702	1.700	1.710	1.714	1.710	1.722	1.720	1.730	1.734	0						3	ა ი	4
0.24	1.738	1.742	1.746	1.750	1.754	1.758	1.762	1.766	1.770	1.774	0						3	3	4
0.25	1.770	1.702	1.700	1.791	1.795	1.799	1.603	1.007	1.011	1.010								3	4
0.26	1.820	1.824	1.828	1.832	1.837	1.841	1.845	1.849	1.854	1.858	0			2	2	3	3	3	4
0.27	1.862	1.866	1.871	1.875	1.879	1.884	1.888	1.892	1.897	1.901	0			2	2	3	3	3	4
0.28	1.905	1.910	1.914	1.919	1.923	1.928	1.932	1.936	1.941	1.945	0			2	2	3	3	4	4
0.29	1.950	1.954	1.959	1.963	1.968	1.972	1.977	1.982	1.986	1.991	0			2	2	3	3	4	4
0.30	1.995	2.000	2.004	2.009	2.014	2.018	2.023	2.028	2.032	2.037	0			2	2	3	3	4	4
0.31	2.042	2.046	2.051	2.056	2.061	2.065	2.070	2.075	2.080	2.084	0	1	1	2	2	3	3	4	4
0.32	2.089	2.094	2.099	2.104	2.109	2.113	2.118	2.123	2.128	2.133	0			2	2	3	3	4	4
0.33	2.138	2.143	2.148	2.153	2.158	2.163	2.168	2.173	2.178	2.183	0		1	2	2	3	3	4	4
0.34	2.188	2.193	2.198	2.203	2.208	2.213	2.218	2.223	2.228	2.234	1		2	2	3	3	4	4	5
0.35	2.239	2.244	2.249	2.254	2.259	2.265	2.270	2.275	2.280	2.286	1	1	2	2	3	3	4	4	5
0.36	2.291	2.296	2.301	2.307	2.312	2.317	2.323	2.328	2.333	2.339	1	1	2	2	3	3	4	4	5
0.37	2.344	2.350	2.355	2.360	2.366	2.371	2.377	2.382	2.388	2.393	1	1	2	2	3	3	4	4	5
0.38	2.399	2.404	2.410	2.415	2.421	2.427	2.432	2.438	2.443	2.449	1	1	2	2	3	3	4	4	5
0.39	2.455	2.460	2.466	2.472	2.477	2.483	2.489	2.495	2.500	2.506	1	1	2	2	3	3	4	5	5
0.40	2.512	2.518	2.523	2.529	2.535	2.541	2.547	2.553	2.559	2.564	1	1	2	2	3	4	4	5	5
0.41	2.570	2.576	2.582	2.588	2.594	2.600	2.606	2.612	2.618	2.624	1	1	2	2	3	4	4	5	5
0.42	2.630	2.636	2.642	2.649	2.655	2.661	2.667	2.673	2.679	2.685	1	1	2	2	3	4	4	5	6
0.43	2.692	2.698	2.704	2.710	2.716	2.723	2.729	2.735	2.742	2.748	1	1	2	3	3	4	4	5	6
0.44	2.754	2.761	2.767	2.773	2.780	2.786	2.793	2.799	2.805	2.812	1	1	2	3	3	4	4	5	6
0.45	2.818	2.825	2.831	2.838	2.844	2.851	2.858	2.864	2.871	2.877	1	1	2	3	3	4	5	5	6
0.46	2.884	2.891	2.897	2.904	2.911	2.917	2.924	2.931	2.938	2.944	1	1	2	3	3	4	5	5	6
0.47	2.951	2.958	2.965	2.972	2.979	2.985	2.992	2.999	3.006	3.013	1	1	2	3	3	4	5	5	6
0.48	3.020	3.027	3.034	3.041	3.048	3.055	3.062	3.069	3.076	3.083	1	1	2	3	4	4	5	6	6
0.49	3.090	3.097	3.105	3.112	3.119	3.126	3.133	3.141	3.148	3.155	1	1	2	3	4	4	5	6	6

ANTILOG TABLE

													Me	ean	Diffe	eren	ice		
0.50	3.162	3.170	3.177	3.184	3.192	3.199	3.206	3.214	3.221	3.228	1	1	2	3	4	4	5	6	7
0.51	3.236	3.243	3.251	3.258	3.266	3.273	3.281	3.289	3.296	3.304	1	2	2	3	4	5	5	6	7
0.52	3.311	3.319	3.327	3.334	3.342	3.350	3.357	3.365	3.373	3.381	1	2	2	3	4	5	5	6	7
0.53	3.388	3.396	3.404	3.412	3.420	3.428	3.436	3.443	3.451	3.459	1	2	2	3	4	5	6	6	7
0.54	3.467	3.475	3.483	3.491	3.499	3.508	3.516	3.524	3.532	3.540	1	2	2	3	4	5	6	6	7
0.55	3.548	3.556	3.565	3.573	3.581	3.589	3.597	3.606	3.614	3.622	1	2	2	3	4	5	6	7	7
0.56	3.631	3.639	3.648	3.656	3.664	3.673	3.681	3.690	3.698	3.707	1	2	2	3	4	5	6	7	8
0.57	3.715	3.724	3.733	3.741	3.750	3.758	3.767	3.776	3.784	3.793	1	2	3	3	4	5	6	7	8
0.58	3.802	3.811	3.819	3.828	3.837	3.846	3.855	3.864	3.873	3.882	1	2	3	4	4	5	6	7	8
0.59	3.890	3,899	3.908	3.917	3.926	3.936	3.945	3.954	3.963	3.972		2	3	4	5	5	6	7	8
0.60	3.981	3.990	3,999	4.009	4.018	4.027	4.036	4.046	4.055	4.064	1	2	3	4	5	6	6	7	8
0.61	4 074	4 083	4 093	4 102	4 111	4 121	4 130	4 140	4 150	4 159	1	2	3	4	5	6	7	8	9
0.62	4 169	4 178	4 188	4 198	4 207	4 217	4 227	4 236	4 246	4 256		2	3	4	5	6	7	8	9
0.63	4 266	4 276	4 285	4 295	4 305	4 315	4 325	4 335	4 345	4 355	1	2	3	4	5	6	7	8	9
0.64	4 365	4 375	4 385	4 395	4 4 0 6	4 4 1 6	4 4 2 6	4 4 3 6	4 4 4 6	4 457		2	3	4	5	6	7	8	q
0.65	4 467	4.070	4 487	4.000	4 508	4 519	4 529	4 539	4 550	4 560		2	3		5	6	7	8	g
0.66	4 571	4 581	4 592	4 603	4 613	4 624	4.634	4.645	4 656	4.667		2	3		5	6	7	a	10
0.00	4.677	4.688	1 600	4 710	4 721	4 732	4 742	4 753	4.000	4.007		2	3		5	7	7	a	10
0.07	4.077	4.000	4.808	4.710	4.721	4.752	4.742	4.755	4.704	4.775		2	3		5	7	8	a	10
0.00	4.808	4 909	4 920	4.032	4.001	4 955	4 966	4 977	4.075	5.000		2	3		5	7	8	a	10
0.00	5.012	5.023	5.035	5.047	5 058	5.070	5.082	5.003	5 105	5 117		2	3		5	7	8	a	11
0.70	5 129	5 140	5 152	5 164	5 176	5 188	5 200	5 212	5 224	5 236		2	1	5	6	7	8	10	11
0.71	5 248	5 260	5 272	5 284	5 207	5 300	5 321	5 333	5 3/6	5 358		2		5	6	7	0	10	11
0.72	5 270	5 292	5.212	5.204	5.297	5.309	5.521	5.555	5.340	5 492		2	4	5	6	0	9	10	11
0.73	5.370	5.505	5.595	5.400	5.420	5.455	5.445	5.450	5.470	5.405		2	4	5	6	0	9	10	12
0.74	5.495	5.500	5.521	5.554	5.540	5.559	5.572	5.305	5.580	5.010		2	4	5	7	0	9	10	12
0.75	5.025	5.050	5.049	5.002	5.075	5.009	5.702	5.715	5.720	5.741		2	4	5	7	0	9	10	12
0.70	5 999	5.002	5.701	5.794	5.000	5.021	5.034	5 094	5.001	6.012		2	4	5	7	0	10	11	12
0.77	6.026	6.020	6.052	6.067	6.091	6.005	6 100	6 1 2 4	6 1 2 9	6 152		2		6	7	0	10	11	12
0.70	6 166	6 1 9 0	6 104	6 200	6 222	6.227	6 252	6 266	6 291	6 205		2		6	7	0	10	11	12
0.79	6 310	6 324	6 3 3 0	6 353	6 368	6 383	6 307	6 412	6 / 27	6.442		3	4	6	7	9	10	12	13
0.00	6.457	6 471	6.486	6 501	6.516	6 531	6.546	6 561	6 577	6 5 9 2		3	5	6	2 2	9	11	12	11
0.01	6 607	6 622	6 637	6 653	6 668	6 683	6 600	6 714	6 730	6 745	2	3	5	6	8	9	11	12	14
0.02	6 761	6 776	6 792	6 808	6.823	6.830	6 855	6 871	6 887	6 902	2	3	5	6	8	a	11	12	14
0.00	6 918	6 934	6 950	6 966	6 982	6 998	7 015	7 031	7 047	7.063	2	3	5	6	8	10	11	13	15
0.85	7 070	7.006	7 112	7 1 2 0	7 1 4 5	7 161	7 178	7 10/	7 211	7 228	2	3	5		8	10	12	13	15
0.00	7 244	7 261	7 278	7 295	7 311	7 328	7 345	7 362	7 370	7 396	2	3	5	7	8	10	12	13	15
0.87	7 413	7.430	7 447	7.464	7 482	7 499	7 516	7 534	7 551	7 568	2	3	5	7	a	10	12	14	16
0.88	7 586	7.603	7 621	7.638	7.656	7.674	7.601	7 709	7 727	7 745	2	3	5	7	a	10	12	14	16
0.89	7 762	7 780	7 798	7.816	7 834	7 852	7.870	7 889	7 907	7 925	2	4	5	7	g	11	12	14	16
0.00	7 943	7 962	7 980	7 998	8 017	8.035	8 054	8.072	8 001	8 110	2		6	7	a	11	13	15	17
0.00	8 128	8 147	8 166	8 185	8 204	8 222	8 241	8 260	8 270	8 200	2	4	6	8	9	11	13	15	17
0.97	8 318	8 337	8 356	8 375	8 305	8 414	8 433	8 453	8 472	8 402	2	4	6	8	10	12	14	15	17
0.02	8 511	8 531	8 551	8 570	8 500	8 610	8 630	8 650	8 670	8 690	2	4	6	8	10	12	14	16	18
0.94	8 710	8 730	8 750	8 770	8 700	8 810	8 831	8 851	8 872	8 802	2	4	6	8	10	12	14	16	18
0.95	8.913	8,933	8 954	8 974	8,995	9.016	9.036	9.057	9.078	9,099	2	4	6	8	10	12	15	17	19
0.96	9 120	9 1 4 1	9 162	9 183	9 204	9 226	9 247	9 268	9 290	9,311	2	4	6	8	11	13	15	17	19
0.00	9,333	9,354	9,376	9,397	9 4 1 9	9 4 4 1	9 462	9 4 8 4	9,506	9.528	2	4	7	g	11	13	15	17	20
0.98	9,550	9.572	9.594	9.616	9,638	9.661	9,683	9.705	9,727	9.750	2	4	7	9	11	13	16	18	20
0.99	9.772	9.795	9.817	9.840	9.863	9.886	9.908	9.931	9.954	9.977	2	5	7	9	11	14	16	18	20

NATURAL SINES

x	0	1	2	3	4	5	6	7	8	9
0	0	0.0017453	0.0034907	0.0052360	0.0069813	0.0087265	0.010472	0.012217	0.013962	0.015707
1	0.017452	0.019197	0.020942	0.022687	0.024432	0.026177	0.027922	0.029666	0.031411	0.033155
2	0.034899	0.036644	0.038388	0.040132	0.041876	0.043619	0.045363	0.047106	0.04885	0.050593
3	0.052336	0.054079	0.055822	0.057564	0.059306	0.061049	0.062791	0.064532	0.066274	0.068015
4	0.069756	0.071497	0.073238	0.074979	0.076719	0.078459	0.080199	0.081939	0.083678	0.085417
5	0.087156	0.088894	0.090633	0.092371	0.094108	0.095846	0.097583	0.09932	0.101056	0.102793
6	0.104528	0.106264	0.107999	0.109734	0.111469	0.113203	0.114937	0.116671	0.118404	0.120137
7	0.121869	0.123601	0.125333	0.127065	0.128796	0.130526	0.132256	0.133986	0.135716	0.137445
8	0.139173	0.140901	0.142629	0.144356	0.146083	0.147809	0.149535	0.151261	0.152986	0.15471
9	0.156434	0.158158	0.159881	0.161604	0.163326	0.165048	0.166769	0.168489	0.170209	0.171929
x	0	1	2	3	4	5	6	7	8	9
10	0.173648	0.175367	0.177085	0.178802	0.180519	0.182236	0.183951	0.185667	0.187381	0.189095
11	0.190809	0.192522	0.194234	0.195946	0.197657	0.199368	0.201078	0.202787	0.204496	0.206204
12	0.207912	0.209619	0.211325	0.21303	0.214735	0.21644	0.218143	0.219846	0.221548	0.22325
13	0.224951	0.226651	0.228351	0.23005	0.231748	0.233445	0.235142	0.236838	0.238533	0.240228
14	0.241922	0.243615	0.245307	0.246999	0.24869	0.25038	0.252069	0.253758	0.255446	0.257133
15	0.258819	0.260505	0.262189	0.263873	0.265556	0.267238	0.26892	0.2706	0.27228	0.273959
16	0.275637	0.277315	0.278991	0.280667	0.282341	0.284015	0.285688	0.287361	0.289032	0.290702
17	0.292372	0.29404	0.295708	0.297375	0.299041	0.300706	0.30237	0.304033	0.305695	0.307357
18	0.309017	0.310676	0.312335	0.313992	0.315649	0.317305	0.318959	0.320613	0.322266	0.323917
19	0.325568	0.327218	0.328867	0.330514	0.332161	0.333807	0.335452	0.337095	0.338738	0.34038
X	0	1	2	3	4	5	6	7	8	9
20	0.34202	0.34366	0.345298	0.346936	0.348572	0.350207	0.351842	0.3534/5	0.355107	0.356/38
21	0.358368	0.359997	0.361625	0.363251	0.364877	0.366501	0.368125	0.369747	0.3/1368	0.372988
22	0.374607	0.376224	0.377841	0.379456	0.38107	0.382683	0.384295	0.385906	0.387516	0.389124
23	0.390731	0.392337	0.393942	0.395540	0.397146	0.398749	0.400349	0.401946	0.403545	0.405142
24	0.400737	0.40000	0.409923	0.411314	0.413104	0.414095	0.410201	0.417007	0.419432	0.421030
26	0.422010	0.424199	0.441506	0.427550	0.444635	0.436311	0.432000	0.435055	0.450878	0.452435
20	0.45399	0.455545	0 457098	0.45865	0.4602	0.461749	0.463296	0.464842	0.466387	0.46793
28	0.469472	0.471012	0.472551	0.474088	0.475624	0.477159	0.478692	0.480223	0.481754	0.483282
29	0.48481	0.486335	0.48786	0.489382	0.490904	0.492424	0.493942	0.495459	0.496974	0.498488
x	0	1	2	3	4	5	6	7	8	9
30	0.5	0.501511	0.50302	0.504528	0.506034	0.507538	0.509041	0.510543	0.512043	0.513541
31	0.515038	0.516533	0.518027	0.519519	0.52101	0.522499	0.523986	0.525472	0.526956	0.528438
32	0.529919	0.531399	0.532876	0.534352	0.535827	0.5373	0.538771	0.54024	0.541708	0.543174
33	0.544639	0.546102	0.547563	0.549023	0.550481	0.551937	0.553392	0.554844	0.556296	0.557745
34	0.559193	0.560639	0.562083	0.563526	0.564967	0.566406	0.567844	0.56928	0.570714	0.572146
35	0.573576	0.575005	0.576432	0.577858	0.579281	0.580703	0.582123	0.583541	0.584958	0.586372
36	0.587785	0.589196	0.590606	0.592013	0.593419	0.594823	0.596225	0.597625	0.599024	0.60042
37	0.601815	0.603208	0.604599	0.605988	0.607376	0.608761	0.610145	0.611527	0.612907	0.614285
38	0.615661	0.617036	0.618408	0.619779	0.621148	0.622515	0.62388	0.625243	0.626604	0.627963
39	0.62932	0.630676	0.632029	0.633381	0.634731	0.636078	0.637424	0.638768	0.64011	0.64145
x	0	1	2	3	4	5	6	7	8	9
40	0.642788	0.644124	0.645458	0.64679	0.64812	0.649448	0.650774	0.652098	0.653421	0.654741
41	0.656059	0.657375	0.658689	0.660002	0.661312	0.66262	0.663926	0.66523	0.666532	0.667833
42	0.669131	0.670427	0.671721	0.673013	0.674302	0.67559	0.676876	0.67816	0.679441	0.680721
43	0.681998	0.683274	0.684547	0.685818	0.687088	0.688355	0.68962	0.690882	0.692143	0.693402
44	0.694658	0.695913	0.697165	0.698415	0.699663	0.700909	0.702153	0.703395	0.704634	0.705872
45	0.707107	0.70834	0.709571	0.710799	0.712026	0.71325	0.714473	0.715693	0.716911	0.718126

NATURAL SINES

46	0.71934	0.720551	0.72176	0.722967	0.724172	0.725374	0.726575	0.727773	0.728969	0.730162
47	0.731354	0.732543	0.73373	0.734915	0.736097	0.737277	0.738455	0.739631	0.740805	0.741976
48	0.743145	0.744312	0.745476	0.746638	0.747798	0.748956	0.750111	0.751264	0.752415	0.753563
49	0.75471	0.755853	0.756995	0.758134	0.759271	0.760406	0.761538	0.762668	0.763796	0.764921
x	0	1	2	3	4	5	6	7	8	9
50	0.766044	0.767165	0.768284	0.7694	0.770513	0.771625	0.772734	0.77384	0.774944	0.776046
51	0.777146	0.778243	0.779338	0.78043	0.78152	0.782608	0.783693	0.784776	0.785857	0.786935
52	0.788011	0.789084	0.790155	0.791224	0.79229	0.793353	0.794415	0.795473	0.79653	0.797584
53	0.798636	0.799685	0.800731	0.801776	0.802817	0.803857	0.804894	0.805928	0.80696	0.80799
54	0.809017	0.810042	0.811064	0.812084	0.813101	0.814116	0.815128	0.816138	0.817145	0.81815
55	0.819152	0.820152	0.821149	0.822144	0.823136	0.824126	0.825113	0.826098	0.827081	0.82806
56	0.829038	0.830012	0.830984	0.831954	0.832921	0.833886	0.834848	0.835807	0.836764	0.837719
57	0.838671	0.83962	0.840567	0.841511	0.842452	0.843391	0.844328	0.845262	0.846193	0.847122
58	0.848048	0.848972	0.849893	0.850811	0.851727	0.85264	0.853551	0.854459	0.855364	0.856267
59	0.857167	0.858065	0.85896	0.859852	0.860742	0.861629	0.862514	0.863396	0.864275	0.865151
х	0	1	2	3	4	5	6	7	8	9
60	0.866025	0.866897	0.867765	0.868632	0.869495	0.870356	0.871214	0.872069	0.872922	0.873772
61	0.87462	0.875465	0.876307	0.877146	0.877983	0.878817	0.879649	0.880477	0.881303	0.882127
62	0.882948	0.883766	0.884581	0.885394	0.886204	0.887011	0.887815	0.888617	0.889416	0.890213
63	0.891007	0.891798	0.892586	0.893371	0.894154	0.894934	0.895712	0.896486	0.897258	0.898028
64	0.898794	0.899558	0.900319	0.901077	0.901833	0.902585	0.903335	0.904083	0.904827	0.905569
65	0.906308	0.907044	0.907777	0.908508	0.909236	0.909961	0.910684	0.911403	0.91212	0.912834
66	0.913545	0.914254	0.91496	0.915663	0.916363	0.91706	0.917755	0.918446	0.919135	0.919821
67	0.920505	0.921185	0.921863	0.922538	0.92321	0.92388	0.924546	0.92521	0.925871	0.926529
68	0.927184	0.927836	0.928486	0.929133	0.929776	0.930418	0.931056	0.931691	0.932324	0.932954
69	0.93358	0.934204	0.934826	0.935444	0.93606	0.936672	0.937282	0.937889	0.938493	0.939094
х	0	1	2	3	4	5	6	7	8	9
70	0.939693	0.940288	0.940881	0.941471	0.942057	0.942641	0.943223	0.943801	0.944376	0.944949
71	0.945519	0.946085	0.946649	0.94721	0.947768	0.948324	0.948876	0.949425	0.949972	0.950516
72	0.951057	0.951594	0.952129	0.952661	0.953191	0.953717	0.95424	0.954761	0.955278	0.955793
73	0.956305	0.956814	0.957319	0.957822	0.958323	0.95882	0.959314	0.959805	0.960294	0.960779
74	0.961262	0.961741	0.962218	0.962692	0.963163	0.96363	0.964095	0.964557	0.965016	0.965473
75	0.965926	0.966376	0.966823	0.967268	0.967709	0.968148	0.968583	0.969016	0.969445	0.969872
76	0.970296	0.970716	0.971134	0.971549	0.971961	0.97237	0.972776	0.973179	0.973579	0.973976
77	0.97437	0.974761	0.975149	0.975535	0.975917	0.976296	0.976672	0.977046	0.977416	0.977783
78	0.978148	0.978509	0.978867	0.979223	0.979575	0.979925	0.980271	0.980615	0.980955	0.981293
79	0.981627	0.981959	0.982287	0.982613	0.982935	0.983255	0.983571	0.983885	0.984196	0.984503
x	0	1	2	3	4	5	6	7	8	9
80	0.984808	0.985109	0.985408	0.985703	0.985996	0.986286	0.986572	0.986856	0.987136	0.987414
81	0.987688	0.98796	0.988228	0.988494	0.988756	0.989016	0.989272	0.989526	0.989776	0.990024
82	0.990268	0.990509	0.990748	0.990983	0.991216	0.991445	0.991671	0.991894	0.992115	0.992332
83	0.992546	0.992757	0.992966	0.993171	0.993373	0.993572	0.993768	0.993961	0.994151	0.994338
84	0.994522	0.994703	0.994881	0.995056	0.995227	0.995396	0.995562	0.995725	0.995884	0.996041
85	0.996195	0.996345	0.996493	0.996637	0.996779	0.996917	0.997053	0.997185	0.997314	0.997441
86	0.997564	0.997684	0.997801	0.997916	0.998027	0.998135	0.99824	0.998342	0.998441	0.998537
87	0.99863	0.998719	0.998806	0.99889	0.998971	0.999048	0.999123	0.999194	0.999263	0.999328
88	0.999391	0.99945	0.999507	0.99956	0.99961	0.999657	0.999701	0.999743	0.999781	0.999816
89	0.999848	0.999877	0.999903	0.999925	0.999945	0.999962	0.999976	0.999986	0.999994	0.999998
90	1	0.999998	0.999994	0.999986	0.999976	0.999962	0.999945	0.999925	0.999903	0.999877

NATURAL COSINES

۲

x	0	1	2	3	4	5	6	7	8	9
0	1	0.999998	0.999994	0.999986	0.999976	0.999962	0.999945	0.999925	0.999903	0.999877
1	0.999848	0.999816	0.999781	0.999743	0.999701	0.999657	0.99961	0.99956	0.999507	0.99945
2	0.999391	0.999328	0.999263	0.999194	0.999123	0.999048	0.998971	0.99889	0.998806	0.998719
3	0.99863	0.998537	0.998441	0.998342	0.99824	0.998135	0.998027	0.997916	0.997801	0.997684
4	0.997564	0.997441	0.997314	0.997185	0.997053	0.996917	0.996779	0.996637	0.996493	0.996345
5	0.996195	0.996041	0.995884	0.995725	0.995562	0.995396	0.995227	0.995056	0.994881	0.994703
6	0.994522	0.994338	0.994151	0.993961	0.993768	0.993572	0.993373	0.993171	0.992966	0.992757
7	0.992546	0.992332	0.992115	0.991894	0.991671	0.991445	0.991216	0.990983	0.990748	0.990509
8	0.990268	0.990024	0.989776	0.989526	0.989272	0.989016	0.988756	0.988494	0.988228	0.98796
9	0.987688	0.987414	0.987136	0.986856	0.986572	0.986286	0.985996	0.985703	0.985408	0.985109
x	0	1	2	3	4	5	6	7	8	9
10	0.984808	0.984503	0.984196	0.983885	0.983571	0.983255	0.982935	0.982613	0.982287	0.981959
11	0.981627	0.981293	0.980955	0.980615	0.980271	0.979925	0.979575	0.979223	0.978867	0.978509
12	0.978148	0.977783	0.977416	0.977046	0.976672	0.976296	0.975917	0.975535	0.975149	0.974761
13	0.97437	0.973976	0.973579	0.973179	0.972776	0.97237	0.971961	0.971549	0.971134	0.970716
14	0.970296	0.969872	0.969445	0.969016	0.968583	0.968148	0.967709	0.967268	0.966823	0.966376
15	0.965926	0.965473	0.965016	0.964557	0.964095	0.96363	0.963163	0.962692	0.962218	0.961741
16	0.961262	0.960779	0.960294	0.959805	0.959314	0.95882	0.958323	0.957822	0.957319	0.956814
17	0.956305	0.955793	0.955278	0.954761	0.95424	0.953717	0.953191	0.952661	0.952129	0.951594
18	0.951057	0.950516	0.949972	0.949425	0.948876	0.948324	0.947768	0.94721	0.946649	0.946085
19	0.945519	0.944949	0.944376	0.943801	0.943223	0.942641	0.942057	0.941471	0.940881	0.940288
X	0	1	2	3	4	5	6	/	8	9
20	0.939693	0.939094	0.938493	0.937889	0.937282	0.936672	0.93606	0.935444	0.934826	0.934204
21	0.93358	0.932954	0.932324	0.931691	0.931056	0.930418	0.929776	0.929133	0.928486	0.927836
22	0.927184	0.926529	0.925871	0.92521	0.924546	0.92388	0.92321	0.922538	0.921863	0.921185
23	0.920303	0.919621	0.919133	0.910440	0.917755	0.91700	0.910303	0.913003	0.91490	0.914234
24	0.913343	0.912034	0.91212	0.911403	0.910004	0.909901	0.909230	0.906506	0.907777	0.907044
25	0.900300	0.903309	0.904027	0.904005	0.905555	0.902303	0.901055	0.901077	0.900519	0.891798
27	0.891007	0.890213	0.889416	0.888617	0.887815	0.887011	0.886204	0.885394	0.884581	0.883766
28	0.882948	0.882127	0.881303	0.880477	0.879649	0.878817	0.877983	0.877146	0.876307	0.875465
29	0.87462	0.873772	0.872922	0.872069	0.871214	0.870356	0.869495	0.868632	0.867765	0.866897
x	0	1	2	3	4	5	6	7	8	9
30	0.866025	0.865151	0.864275	0.863396	0.862514	0.861629	0.860742	0.859852	0.85896	0.858065
31	0.857167	0.856267	0.855364	0.854459	0.853551	0.85264	0.851727	0.850811	0.849893	0.848972
32	0.848048	0.847122	0.846193	0.845262	0.844328	0.843391	0.842452	0.841511	0.840567	0.83962
33	0.838671	0.837719	0.836764	0.835807	0.834848	0.833886	0.832921	0.831954	0.830984	0.830012
34	0.829038	0.82806	0.827081	0.826098	0.825113	0.824126	0.823136	0.822144	0.821149	0.820152
35	0.819152	0.81815	0.817145	0.816138	0.815128	0.814116	0.813101	0.812084	0.811064	0.810042
36	0.809017	0.80799	0.80696	0.805928	0.804894	0.803857	0.802817	0.801776	0.800731	0.799685
37	0.798636	0.797584	0.79653	0.795473	0.794415	0.793353	0.79229	0.791224	0.790155	0.789084
38	0.788011	0.786935	0.785857	0.784776	0.783693	0.782608	0.78152	0.78043	0.779338	0.778243
39	0.777146	0.776046	0.774944	0.77384	0.772734	0.771625	0.770513	0.7694	0.768284	0.767165
x	0	1	2	3	4	5	6	7	8	9
40	0.766044	0.764921	0.763796	0.762668	0.761538	0.760406	0.759271	0.758134	0.756995	0.755853
41	0.75471	0.753563	0.752415	0.751264	0.750111	0.748956	0.747798	0.746638	0.745476	0.744312
42	0.743145	0.741976	0.740805	0.739631	0.738455	0.737277	0.736097	0.734915	0.73373	0.732543
43	0.731354	0.730162	0.728969	0.727773	0.726575	0.725374	0.724172	0.722967	0.72176	0.720551
44	0.71934	0.718126	0.716911	0.715693	0.714473	0.71325	0.712026	0.710799	0.709571	0.70834
45	0.707107	0.705872	0.704634	0.703395	0.702153	0.700909	0.699663	0.698415	0.697165	0.695913



۲

۲

NATURAL COSINES

۲

46	0.694658	0.693402	0.692143	0.690882	0.68962	0.688355	0.687088	0.685818	0.684547	0.683274
47	0.681998	0.680721	0.679441	0.67816	0.676876	0.67559	0.674302	0.673013	0.671721	0.670427
48	0.669131	0.667833	0.666532	0.66523	0.663926	0.66262	0.661312	0.660002	0.658689	0.657375
49	0.656059	0.654741	0.653421	0.652098	0.650774	0.649448	0.64812	0.64679	0.645458	0.644124
x	0	1	2	3	4	5	6	7	8	9
50	0.642788	0.64145	0.64011	0.638768	0.637424	0.636078	0.634731	0.633381	0.632029	0.630676
51	0.62932	0.627963	0.626604	0.625243	0.62388	0.622515	0.621148	0.619779	0.618408	0.617036
52	0.615661	0.614285	0.612907	0.611527	0.610145	0.608761	0.607376	0.605988	0.604599	0.603208
53	0.601815	0.60042	0.599024	0.597625	0.596225	0.594823	0.593419	0.592013	0.590606	0.589196
54	0.587785	0.586372	0.584958	0.583541	0.582123	0.580703	0.579281	0.577858	0.576432	0.575005
55	0.573576	0.572146	0.570714	0.56928	0.567844	0.566406	0.564967	0.563526	0.562083	0.560639
56	0.559193	0.557745	0.556296	0.554844	0.553392	0.551937	0.550481	0.549023	0.547563	0.546102
57	0.544639	0.543174	0.541708	0.54024	0.538771	0.5373	0.535827	0.534352	0.532876	0.531399
58	0.529919	0.528438	0.526956	0.525472	0.523986	0.522499	0.52101	0.519519	0.518027	0.516533
59	0.515038	0.513541	0.512043	0.510543	0.509041	0.507538	0.506034	0.504528	0.50302	0.501511
x	0	1	2	3	4	5	6	7	8	9
60	0.5	0.498488	0.496974	0.495459	0.493942	0.492424	0.490904	0.489382	0.48786	0.486335
61	0.48481	0.483282	0.481754	0.480223	0.478692	0.477159	0.475624	0.474088	0.472551	0.471012
62	0.469472	0.46793	0.466387	0.464842	0.463296	0.461749	0.4602	0.45865	0.457098	0.455545
63	0.45399	0.452435	0.450878	0.449319	0.447759	0.446198	0.444635	0.443071	0.441506	0.439939
64	0.438371	0.436802	0.435231	0.433659	0.432086	0.430511	0.428935	0.427358	0.425779	0.424199
65	0.422618	0.421036	0.419452	0.417867	0.416281	0.414693	0.413104	0.411514	0.409923	0.40833
66	0.406737	0.405142	0.403545	0.401948	0.400349	0.398749	0.397148	0.395546	0.393942	0.392337
67	0.390731	0.389124	0.387516	0.385906	0.384295	0.382683	0.38107	0.379456	0.377841	0.376224
68	0.374607	0.372988	0.371368	0.369747	0.368125	0.366501	0.364877	0.363251	0.361625	0.359997
69	0.358368	0.356738	0.355107	0.353475	0.351842	0.350207	0.348572	0.346936	0.345298	0.34366
х	0	1	2	3	4	5	6	7	8	9
70	0.34202	0.34038	0.338738	0.337095	0.335452	0.333807	0.332161	0.330514	0.328867	0.327218
71	0.325568	0.323917	0.322266	0.320613	0.318959	0.317305	0.315649	0.313992	0.312335	0.310676
72	0.309017	0.307357	0.305695	0.304033	0.30237	0.300706	0.299041	0.297375	0.295708	0.29404
73	0.292372	0.290702	0.289032	0.287361	0.285688	0.284015	0.282341	0.280667	0.278991	0.277315
74	0.275637	0.273959	0.27228	0.2706	0.26892	0.267238	0.265556	0.263873	0.262189	0.260505
75	0.258819	0.257133	0.255446	0.253758	0.252069	0.25038	0.24869	0.246999	0.245307	0.243615
76	0.241922	0.240228	0.238533	0.236838	0.235142	0.233445	0.231748	0.23005	0.228351	0.226651
77	0.224951	0.22325	0.221548	0.219846	0.218143	0.21644	0.214735	0.21303	0.211325	0.209619
78	0.207912	0.206204	0.204496	0.202787	0.201078	0.199368	0.197657	0.195946	0.194234	0.192522
79	0.190809	0.189095	0.187381	0.185667	0.183951	0.182236	0.180519	0.178802	0.177085	0.175367
x	0	1	2	3	4	5	6	7	8	9
80	0.173648	0.171929	0.170209	0.168489	0.166769	0.165048	0.163326	0.161604	0.159881	0.158158
81	0.156434	0.15471	0.152986	0.151261	0.149535	0.147809	0.146083	0.144356	0.142629	0.140901
82	0.139173	0.137445	0.135716	0.133986	0.132256	0.130526	0.128796	0.127065	0.125333	0.123601
83	0.121869	0.120137	0.118404	0.116671	0.114937	0.113203	0.111469	0.109734	0.107999	0.106264
84	0.104528	0.102793	0.101056	0.09932	0.097583	0.095846	0.094108	0.092371	0.090633	0.088894
85	0.087156	0.085417	0.083678	0.081939	0.080199	0.078459	0.076719	0.074979	0.073238	0.071497
86	0.069756	0.068015	0.066274	0.064532	0.062791	0.061049	0.059306	0.057564	0.055822	0.054079
87	0.052336	0.050593	0.04885	0.047106	0.045363	0.043619	0.041876	0.040132	0.038388	0.036644
88	0.034899	0.033155	0.031411	0.029666	0.027922	0.026177	0.024432	0.022687	0.020942	0.019197
89	0.017452	0.015707	0.013962	0.012217	0.010472	0.0087265	0.0069813	0.0052360	0.0034907	0.0017453
90	0	0.0017453	0.0034907	0.0052360	0.0069813	0.0087265	0.010472	0.012217	0.013962	0.015707



۲

۲

NATURAL TANGENTS

×	0	1	2	3	4	5	6	7	8	9
0	0	0.0017453	0.003/1907	0.0052360		0.0087269	0.010472	0 012218	0.013964	0.015709
1	0 017455	0.0017400	0.0034507	0.0032500	0.0005014	0.026186	0.027933	0.029679	0.031426	0.033173
2	0.017455	0.015201	0.020047	0.022055	0.024433	0.020100	0.027555	0.025075	0.031420	0.050658
3	0.057921	0.054158	0.055909	0.05766	0.059411	0.061163	0.062915	0.064667	0.06642	0.068173
4	0.069927	0.071681	0.073435	0.07519	0.076946	0.078702	0.080458	0.082215	0.083972	0.08573
5	0.087489	0.089248	0.091007	0.092767	0.094528	0.096289	0.098051	0.099813	0.101576	0.10334
6	0.105104	0.106869	0.108635	0.110401	0.112168	0.113936	0.115704	0.117473	0.119243	0.121013
7	0.122785	0.124557	0.126329	0.128103	0.129877	0.131652	0.133428	0.135205	0.136983	0.138761
8	0.140541	0.142321	0.144102	0.145884	0.147667	0.149451	0.151236	0.153022	0.154808	0.156596
9	0.158384	0.160174	0.161965	0.163756	0.165549	0.167343	0.169137	0.170933	0.17273	0.174528
x	0	1	2	3	4	5	6	7	8	9
10	0.176327	0.178127	0.179928	0.181731	0.183534	0.185339	0.187145	0.188952	0.19076	0.19257
11	0.19438	0.196192	0.198005	0.19982	0.201635	0.203452	0.205271	0.20709	0.208911	0.210733
12	0.212557	0.214381	0.216208	0.218035	0.219864	0.221695	0.223526	0.22536	0.227194	0.229031
13	0.230868	0.232707	0.234548	0.23639	0.238234	0.240079	0.241925	0.243774	0.245624	0.247475
14	0.249328	0.251183	0.253039	0.254897	0.256756	0.258618	0.26048	0.262345	0.264211	0.266079
15	0.267949	0.269821	0.271694	0.273569	0.275446	0.277325	0.279205	0.281087	0.282971	0.284857
16	0.286745	0.288635	0.290527	0.29242	0.294316	0.296213	0.298113	0.300014	0.301918	0.303823
17	0.305731	0.30764	0.309552	0.311465	0.313381	0.315299	0.317219	0.319141	0.321065	0.322991
18	0.32492	0.32685	0.328783	0.330718	0.332656	0.334595	0.336537	0.338481	0.340428	0.342377
19	0.344328	0.346281	0.348237	0.350195	0.352156	0.354119	0.356084	0.358052	0.360022	0.361995
х	0	1	2	3	4	5	6	7	8	9
20	0.36397	0.365948	0.367928	0.369911	0.371897	0.373885	0.375875	0.377869	0.379864	0.381863
21	0.383864	0.385868	0.387874	0.389884	0.391896	0.39391	0.395928	0.397948	0.399971	0.401997
22	0.404026	0.406058	0.408092	0.41013	0.41217	0.414214	0.41626	0.418309	0.420361	0.422417
23	0.424475	0.426536	0.428601	0.430668	0.432739	0.434812	0.436889	0.438969	0.441053	0.443139
24	0.445229	0.447322	0.449418	0.451517	0.45362	0.455726	0.457836	0.459949	0.462065	0.464185
25	0.466308	0.468434	0.470564	0.472698	0.474835	0.476976	0.47912	0.481267	0.483419	0.485574
26	0.487733	0.489895	0.492061	0.494231	0.496404	0.498582	0.500763	0.502948	0.505136	0.507329
27	0.509525	0.511726	0.51393	0.516138	0.518351	0.520567	0.522787	0.525012	0.52724	0.529473
28	0.531709	0.53395	0.536195	0.538445	0.540698	0.542956	0.545218	0.547484	0.549755	0.55203
29	0.554309	0.556593	0.558881	0.561174	0.563471	0.565773	0.568079	0.57039	0.572705	0.575026
x	0	1	2	3	4	5	6	7	8	9
30	0.57735	0.57968	0.582014	0.584353	0.586697	0.589045	0.591398	0.593757	0.59612	0.598488
31	0.600861	0.603239	0.605622	0.60801	0.610403	0.612801	0.615204	0.617613	0.620026	0.622445
32	0.624869	0.627299	0.629734	0.632174	0.634619	0.63707	0.639527	0.641989	0.644456	0.646929
33	0.649408	0.651892	0.654382	0.6568//	0.659379	0.661886	0.664398	0.666917	0.669442	0.6/19/2
34	0.674509	0.677051	0.679599	0.682154	0.684714	0.687281	0.689854	0.692433	0.695018	0.69761
35	0.700208	0.702812	0.705422	0.708039	0.710663	0.713293	0.71593	0.718573	0.721223	0.723879
30	0.720543	0.729213	0.751009	0.734575	0.737204	0.739901	0.742000	0.745377	0.746096	0.750621
37	0.753554	0.750294	0.759041	0.701790	0.704556	0.705426	0.770104	0.001151	0.004021	0.778479
30	0.761260	0.7641	0.760922	0.769752	0.79259	0.795430	0.79629	0.8001151	0.804021	0.000090
39	0.809784	1	0.81558	0.010491	0.821409	0.824330 E	0.827272	0.830210	0.833109	0.83013
	0.8301	L 0.842078	0.845066	0.848062	4	0.854081	0.857104	0.860136	0.863177	9 0 866227
41	0.0391	0.042070	0.875434	0.878521	0.831619	0.884725	0.837104	0.800130	0.804103	0.807249
42	0.900404	0.903560	0.906745	0.070321	0.913125	0.916331	0.919547	0.922773	0.094105	0.9297249
43	0.932515	0.935783	0.939063	0.942352	0.945653	0.948965	0.952287	0.955621	0.958966	0.962322
44	0,965689	0,969067	0,972458	0,975859	0,979272	0,982697	0,986134	0,989582	0,993043	0,996515
45	1	1.0035	1.00701	1.01053	1.01406	1.01761	1.02117	1.02474	1.02832	1.03192

NA	TU	RAL	TAN	GEN	TS

46	1.03553	1.03915	1.04279	1.04644	1.0501	1.05378	1.05747	1.06117	1.06489	1.06862
47	1.07237	1.07613	1.0799	1.08369	1.08749	1.09131	1.09514	1.09899	1.10285	1.10672
48	1.11061	1.11452	1.11844	1.12238	1.12633	1.13029	1.13428	1.13828	1.14229	1.14632
49	1.15037	1.15443	1.15851	1.16261	1.16672	1.17085	1.175	1.17916	1.18334	1.18754
x	0	1	2	3	4	5	6	7	8	9
50	1.19175	1.19599	1.20024	1.20451	1.20879	1.2131	1.21742	1.22176	1.22612	1.2305
51	1.2349	1.23931	1.24375	1.2482	1.25268	1.25717	1.26169	1.26622	1.27077	1.27535
52	1.27994	1.28456	1.28919	1.29385	1.29853	1.30323	1.30795	1.31269	1.31745	1.32224
53	1.32704	1.33187	1.33673	1.3416	1.3465	1.35142	1.35637	1.36134	1.36633	1.37134
54	1.37638	1.38145	1.38653	1.39165	1.39679	1.40195	1.40714	1.41235	1.41759	1.42286
55	1.42815	1.43347	1.43881	1.44418	1.44958	1.45501	1.46046	1.46595	1.47146	1.47699
56	1.48256	1.48816	1.49378	1.49944	1.50512	1.51084	1.51658	1.52235	1.52816	1.534
57	1.53986	1.54576	1.5517	1.55766	1.56366	1.56969	1.57575	1.58184	1.58797	1.59414
58	1.60033	1.60657	1.61283	1.61914	1.62548	1.63185	1.63826	1.64471	1.6512	1.65772
59	1.66428	1.67088	1.67752	1.68419	1.69091	1.69766	1.70446	1.71129	1.71817	1.72509
x	0	1	2	3	4	5	6	7	8	9
60	1.73205	1.73905	1.7461	1.75319	1.76032	1.76749	1.77471	1.78198	1.78929	1.79665
61	1.80405	1.8115	1.81899	1.82654	1.83413	1.84177	1.84946	1.8572	1.86499	1.87283
62	1.88073	1.88867	1.89667	1.90472	1.91282	1.92098	1.9292	1.93746	1.94579	1.95417
63	1.96261	1.97111	1.97966	1.98828	1.99695	2.00569	2.01449	2.02335	2.03227	2.04125
64	2.0503	2.05942	2.0686	2.07785	2.08716	2.09654	2.106	2.11552	2.12511	2.13477
65	2.14451	2.15432	2.1642	2.17416	2.18419	2.1943	2.20449	2.21475	2.2251	2.23553
66	2.24604	2.25663	2.2673	2.27806	2.28891	2.29984	2.31086	2.32197	2.33317	2.34447
67	2.35585	2.36733	2.37891	2.39058	2.40235	2.41421	2.42618	2.43825	2.45043	2.4627
68	2.47509	2.48758	2.50018	2.51289	2.52571	2.53865	2.5517	2.56487	2.57815	2.59156
69	2.60509	2.61874	2.63252	2.64642	2.66046	2.67462	2.68892	2.70335	2.71792	2.73263
X	0	1	2	3	4	5	6	7	8	9
70	2.74748	2.76247	2.77761	2.79289	2.80833	2.82391	2.83965	2.85555	2.87161	2.88783
71	2.90421	2.92076	2.93748	2.95437	2.9/144	2.98868	3.00611	3.02372	3.04152	3.0595
72	3.07768	3.09606	3.11464	3.13341	3.1524	3.17159	3.191	3.21063	3.23048	3.25055
73	3.27065	3.29139	3.31210	2.5551/	2 5016	3.37394	3.39//1	3.41973	3.44202	3.40430
74	3 73205	3,51055	3 79/95	3.33701	3 83006	3 86671	3 80474	3 02316	3.06001	3.70010
76	4 01078	4 04081	4 07127	4 10216	4 1335	4 1653	4 19756	4 2303	4 26352	4 29724
77	4.33148	4.36623	4.40152	4.43735	4.47374	4.51071	4.54826	4.58641	4.62518	4.66458
78	4 70463	4 74534	4 78673	4 82882	4 87162	4 91516	4 95945	5 00451	5 05037	5 09704
79	5.14455	5.19293	5.24218	5.29235	5.34345	5.39552	5.44857	5.50264	5.55777	5.61397
x	0	1	2	3	4	5	6	7	8	9
80	5.67128	5.72974	5.78938	5.85024	5.91236	5.97576	6.04051	6.10664	6.17419	6.24321
81	6.31375	6.38587	6.45961	6.53503	6.61219	6.69116	6.77199	6.85475	6.93952	7.02637
82	7.11537	7.20661	7.30018	7.39616	7.49465	7.59575	7.69957	7.80622	7.91582	8.02848
83	8.14435	8.26355	8.38625	8.51259	8.64275	8.77689	8.9152	9.05789	9.20516	9.35724
84	9.51436	9.6768	9.84482	10.0187	10.1988	10.3854	10.5789	10.7797	10.9882	11.2048
85	11.4301	11.6645	11.9087	12.1632	12.4288	12.7062	12.9962	13.2996	13.6174	13.9507
86	14.3007	14.6685	15.0557	15.4638	15.8945	16.3499	16.8319	17.3432	17.8863	18.4645
87	19.0811	19.7403	20.4465	21.2049	22.0217	22.9038	23.8593	24.8978	26.0307	27.2715
88	28.6363	30.1446	31.8205	33.6935	35.8006	38.1885	40.9174	44.0661	47.7395	52.0807
88 89	28.6363 57.29	30.1446 63.6567	31.8205 71.6151	33.6935 81.847	35.8006 95.4895	38.1885 114.589	40.9174 143.237	44.0661 190.984	47.7395 286.478	52.0807 572.957

State Council of Educational Research and Training, Chennai-6

6

Higher Secondary Second Year Physics volume 2 List of Subject Experts in Textbook Writing

Domain Expert & Mentor

Prof. Rita John

Professor and Head, Department of Theoretical Physics University of Madras, Chennai.

Reviewers

Dr. V. N. Mani. Scientist E, Head (C-MET) Department of Electronic & Information Technology, Hyderabad, Government of India.

Prof. P. Ravindran

Dept. of. Physics, School of Basic and Applied Sciences, Central University of Tamil Nadu, Thiruvarur.

Dr. Rajeev Shesha Joshi Assistant Professor School of Physical Sciences, Central University of Karnataka.

Dr. Joe Jesudurai

Associate Professor Dean of Sciences, Department of Physics, Loyola College, Chennai-34.

Content Writers

Mr. C. Joseph Prabagar

Assistant Professor PG & Research Department of Physics, Loyola College, Chennai-34.

Dr. S. S.Naina Mohammed

Assistant Professor PG & Research Department of Physics, Government Arts College, Udumalpet, Tiruppur Dt - 642 126,

Dr. R Sugaraj Samuel

Assistant Professor PG & Research Department of Physics, The New College, Royapettah, Chennai-14.

Dr. P. Elangovan Assistant Professor PG & Research Department of Physics, Pachaiyappa's college, Chennai

Mr. T. Thamaraiselvan PGT, GBHSS, Aranthangi – 614 616 Pudukottai Dt

Content Readers

Dr. V. Sivamadhavi

Associate Professor Bharathi Women's Collage (A) Chennai

Mr. N. Thamaraikannan

PG Assistant, JGN Hr.Sec.School, Tambaram, Kanchipuram Dt

Dr. S. Ravikasi Venkatraman

PG Assistant, Govt. Hr. Sec.School, Semmancheri, Kanchipuram Dt

Mr. T. Subbiah

PG Assistant, Govt.Girls Hr.Sec. School, Achirupakkam, Kanchipuram Dt.

Mr.M.Palanichamy

Head Master, Government Hr. Sec. School Krishnarayapuram Karur Dt.

Tamil Translators

Mr. M. Palanikumar,

PGT,MNMSP Senthil Kumara Nadar HSS, Mallankinaru – 626 109 Virudhunagar Dt.

Mr. A. Ganesh

PGT, Sundaram GHSS, Thirumazhisai – 600 124 Thiruvallur Dt

Mr. S. Sritharan

PGT, GHSS, Annasalai Rasipuram - 637408 Namakkal Dt.

Dr. K. Vasudevan

PGT, Govt.ADW.Hr.Sec.School, Kalangani – 637 014, Namakkal Dt

Mr. E. Elangovan

PGT, J. G. GHSS, Manali New Town – 600 103 Thiruvallur Dt.

ICT Coordinators

Mr.G.Bergin PG Assistant (Physics), GBHSS, Sayalgudi, Ramanathapuram Dt.

Mr. D. Jeyaselvan BT Assistant (Science),GHS, Varagur, Thanjavur Dt.

312

ICT- Animation & Video Developer

Mr. Kennedy Bernajsha

Kennedy Bernajsha Lemurians Media F2 Padmavaithi Flat, Thilaiganga Nagar 7th Street, Nanganallur, Chennai.

SCERT Subject Coordinators

Mrs. D. Shanmugasundari Graduate Assistant P.U.M.School, Melathulukkankulam Kariyapatti Union, Virudhunagar Dt.

Mr. G. Arulraja

Graduate Assistant MKV Govt.Boys.Hr.Sec.School Arani,Thiruvallur Dt

QR CODE Management Team

R. Jaganathan SGT, PUMS - Ganesapuram, Polur , Thiruvannamalai.

S. Albert Valavan Babu

B.T, G.H.S, Perumal Kovil, Paramakudi, Ramanathapuram.

M. Murugesan, B.T. Asst., PUMS., Pethavelankottagam, Muttupettai, Thiruvarur.

Typist Mrs.D.Kavitha

Art and Design Team

Layout Udhaya info, Chennai

Illustration K. Sasi Kumar

In-House QC - Asker Ali

Co-ordination Ramesh Munisamy

This book has been printed on 80 G.S.M. Elegant Maplitho paper. Printed by offset at: